N74. 10893

MS-I-73:-01

October 1973



CASE FILE COPY

FY 1973 SCIENTIFIC AND TECHNICAL REPORTS, ARTICLES, PAPERS, AND PRESENTATIONS

Management Services Office

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION



ABSTRACT

This document presents formal NASA technical reports, papers published in technical journals, and presentations by MSFC personnel in FY 73. It also includes papers of MSFC contractors.

After being announced in STAR or C STAR, all of the NASA series reports listed may be obtained from the Scientific and Technical Information Facility, P.O. Box 33, College Park, Maryland 20740.

The information in this report will be of value to the scientific and engineering community in determining what information has been published and what is available.

FY 1973 SCIENTIFIC AND TECHNICAL REPORTS, ARTICLES, PAPERS, AND PRESENTATIONS

Scientific and Technical Information Division Management Services Office

FOREWORD

In accordance with the NASA Space Act of 1958 the MSFC has provided for the widest practicable and appropriate dissemination of information concerning its activities and the results thereof.

Since July 1, 1960, when the George C. Marshall Space Flight Center was organized, the reporting of scientific and engineering information has been considered a prime responsibility of the Center. Our credo has been that "research and development work is valuable, but only if its results can be communicated and made understandable to others."

The N numbers shown for the reports listed are assigned by the NASA Scientific and Technical Information Facility, College Park, Maryland, indicating that the material is unclassified and unlimited and is available for public use. The N number should be cited when requesting a document.

GEORGE C. MARSHALL SPACE FLIGHT CENTER Marshall Space Flight Center, Alabama

FY 1973 SCIENTIFIC AND TECHNICAL REPORTS, ARTICLES, PAPERS, AND PRESENTATIONS

TABLE OF CONTENTS

	Page
NASA TECHNICAL MEMORANDA	1
NASA TECHNICAL NOTES	28
NASA TECHNICAL REPORTS	36
NASA SPECIAL PUBLICATIONS	39
CONTRACTOR REPORTS	40
MSFC PAPERS CLEARED FOR PRESENTATION	79

(Note: The following four reports were published but not listed in the FY 1972 edition of this publication.)

TM X-64649 June 9, 1972 Precise Linear Sun Sensor. Danny D. Johnston. Astrionics Laboratory.

N72-29468

An evaluation of the precise linear sun sensor relating to future mission applications was performed. The test procedures, data, and results of the dual-axis, solid-state system are included. Brief descriptions of the sensing head and of the system's operational characteristics are presented. A unique feature of the system is that multiple sensor heads with various fields of view may be used with the same electronics.

TM X-64664 May 24, 1972

Design of a Mach 8.0 Axisymmetric

Nozzle for a Hypersonic Test Facility.

Joseph L. Sims and Robert F. Elkin.

Aero-Astrodynamics Laboratory.

N72-27273

An axisymmetric nozzle has been designed to produce test section flow at a Mach number of 8.0 for use in a hypersonic test facility at MSFC. Nominal design conditions used to calculate the viscous correction to the wall contour were selected from the results of a parametric boundary layer investigation so that the widest possible range of satisfactory. operating conditions could be obtained. Coordinates for the nozzle are presented in a tabular form suitable for design and manufacturing. The basic analysis techniques have been used to generate results to compare with experimental data from a facility at Langley Research Center. The agreement reasonably good.

TM X-64666 May 30, 1972
Research Achievements Review. Vol. IV,
No. 5. Quality and Reliability Assurance
Research at MSFC. J. B. Beal, M. C.
McIlwain, T. F. Morris, M. J. Berkebile,
and F. Villella. Science and Engineering.
N72-27516

TM X-64669 December 1, 1971 Vibration Manual. Claude Green, ed. Astronautics Laboratory. N72-28901

This document provides guidelines of the methods and applications used in vibration technology at MSFC. Its purpose is to provide a practical tool for coordination and understanding between industry and government groups concerned with vibration of systems and equipments. Topics covered include measuring, reducing, analyzing, and methods for obtaining simulated environments and formulating vibration specifications. Other sections cover methods for vibration and shock testing, theoretical aspects of data processing, vibration response analysis, and techniques of designing for vibration.

TM X-2635 November 1972
Chemical Processing Manual. F. J.
Beyerle. Process Engineering Laboratory.
N73-14117

This manual presents all documents directly related to chemical processes that were prepared by the Product Engineering and Process Technology Laboratory and are pertinent to the continuing technology of spacecraft development. Chemical processes presented in this document include cleaning, pickling, surface finishes, chemical milling,

plating, dry film lubricants, and polishing. All types of chemical processes applicable to aluminum, for example, are to be found in the Aluminum Alloy Section. There is a separate section for each category of metallic alloy plus a section for non-metals, such as plastics. The refractories, super-alloys and titanium, are prime candidates for the Space Shuttle; therefore, the chemical processes applicable to these alloys are contained in individual sections of this manual.

TM X-64671 June 8, 1972
Probability of Satellite Collision. James
W. McCarter. Aero-Astrodynamics
Laboratory. N72-29833

A method is presented for computing the probability of a collision between a particular artificial earth satellite and any one of the total population of earth satellites. The collision hazard incurred by the proposed modular Space Station is assessed using the technique presented. The results of a parametric study to determine what type of satellite orbits produces the greatest contribution to the total collision probability are presented. Collision probability for the Space Station is given as a function of Space Station altitude and inclination. Collision probability was also parameterized over miss distance and mission duration.

TM X-64672 March 1972
Flat Conductor Cable Applications.
W. Angele. Process Engineering Laboratory.
N72-32222

This report contains brief descriptions, supplemented with artwork, of some of the numerous applications of flat conductor cable

(FCC) systems. Both Government and commercial uses have been considered, with described applications designated as either aerospace, military, or commercial. The document is designed to illustrate the number and variety of ways in which FCC is being applied and considered for future designs.

TM X-64673 April 13, 1972
Pulse Performance Analysis for Small
Hypergolic Propellant Rocket Engines.
Gerald W. Smith and Richard H. Sforzini.
Astronautics Laboratory. N72-24823

Small rocket engine tests were conducted for the purpose of obtaining pulse performance data to aid in preliminary design and evaluation of attitude control systems. Both monopropellant and hypergolic bipropellant engines of thrust levels from 1 to 100 lbs were tested. The performance data for the hypergolic propellant rockets are compared with theoretical performance calculated from idealized chamber filling and evacuation characteristics. Electromechanical delays in valve response and heat transfer characteristics were found to cause substantial deviation between theoretical and test performance. The theoretical analysis is modified to obtain a semi-empirical model for hypergolic propellant rockets which is demonstrated to be reasonably accurate for two different engine configurations over a considerable range of duty cycles.

TM X-64674 August 1972 A Catalogue of Normalized Intensity Functions and Polarization From a Cloud of Particles with a Size Distribution of α^{-4} . P. D. Craven and G. A. Gary. Space Sciences Laboratory. N72-28717

The Mie theory of light scattering by spheres is used to calculate the scattered resulting from intensity functions scattering in a polydispersed collection of spheres. The distribution used behaves according to the inverse fourth power law; graphs and tables for the angular dependence of the intensity and polarization of this law are given. The effects of the particle size range and the integration increment are investigated.

TM X-64675 June 27, 1972 Space Shuttle Earth Orbital Rendezvous Targeting Techniques for Near Circular Target Satellite Orbits. A. W. Deaton. Aero-Astrodynamics Laboratory.

N72-28835

This report develops the targeting techniques required to achieve space shuttle rendezvous with a target satellite in a near circular orbit.

TM X-64676 May 26, 1972
Feasibility Study – Replacement of the Inoperative Decommutating Buffer Subsystem for the Instrumentation Checkout Complex in the Quality and Reliability Assurance Laboratory. James W. Hilliard. Computation Laboratory.

N72-28458

The intent of this document is to describe a general purpose computer system that is necessary for replacement of the present inoperative signal decommutator special purpose computer subsystem of the Instrumentation Checkout Complex in the Quality and Reliability Assurance Laboratory. The present decommutator subsystem has a very poor history of reliability and since April 1970,

it has become inoperative because the core memory cannot be repaired. Functions of the present signal decommutator subsystem are to demultiplex, record in real-time, playback in real-time, and output to the SDS-930 control computer for analysis of the telemetry data. Recommendations for replacement of the inoperative telemetry decommutator subsystem are for the purchase of a mini-computer that is described in this document. A review of the General Service Administration Automatic Data Processing Equipment (ADPE) Availability List disclosed general purpose or special purpose equipment that could meet telemetry decommutator requirements.

TM X-64677 May 1972
Comets and Asteroids – A Strategy for Exploration. Comet and Asteroid Mission Study Panel. N72-33831

Many of the asteroids probably formed near the orbits where they are found today. They accreted from gases and particles that represented the primordial solar system cloud at that location. Comets, in contrast to asteroids, probably formed far out in the solar system, and at very low temperatures; since they have retained their volatile components they are probably the most primordial matter that presently can be found anywhere in the solar system. Exploration and detailed study of comets and asteroids, therefore, should be a significant part of NASA's efforts to understand the solar system. A comet and asteroid program should consist of six major types of projects: ground-based observations; Earthobservations; flybys; rendezvous; orbital landings; and sample returns. A preliminary listing of the primary objectives of each project

type is found in Table I. The Comet and Asteroid Mission Study Panel recommends that planning and implementation of these six types of projects be initiated as soon as practical. Missions of the flyby type could be accomplished with existing conventional propulsion systems. Missions of the other types, however, must be carried out with electric propulsion systems, such as solar-electric propulsion. Some of the scientific instruments for the recommended observations could be adopted from previous planetary and interplanetary projects; some would represent new developments.

TM X-64678 May 15, 1972

A Preliminary Investigation of the Environmental Control and Life Support Subsystems (EC/LSS) for Animal and Plant Experiment Payloads. Hubert B. Wells. Preliminary Design Office, Program Development. N72-29050

This report presents a preliminary study of the environmental control and life support subsystems (EC/LSS) necessary for an earth orbital spacecraft to conduct biological experiments. The primary spacecraft models available for conducting these biological experiments are the Space Shuttle and Modular Space Station. The experiments would be housed in a separate module that would be contained in either the Shuttle payload bay or attached to the Modular Space Station. This would be manned only experiment-related tasks, and would contain a separate EC/LSS for the crew and animals. Metabolic data have been tabulated on various animals that are considered useful for a typical experiment program. The minimum payload for the 30-day Space Shuttle module was found to require about the equivalent of a

one-man EC/LSS; however, the selected two-man Shuttle assemblies will give a growth and contingency factor of about 50 percent. The maximum payloads for the Space Station mission will require at least a seven-man EC/LSS for the laboratory colony and a nine-man EC/LSS for the centrifuge colony. There is practically no room for growth or contingencies in these areas.

TM X-64679

Variational Differential Equations for Engineering Type Trajectories Close to a Planet With an Atmosphere. E. D. Dickmanns. Aero-Astrodynamics Laboratory.

N72-27891

A model for trajectory computations for engineering-type application is described. The differential equations for the adjoint variables are derived and coded in FORTRAN. The program is written in a form to either take into account or neglect thrust, aerodynamic forces, planet rotation and oblateness, and altitude dependent winds.

TM X-64680 March 6, 1972 HEAO Star Tracker Search Program. William J. Weiler. Preliminary Design Office, Program Development.

N72-28665

The High Energy Astronomy Observatory (HEAO) requires a highly accurate and flexible control system to accommodate its scientific payload. One of the critical elements of this system is the star tracker subsystem, which defines an accurate three-axis attitude reference. A digital computer program has been developed to evaluate the ability of a particular star tracker configuration to meet the

requirements for attitude reference at various vehicle orientations. Used in conjunction with an adequate star catalog, this program provides information availability of stars for each tracker and on the ability of the system to maintain three-axis attitude reference throughout a representative sequence of vehicle orientations. This program was developed to provide information necessary for the selection of baseline and possible alternate star tracker configurations for the HEAO-C mission. It could be adapted, however, to other missions which utilize star tracker systems.

TM X-64681 July 5, 1972
Apollo 15 Contamination Photography.
R. J. Naumann. Space Sciences Laboratory. N72-29839

The problem of optical contamination in the form of particulates in the vicinity of a spacecraft has been a source of concern for any astronomical experiment that performed in sunlight. This concern prompted a photographic photometric experiment on Apollo 15 to measure the brightness of the residual contamination cloud as well as the cloud produced by dumping waste water overboard. An upper limit of $10^{-12.3}$ B_O (B_O designates the brightness of the solar disc) was placed on the residual cloud at a 90-deg sun angle, which is comparable to the zodiacal light. The brightness of the cloud produced by the waste dump was estimated to be 10^{-9.2} Bo. It was observed to decrease rapidly to Bo in minutes, then fluctuate in 10-11.6 brightness for at least 25 minutes as additional material left the spacecraft. The cloud was observed to consist of individually resolved particle tracks estimated to be particles ranging from millimeters to centimeters in diameter in addition to a background of unresolved particles with an average diameter of 10.5 microns. Most of the tracks proceeded in straight-line paths from the dump nozzle. Several tracks violated this direction, apparently having been scattered by collisions. A few tracks appeared to have definite curvatures, which are believed to be caused by charged particle interactions.

TM X-64682 August 2, 1972

A Mechanical Property and Stress
Corrosion Evaluation of Custom 455
Stainless Steel Alloy. J. W. Montano.
Astronautics Laboratory. N73-11509

This report is a continuation of the work reported in NASA TM X-53665, dated October 20, 1967. Presented in this report are the mechanical and stress corrosion properties of vacuum melted Custom 455 stainless steel alloy bar [1.0-inch (2.54 cm) diameter] and sheet [0.083-inch (0.211 cm) thick] material aged at 950°F (510°C), 1000°F (538°C), and 1050°F (566°C). Low temperature mechanical properties were determined at temperatures of 80°F (26.7°C), 0°F (-17.8°C), -100°F (-73°C), and -200°F (-129°C). For all three aging treatments, the ultimate tensile and 0.2 percent offset yield strengths increased with decreasing test temperatures while the elongation held fairly constant down to -100°F (-73°C) and decreased at -200°F (-129°C). Reduction in area decreased moderately with decreasing temperature for the longitudinal round [0.250-inch (0.635 cm) diameter] specimens. Notched tensile strength and charpy V-notched impact strength decreased with decreasing test temperature. For all three aging treatments, no

failures were observed in the unstressed specimens or the specimens stressed to 50, 75, and 100 percent of their yield strengths for 180 days of alternate immersion testing in a 3.5 percent NaCl solution. As indicated by the results of tensile tests performed after alternate immersion testing, the mechanical properties of Custom 455 alloy were not affected by stress or exposure under the conditions of this evaluation.

TM X-64683 July 1972
Optical Depths in the Interstellar and Intergalactic Media. Klaus Schocken.
Space Sciences Laboratory. N72-29836

Optical depths of the interstellar and intergalactic media for supernova remnants, stars, and galaxies are presented in tabular form.

TM X-64684 August 18, 1972
Fundamental Concepts of Structural
Loading and Load Relief Techniques for
the Space Shuttle. R. S. Ryan, D. K.
Mowery, and S. W. Winder. AeroAstrodynamics Laboratory. N72-31881

The prediction of flight loads and their potential reduction, using various control system logics for the Space Shuttle vehicles, is very complex. Some factors not found on previous launch vehicles that increase the complexity are large lifting surfaces, unsymmetrical structure, unsymmetrical aerodynamics, trajectory control system coupling, and large aeroelastic effects. This paper discusses these load-producing factors and load-reducing techniques. Identification of potential technology areas is included.

TM X-64685 September 1, 1972

Manufacture and Quality Control of Interconnecting Wire Harnesses. MSFC AD

HOC Committee. Quality and Reliability

Assurance Laboratory.

Vol. I N72-33206 Vol. II N72-33207 Vol. III N72-33208 Vol. IV N72-33209

This document has been prepared for use as a standard for manufacture, installation, and quality control of eight types of interconnecting wire harnesses. It is made up of four volumes under one reference number to simplify control and referral on contracts. Each volume can be independently employed should only harnesses within one volume be of interest. The processes, process controls, and inspection and test requirements reflected are based on (a) acknowledgment of harness design requirements defined in MSFC document 40M39582. "Harness. Electrical Design Standard," (b) acknowledgment of harness installation requirements defined in MSFC-SPEC-494. "General Specification Installation of Harness Assembly (Electrical Wiring), Space Vehicle," (c) identification of the various parts, materials, etc, utilized in harness manufacture, and (d) formulation of a typical manufacturing flow diagram for identification of each manufacturing and quality control process, operation, inspection, and test. The document covers interconnecting wire harnesses defined in the design standard. Volume I covers type I, enclosed in fluorocarbon elastomer convolute tubing; type II, enclosed in TFE convolute tubing lined with fiberglass braid; type III, enclosed in TFE convolute tubing; type V, combination of

types III and IV: Volume II covers type IV, open bundle (not enclosed): Volume III covers type VI, enclosed in TFE heat shrink tubing; type VII, flexible armored: and Volume IV covers type VIII, flat conductor cable. Volume breadth covers installations of groups of harnesses in a major assembly and the associated post installation inspections and electrical tests. All volumes are TM X-64685. Knowledge gained through experience on the Saturn V Program coupled with recent advances in techniques, materials, and processes have been incorporated into this document.

TM X-64686 October 1972
Reliability of Hybrid of Microcircuit
Discrete Components. Robert V. Allen
and Salvadore V. Caruso. Astrionics
Laboratory. N73-16208

Hybrid microcircuit technology has rapidly become a standard technique in development and fabrication of electronic hardware. The most obvious reasons for the rapid acceptance of hybrids are small size, reduced weight and higher reliability. The reliability of a hybrid microcircuit determined by factors such as wire bonding, interconnection techniques, thick- and thinfilm processing, discrete component mounting, and hermetic sealing. Most of these factors can be controlled during fabrication cycles with proper process controls. However, since the hybrid manufacturer has little or no control on design and fabrication of discrete these devices have the most components, paramount effect on microcircuit reliability. Therefore, each hybrid manufacturer must establish criteria for selection, qualification, and screening of discrete devices. This report

details the data accumulated during 4 years of research and evaluation of ceramic chip capacitors, ceramic carrier mounted active devices, beam-lead transistors, and chip resistors. Life and temperature coefficient test data, and optical and scanning electron microscope photographs of device failures are presented and the failure modes are described. given Particular interest is to discrete component qualification, power burn-in, and procedures for testing and screening discrete components. Burn-in requirements and test data will be given in support of 100 percent burn-in policy on all NASA flight programs.

TM X-64687 June 15, 1972

Monolithic Microcircuit Techniques.

Bobby W. Kennedy. Astrionics

Laboratory. N72-30232

Contained in this report are brief discussions of the techniques used at MSFC and in industry to make dielectric and metal thin-film depositions for monolithic circuits. Silicon nitride deposition and the properties of silicon nitride films are discussed. Deposition of dichlorosilane and thermally grown silicon dioxide are discussed. The deposition and thermal densification of borosilicate, aluminosilicate, and phosphosilicate glasses are discussed. Metallization for monolithic circuits and the characteristics of thin films are also included.

TM X-64688 August 1972
Mask and Pattern Characteristics. Donald
E. Routh. Astrionics Laboratory.

N72-31288

This document provides the individuals planning to use the mask and pattern facility

with detailed information on equipment accuracy, limitations, and pattern-making capabilities. It also provides insight into potential areas of pattern applications, the sequence of mask making, as well as the possible inputs and outputs available to the user.

TM X-64689 September 1972
Actuator Participation in a Bending
Mode Identification System. Zack
Thompson and Perry Davis. Astrionics
Laboratory. N72-33380

A hydraulic actuator designed for a thrust vector control system used as a shaker for a vehicle to determine the bending mode frequencies is described. The actuator is used as the prime mover and the frequency sensor for the flexible vehicle in a test tower. Advantages in using the actuator piston position with respect to a commanded position to obtain the bending mode frequencies are shown.

TM X-64690 August 1972 Chemical Propulsion Research at MSFC. Research Achievements Review. Vol. IV, No. 6. Science and Engineering.

N73-12840

TM X-64691 June 30, 1972
Fabrication and Testing of Scatter Plates
for Interferometry. Joseph J. Pour, Sr.,
and John R. Pitts. Astrionics Laboratory.
N72-32473

Scatter plate interferometry has become a reliable method of measuring surface configurations of telescope mirrors and other optical components. The scatter plate used in an instrument should be of optimum quality if the surface it is being used to measure is to be of high accuracy. Tests were performed and results show that, although many scatter plates would function, few were of the optimum quality necessary. These few were of the 180 grit group, using 35- and 30-s exposures, which are figures derived from calculations.

TM X-64692 January 31, 1972

Experiment Pointing Control During
Space Shuttle Sortie Missions. P. D.
Nicaise. Preliminary Design Office,
Program Development. N73-12892

The pointing and stability problems of the Sortie mission are examined from the standpoint of basic Shuttle capability and the techniques that could be used for improving this capability to accommodate a maximum number of experiments. Augmentation of the basic Shuttle control system is proposed to provide an acceptable pointing environment. A stabilized reference base is recommended as a general pointing instrument for certain earth observation and astronomy experiments. Simulation results are presented which were obtained by modeling the Skylab Experiment Pointing Control (EPC) system on a thruster controlled Shuttle.

TM X-64693 August 2, 1972
Two Different Approaches for a Control
Law of Single Gimbal Control Moment
Gyros. Werner O. Schiehlen. Astrionics
Laboratory. N72-31660

In the field of momentum exchange attitude control systems, single gimbal control moment gyros (SGCMG's) are of increasing

interest. This report presents a gimbal angle approach and a gimbal rate approach for the SGCMG control law including the singularity avoidance. Both approaches are compared and some illustrative examples are given.

TM X-64694 September 25, 1972 Closed-Form Solutions for Atmospheric Flight with Applications to Shuttle Guidance. Hugo L. Ingram. Aero-Astrodynamics Laboratory. N73-11677

Closed-form solutions for the motion of a rocket-powered vehicle during atmospheric ascent and closed-form solutions unpowered atmospheric reentry are developed. These closed-form solutions are then used to develop a simplified guidance scheme and to develop a variation-ofparameters integration of more accurate equations of motion with the closed-form solutions as base solutions. The variation-ofparameters integration of the more accurate equations of motion also allows the transition partial derivative matrices associated with these equations to be easily developed. Then the partial derivative transition matrices are used to develop a guidance scheme based on the more accurate equations of motion instead of the less accurate closed-form solutions.

TM X-64695 August 1972
Flat Conductor Cable Connectors with
Individually Sealed Contacts. W. Angele.
Process Engineering Laboratory.

N72-32231

The report contains information on the latest NASA/MSFC flat conductor cable connectors, a series with individually sealed

contacts. Data and artwork are concerned with connector historical development, design requirements, design description, and test and cost data.

TM X-64696 August 15, 1972
User's Manual for MSFC Mask and
Display Program. Donald Routh and
Dae-Shik Woo. Astrionics Laboratory.

N72-33193

This report is intended to serve as the User's Manual for the MSFC Mask and Display Program. All program options and a detailed definition of the format of each input card (with examples) are given. Output options and their applications are detailed. A listing of the main program is provided and all update points are explained. information required for a designer/draftsman (for program use) is provided, and it will not be necessary to become intimately familiar with the internal operations to effectively use the extensive capability it has to offer.

TM X-64697 September 1, 1972
DDP-116 General Digital Filtering. Jack
A. Jones and Ronald J. Graham. Computation Laboratory. N72-33189

This report describes the methods for calibrating, selecting filter weights, filtering, and computing filter response functions. These methods are computed on a Statistical Analyzer (STAN) system with a Honeywell DDP-116 Central Processor. The following filter types are computed:

- 1. All Pass
- 2. Low Pass
- 3. High Pass

- 4. Band Pass
- 5. Band Rejection
- 6. Derivative.

TM X-64698

July 1972

The Pseudonoise Test Set: Communication System's Performance Evaluation Based Upon rms Error Testing. G. R. Wallace, S. S. Gussow, W. E. Salter, and G. D. Weathers. Astrionics Laboratory.

N73-12146

A pseudonoise (PN) test set has been built to provide a relatively easy means of accurately determining the end-to-end rms error introduced by a communication system when subjected to wideband data. It utilizes a filtered pseudorandom sequence generator as wideband data source, providing convenient means for digitally delaying the input reference signal for comparison with the distorted test communication system output. In addition to providing a means to measure the end-to-end rms error and the average delay of a communication system, the PN test set also provides a means to determine the tested system's impulse response and correlation function. The theory of PN testing is discussed in detail along with the most difficult aspects of implementation, of matched filter pairs. Both analytical and empirical results are reported which support the contentions that this is an accurate and practical way to acquire figures merit for complete communication systems.

TM X-64699 October 4, 1972

Development of a Container for Handling, Testing, and Storing Discrete Microelectronic Components. George L. Filip and Salvadore V. Caruso. Astrionics Laboratory. N72-33485

A container has been developed for handling, testing, burning-in, and storing discrete microelectronic components without removal from the protective package. The package was designed to accommodate the Leadless Inverted Device (LID) and other carrier-mounted active devices and chip-type discrete resistors and capacitors. Before the indicated development, components were handled and tested in various ways, some of which resulted in damage or contamination. The basic design of the container utilizes precision-machined printed circuit boards and chemically milled (photoetched) contact springs. Included in this design for protection is an O-ring-sealed cover. Methods of fabrication and limitations of the current hardware are presented. Current applications of and possible extensions to the technology are discussed.

TM X-64700 March 14, 1972
Experimental Evaluation of the Skylab
Orbital Workshop Ventilation System
Concept. Steve L. Allums, Leon J.
Hastings, and James T. Ralston. Astronautics Laboratory. N73-16875

Extensive testing was conducted to evaluate the Orbital Workship ventilation concept. Component tests were utilized to determine the relationship between operating characteristics at 1 and 0.34 atm. System tests were conducted at 1 atm within the Orbital Workshop full-scale mockup to assess delivered volumetric flow rate and compartment air velocities. Component tests with the Anemostat circular diffusers (plenum- and duct-mounted) demonstrated that the diffuser produced essentially equivalent patterns and velocities in 1- and 0.34-atm environments. The tests also showed that the pressure drop across the diffuser could be

scaled from 1 to 0.34 atm using the atmosphere pressure ratio. Fan tests indicated that the performance of a multiple, parallelmounted fan cluster could be predicted by summing the single-fan flow rates at a given ΔP . The fan volumetric flow rate and the Orbital Workshop system flow rate at 28 V. 1 atm are equivalent to the flow rates at 26 V, 0.34 atm. The shutdown of one fan in a four-fan cluster resulted in a flow decrease of approximately 40 percent because of the backflow through the inoperative fan. For normal operation at 28 V, the average air velocity in the crew quarters was 6.1 to 15.2 m/min (20 to 50 ft/min) depending upon diffuser flow-pattern. The average air velocity in the forward plenum could be varied from 4.6 to 9.1 m/min (15 to 30 ft/min) with the crew quarters diffusers or from 9.1 to 12.2 m/min (30 to 40 ft/min) with the use of three portable fans. The portable fans could supply ≥ 30.5 m/min (100 ft/min) to localized areas.

TM X-64701 October 19, 1972

The Effect of Hot Salt on the Mechanical Properties of Several Superalloys. E. E. Nelson. Astronautics Laboratory. N73-11510

The effect of sodium chloride on unstressed, transverse, tensile, metal specimens at elevated temperatures has been determined. Results indicate, under the conditions of this test, that the mechanical properties of Inconel 718, René 41, Titanium base alloy 13V-11Cr-3Al, Hastelloy X, HS25 (L605), HS188, and TDNiCr suffer degradation in tensile strength and ductility due to hot-salt exposure.

TM X-64702 October 15, 1972
Ultrasonic Scanning System for Inspection of Brazed Tube Joints. J. L. Haynes and N. A. Maurer. Quality and Reliability Assurance Laboratory.

N73-11445

Described herein is the Ultrasonic Scanning System used to inspect and evaluate in-place brazed tube joints. Because of the expanding use of brazed fittings in the aerospace field the Ultrasonic Scanning System was designed, developed, and built especially for nondestructive testing. It was selected because of its known response to brazing defects not associated with material density changes. The developed scan system is capable of scanning brazed joints in union, tee, elbow, and cross configuration 3/16-inch through 5/8-inch diameters. The system is capable of detecting brazed defects as small as 0.008 by 0.010 inch which the 0.015-inch diameter defect exceeds resolution required by specification. brazed tube scanner ultrasonic recommended for the evaluation of all brazed tube joints that are within its dimensional capabilities and for which an inspection is desired. This recommendation is based upon the in-place scanning and the rapid inspection time capabilities of the system and the innate ability of ultrasonic test methods to detect defects which are not related to material density changes.

TM X-64703 November 6, 1972

Maskmaking Facilities at the Marshall
Space Flight Center. Donald E. Routh.
Astrionics Laboratory. N73-10284

This report describes the research and development maskmaking facilities at the Astrionics Laboratory of the Marshall Space Flight Center. Information is provided on the level of cleanliness and the environmental control within the various work areas. The available equipment and its function in the maskmaking process are detailed. Sufficient information is provided so that a competent clean-room builder could duplicate the facility capabilities.

TM X-64704 October 13, 1972
Systems Simulation for an Airport
Trailing Vortex Warning System. Harold
B. Jeffreys. Aero-Astrodynamics
Laboratory. N73-12267

This report documents the approach, development, and limited system studies associated with a system simulation for an Airport Trailing Vortex Warning System (ATVWS). It attempts to show the usefulness of a systems engineering approach to the problem of developing a system, as dictated by aircraft vortices, which will increase air-traffic flow in the takeoff/landing corridors of busy airports while maintaining the required safety factor for each operation. It is felt that the development and integration of a total system simulation computer program are essential to provide the system designers a way to develop proper and realistic ATVWS requirements to meet the objectives of decreasing aircraft spacings on takeoff and landing while maintaining an adequate safety margin. This report documents the capabilities (assumptions and limitations) provided by the Total System Simulation Model. The simulation provides capability of investigating potential the

problem areas at a fraction of the cost that would be involved in hardware tests only. The simulation program has been developed in a modular form which permits new, more sophisticated component models, when they become available and are required, to be incorporated into the program with a minimum of program modifications. This report documents a limited system study that has been performed using this Total System Simulation Model. The resulting preliminary system requirements, conclusions, and recommendations are given in Section V.

TM X-64705 April 1972
A Cosmic X-Ray Astronomy
Bibliography: The Astrophysical Journal,
1962 to 1972. Robert M. Wilson. Space
Sciences Laboratory. N73-11869

This report presents the results of a survey of the Astrophysical Journal for the time period January 1962 through March 1972 (volumes 135-172). Some 395 references are contained within this document related to cosmic X-ray astronomy.

TM X-64706 September 30, 1972
Assessment of and Standardization for Quantitative Nondestructive Testing.
Robert W. Neuschaefer and James B.
Beal. Quality and Reliability Assurance Laboratory.
N73-14483

This document assesses present capabilities and limitations of Nondestructive Testing (NDT) as applied to aerospace structures during design, development, production, and operational phases. It will help determine what useful structural quantitative and qualitative data may be provided

from raw materials to vehicle refurbishment. This assessment considers metal alloy systems and bonded composites presently applied in active NASA programs or strong contenders for future use. Quantitative and qualitative data has been summarized from recent literature, and in-house information, and presented herein along with a description of those structures or standards where the information was obtained. Examples, in tabular form, of NDT technique capabilities and limitations have been provided. NDT techniques discussed and assessed were radiogultrasonics. penetrants. thermal. acoustic, and electromagnetic. Quantitative data is sparse; therefore, obtaining statistically reliable flaw detection data must be strongly The new requirements for emphasized. reusable space vehicles have resulted in highly efficient design concepts operating in severe environments. This increases the need for quantitative NDT evaluation of selected structural components, the end item and during refurbishment structure, operations.

TM X-64707 October 27, 1972

Fast Digital Noise Filter Capable of
Locating Spectral Peaks and Shoulders.

T. R. Edwards and R. D. Knight. Space
Sciences Laboratory. N73-12212

Experimental data frequently have a poor signal-to-noise ratio which one would like to enhance before analysis. With the data in digital form, this may be accomplished by means of a digital filter. A fast digital filter based upon the principle of least squares and using the techniques of convoluting integers is described. In addition to smoothing, this filter also is capable of accurately and

simultaneously locating spectral peaks and shoulders. This technique has been adapted into a computer subroutine, and results of several test cases are shown, including mass spectral data and data from a proportional counter for the High Energy Astronomy Observatory.

TM X-64708

September 1972

An Automatic Data Acquisition System for the 150-Meter Ground Winds Tower Facility, Kennedy Space Center. Wilson B. Traver, Jr., Thomas E. Owen, and Dennis W. Camp. Aero-Astrodynamics Laboratory.

This report summarizes the design concepts and operational functions of an automatic meteorological data acquisition system for use with the NASA 150-meter ground winds tower at Kennedy Space Center. The technical approach and system specifications are presented in a generalized manner to give a clear overall view of the automatic system and to suggest methods and guidelines for using similar digital systems in other applications. Samples of the output meteorological data are illustrated together with brief discussions of their applications. References are given for additional details on the 150-meter tower structure as well as the engineering development and computer software programs associated with the automatic system.

TM X-64709

Analyses of Solar Viewing Time, Beta Angle, and Doppler Shift for Solar Observations from the Space Shuttle.

Judith P. Brandon. Mission and Payload Planning Office, Program Development.

N73-14840

Studies of solar physics phenomena are aided by the ability to observe the Sun from Earth orbit without periodic occultation. This report presents charts for the selection of suitable orbits about the Earth at which a spacecraft is continuously illuminated through a period of a few days. Selection of the orbits considers the reduction of Doppler shift and wavefront attenuation due to relative orbital velocity and residual Earth atmosphere.

TM X-64710

Photogrammetry and Photo-Interpretation Applied to Analyses of Cloud Cover, Cloud Type, and Cloud Motion. Paul A. Larsen. Aero-Astrodynamics Laboratory. N73-21385

A determination was made of the areal extent of terrain obscured by clouds and cloud shadows on a portion of an Apollo 9 photograph at the instant of exposure. This photogrammetrically determined area then compared to the cloud coverage reported by surface weather observers at approximately the same time and location, as a check on result quality. Stereograms prepared from Apollo 9 vertical photographs, illustrating various percentages of cloud coverage, are presented to help provide a quantitative appreciation of the degradation of terrain photography by clouds and their attendant shadows. A scheme, developed for the U.S. Navy, utilizing pattern recognition techniques for determining cloud motions from satellite photographs, sequences of summarized. Clouds, turbulence, haze, and solar altitude, four elements of our natural environment which affect aerial photographic missions, are each discussed in terms of their effects on imagery obtained by

photography. Data of a type useful to aerial and orbital photographic mission planners, expressing photographic ground coverage in terms of flying height above terrain and camera focal length, for a standard aerial photograph format, are provided. Two oblique orbital photographs taken during the Apollo 9 flight are shown, and photo interpretations, discussing the cloud types imaged and certain visible geographical features, are provided.

TM X-64711 October 1, 1972 Compatibility of Materials with Liquid Oxygen – Vol. I. C. F. Key. Astronautics Laboratory, X73-10133

The test instrument and procedure developed by Lucas and Riehl (Ref. 1) was used to determine the compatibility of a wide variety of materials with liquid oxygen (LOX). This method is based upon the tendency of materials to react with LOX on impact and is commonly known as the "ABMA Tester." Within the past 15 years' use, over 240,000 individual test drops have been made on approximately 2,000 different materials. Pertinent data from these tests have been compiled, and the findings are presented in this report. Recommendations are made for the guidance of designers and others in the selection of safe materials for use in oxygen systems. Materials are discussed according to the following classifications: (1) lubricants, (2) sealants and threading compounds, (3) thermal and electrical insulation, (4) elastomers, plastics and adhesives. (5) gaskets and packing, (6) metals, alloys and solders, (7) solvents, cleaning solutions, and miscellaneous, and (8) dye penetrants.

TM X-64712

Monthly and Annual Percentage Levels of Wind Speed Differences Computed by Using FPS-16 Radar/Jimsphere Wind Profile Data from Cape Kennedy, Florida. Michael Susko and John W. Kaufman. Aero-Astrodynamics Laboratory.

N73-14650

This report presents the percentage levels of wind speed differences computed from radar/Jimsphere sequential FPS-16 profiles. The results are based on monthly profiles obtained from December 1964 to July 1970 at Cape Kennedy, Florida. The profile sequences contain a series of three to Jimspheres released at approximately 1.5-hour intervals. The results given are the persistence analysis of wind speed difference at 1.5-hour intervals to a maximum time interval of 12 hours. Tables 1a through 12e are the monthly percentage levels of wind speed differences and Tables 13a through 13e are the annual percentage of wind speed differences. The percentage levels are based on the scalar wind speed changes calculated over an altitude interval of approximately 50 meters and printed out every 25 meters as a function of initial wind speed within each 5-km layer from near sea level to 20 km. In addition, analyses were made of the wind speed differences for the 0.2- to 1-km layer as an aid for studies associated with take-off and landing of the Space Shuttle. The results may be used as an aid to (1) predict statistical wind speed change limits of lower and upper level winds, (2) provide an understanding of the statistical probabilities of wind speed changes as a function of time, and (3) apply the data in the study of winds aloft for such projects as the Space Shuttle, HEAO, Skylab, and aeronautical vehicles. Information such as this is also important to many aerospace vehicle structural and control system designers

in studying the effects of wind speed variations on the prelaunch monitorship and wind biasing schemes. The availability of this type of information is also important in mission planning and operational analyses plus general meteorological forecasting studies.

TM X-64713

Natural Environment Design Requirements for the Space Tug. George S. West, Jr. Aero-Astrodynamics Laboratory.

N73-14881

Given in this report are the natural environment design requirements for the Space Tug. Since the Space Tug is carried as "cargo" to orbital altitudes in the Space Shuttle bay, orbital environmental impacts and short-period atmospheric density variations are the main concerns of this report.

TM X-64714 January 10, 1973
The Beta Distribution: A Statistical
Model for World Cloud Cover. Lee W.
Falls. Aero-Astrodynamics Laboratory.
N73-14653

Much work has been performed in developing empirical global cloud-cover models. The investigation in this report was made to determine an underlying theoretical statistical distribution to represent worldwide cloud cover. The beta distribution with probability density function,

$$f(x) = \frac{\Gamma(\gamma + \eta)}{\Gamma(\gamma)\Gamma(\eta)} x^{\gamma-1} (1 - x)^{\eta-1}$$

is given to represent the variability of this random variable. It is shown that the beta distribution possesses the versatile statistical characteristics necessary to assume the wide

variety of shapes exhibited by cloud cover. A total of 160 representative empirical cloud-cover distributions were investigated and the conclusion was reached that this study provides sufficient statistical evidence to accept the beta probability distribution as the underlying model for world cloud cover.

TM X-64715 January 10, 1973

Development and Applications of an Orbital Insertion Surface for the Space Shuttle Orbiter/Tug. A. W. Deaton and P. D. Brandon. Aero-Astrodynamics Laboratory. N73-15862

This report develops the concept of a space shuttle orbiter/tug orbital insertion surface and identifies practical applications in the area of ascent targeting, on-orbit rendezvous targeting, payload/OMS propellant offloading, and mission analysis.

TM X-64716 December 8, 1972
Flat Conductor Cable Symposium,
October 10-12, 1972. James D. Hankins
(Coordinator). Process Engineering
Laboratory. N73-23294

This report documents the proceedings of a Flat Conductor Cable (FCC) Symposium and Hardware Exhibit which was held at Marshall Space Flight Center during October 10, 11, and 12, 1972. A total of 24 (out of 26) papers and presentation outlines are included covering cables, connectors, termination techniques, electrical characteristics, aerospace applications, and non-aerospace applications. Questions and answers during a panel discussion are included plus a listing of vendors that displayed FCC hardware.

TM X-64717 January 1973
Traffic Model for the Space Shuttle.
Shuttle Utilization Planning Office,
Program Development. X73-71658

The traffic model for the Space Shuttle is presented along with some supporting and summary data. This document and subsequent editions will provide the Shuttle Program and potential Shuttle users with traffic model information.

TM X-64718 January 18, 1973

High Resolution Power Spectra of Daily
Zurich Sunspot Numbers. Harold C.
Euler, Jr. Aero-Astrodynamics Laboratory. N73-15840

High resolution power spectra of 77 years of Zurich daily sunspot numbers were computed using various lags and data point intervals. Major harmonic peaks of the approximately 124-month period showed up strongly as well as the 27-day solar rotational period.

TM X-64719

Recommendations Relative to the Scientific Missions of a Mars Automated Roving Vehicle (MARV). Robert L. Spencer, ed. Mission and Payload Planning Office, Program Development.

N73-16219

This document establishes logical scientific objectives, defines specific science systems requirements, and recommends scientific experiment payloads which will effectively accomplish the established

objectives through the utilization of an automated roving vehicle systematically exploring the surface of Mars. No concepts of the roving vehicle itself have been presented or recommended. It is intended that this document be used in the formulation of any such vehicle design concepts.

TM X-64720 November 1972
Ascent Control Studies of the 049 and ATP Parallel Burn Solid Rocket Motor Shuttle. Robert S. Ryan, David K. Mowery, Morris Hammer, and A.C. Weisler. Aero-Astrodynamics Laboratory.

N73-17854

The control authority approach is a major problem of the parallel burn solid Shuttle configuration due to the many resulting system impacts regardless of the approach. This report discusses the major trade studies and their results, which led to the recommendation of an SRB TVC control authority approach.

TM X-64721 January 22, 1973
Transient Permeation of Organic Vapors
Through Elastomeric Membranes. James
E. Curry. Astronautics Laboratory.

N73-16112

The permeation of benzene and acetone vapors through sulfur-cured natural rubber was studied by the time-lag method. The experimental results were analyzed by a method suggested by Meares. $D_{\rm O}$, the zero concentration diffusion coefficient, was obtained by the early-time method. The Frisch time-lag equation was utilized to estimate both the solubility coefficient (a) and the additional parameter (b) required to

define the concentration-dependence of the diffusion coefficient, $D(c) = D_0 \exp(bc)$. This form of concentration dependence was manifested by the corresponding permeability coefficient values. At low entering penetrant pressure where the transport coefficients are constant, indirect evidence was obtained that Do is the mechanistically correct diffusion coefficient. The solubility coefficient values calculated for benzene vapor in natural rubber are in reasonable agreement with published equilibrium sorption data for a similar rubber At higher entering penetrant compound. diffusion pressures, average coefficients obtained at steady state tended to be larger than the corresponding average diffusion coefficients derived from the time-lags. This has been attributed to slow relaxation effects in the swollen membrane which inject an element of time dependence into transport process.

TM X-64722 March 1973
The Attenuation of X Rays Emitted by
Supernovae. Klaus Schocken. Space
Sciences Laboratory. N73-21701

The attenuation of X rays in Arnett's C¹² detonation supernova model is computed. The attenuation of X rays in the filaments of the Crab Nebula is computed using a model for the filaments by Woltjer and a model by Davidson and Tucker. An empirical expression by Gorenstein, Kellogg, and Gursky for the optical thickness of the interstellar medium for three supernova remnants is analyzed.

TM X-64723 February 1973 Research Achievements Review. Vol. IV, No. 7. Process Engineering Research at MSFC. Science and Engineering.

N73-22915

TM X-64724 November 1972
Electrophoresis Demonstration on Apollo
16. R. S. Snyder. Astronautics
Laboratory. N73-18157

Free fluid electrophoresis, a process used to separate particulate species according to surface charge, size, or shape was suggested as a promising technique to utilize the nearzero-gravity condition of space. Fluid electrophoresis on earth is disturbed by gravityinduced thermal convection and sedimentation. An apparatus was developed to demonstrate the principle and possible problems of electrophoresis on Apollo 14 and the separation boundary between red and blue dye was photographed in space. The basic operating elements of the Apollo 14 unit were used for a second flight demonstration on Apollo 16. Polystyrene latex particles of two different sizes were used to simulate the electrophoresis of large biological particles. The particle bands in space were stable compared extremely to ground operation because convection in the fluid was negligible. Electrophoresis of the polystyrene latex particle groups according to size was accomplished although electro-osmosis in the flight apparatus prevented the clear separation of two particle bands.

TM X-64725 February 28, 1973
Scientific Involvement in Skylab by the
Space Sciences Laboratory of the
Marshall Space Flight Center. Carl E.
Winkler, ed. Space Sciences Laboratory.
N73-20886

This report briefly describes the involvement of the Marshall Space Flight Center's Space Sciences Laboratory in the Skylab program from the early feasibility studies through the analysis and publication of flight scientific and technical results. This includes Mission Operations Support, the Apollo Telescope Mount, Materials Science/Manufacturing in Space, Optical Contamination, Environmental and Thermal Design Criteria, and several corollary measurements and experiments.

TM X-64726 December 15, 1972 Large Space Telescope, Phase A Final Report. Vols. I through V. Program Development.

> Vol. I N73-18449 Vol. II N73-18450 Vol. III N73-18451 Vol. IV N73-18452 Vol. V N73-18453

This document is a report of the Phase A study of the Large Space Telescope (LST). The study defines an LST concept based on the broad mission guidelines provided by the Office of Space Science (OSS), the scientific requirements developed by OSS with the scientific community, and an understanding of long range NASA planning current at the time the study was performed. The LST is an unmanned astronomical observatory facility, consisting of an optical telescope assembly (OTA), scientific instrument package (SIP), and a support systems module (SSM). The report consists of five volumes: Volume I is an executive summary, Volume II is a summary of the entire report, and Volumes III, IV, and V contain the analyses and conceptual designs of the OTA, SIP, and SSM, respectively. The report describes the constraints and trade off analyses that were performed to arrive at a reference design for

each system and for the overall LST configuration. The LST will be launched into low earth orbit by the Space Shuttle and operated for 10 to 15 years. The Shuttle will also be used to maintain the LST and to update the scientific instrument complement. Several maintenance modes have been investigated, including on-orbit pressurization of the SSM to provide a shirtsleeve environment for maintenance, and earth return of the LST. The will LST provide the scientific community with several fundamentally unique capabilities which will permit the acquisition of new and important observational data. Its location in space permits observations over the entire spectrum from about 100 nm to the far infrared. A low cost design approach was followed in the Phase A study. This resulted in the use of standard spacecraft hardware, the provision for maintenance at the black box level, growth potential in systems designs, and the sharing of Shuttle maintenance flights with other payloads.

TM X-64727 July 17, 1972

A Comparison of CMG Steering Laws for High Energy Astronomy Observatories (HEAOs). Billy G. Davis. Preliminary Design Office, Program Development.

N73-20718

This report contains a comparison of six selected control moment gyro (CMG) steering laws for use on the HEAO spacecraft. Basic equations are developed to project the momentum and torque of four skewed, single gimbal CMGs into vehicle coordinates. In response to the spacecraft attitude error signal, six algorithms (steering laws) are derived for controlling the CMG gimbal movements. HEAO performance data were

obtained using each. steering law and compared on the basis of such factors as accuracy, complexity, singularities, hang-up and failure adaption. Moreover, each law was simulated with and without a magnetic momentum management system. With magnetics, momentum is continuously dumped against the earth's magnetic field and the gimbal angles stay small, thus permitting linear operation of the steering law. The performance of any steering law enhanced by the magnetic system and all performed equally well. Without magnetics, the gimbal angles get large and there are significant differences in steering law performances due to cross coupling and nonlinearities. The performance of the pseudo inverse law was consistently better than the other laws and is recommended for HEAO.

TM X-64728 October 1972
Termination of Flat Conductor Cable to NASA/MSFC Plugs. W. Angele. Process
Engineering Laboratory. N73-20239

The report contains data, supplemented with artwork, on the major steps involved in terminating flat conductor cable (FCC) to MSFC's FCC plugs. Cable and shield preparation steps include material cutting, insulation stripping, and plating of exposed conductors. Methods and equipment required to terminate FCC to each of four MSFC plugs are described.

TM X-64729 March 7, 1973

A Mechanical Property and Stress
Corrosion Evaluation of 431 Stainless
Steel Alloy. J. W. Montano. Astronautics
Laboratory. N73-21441

This report presents the mechanical properties of type 431 stainless steel in two conditions: annealed bar and hardened and tempered bar. Test specimens, manufactured approximately 1.0 inch (2.54 cm)diameter bar stock, were tested at temperatures of $80^{\circ}F$ (+26.7°C), $0^{\circ}F$ (-17.8°C), -100°F (-73°C), and -200°F (-129°C). The test data indicated excellent tensile strength, notched/unnotched tensile ratio, ductility, shear, and impact properties at all testing temperatures. Results of the alternate immersion stress corrosion tests on stressed and longitudinal tensile specimens unstressed 0.1250 inch (0.3175 cm) diameter and transverse "C"-ring specimens, machined from 1.0 inch (2.54 cm) diameter bar stock, indicated that the material is not susceptible to stress corrosion cracking when tested in a 3.5-percent NaCl solution for 180 days.

TM X-64730 January 12, 1973

Evaluation of Flexible Ring Baffles for Damping Liquid Oscillations. Frank Bugg. Aero-Astrodynamics Laboratory.

N73-21273

An experimental study was undertaken of damping produced by single flexible-ring baffles in a 396-cm diameter tank of liquid nitrogen. Two 24.8-cm wide baffles were tested. One baffle was 0.00635-cm thick type 301 stainless steel and the other 0.0254-cm thick Teflon FEP. Each baffle produced damping of liquid oscillations equal to or greater than that expected from rigid baffles of the same size. The equations used to determine the baffle thickness required were found to be adequate baffle design equations.

TM X-64731 March 1973

Space Shuttle Traffic Model Developed from 1971 Mission Model. Shuttle Utilization Planning Office, Program Development. N73-26878

Traffic model data for the Space Shuttle using the 1971 NASA, DoD, and commercial mission models are presented along with descriptions and schedules for the NASA and commercial payloads used to develop the data.

TM X-64732 January 15, 1973 Structural Control Interaction. Robert S. Ryan, D. K. Mowery, S. W. Winder, and Halsey E. Worley. Aero-Astrodynamics Laboratory. N73-21834

The basic guidance and control concepts that lead to structural control interaction and structural dynamic loads are identified. Space vehicle ascent flight load sources and the loadrelieving mechanism are discussed, along with the characteristics and special problems of present and future space vehicles including launch vehicles, orbiting vehicles, and the Space Shuttle flyback vehicle. The special dynamics and control analyses and test problems apparent at this time summarized. This report is in essence a presentation that was prepared for "NASA Structures and Materials Advisory Committee" as a means of providing information for research planning.

TM X-64733 March 21, 1973 Synthetic Sea Water — An Improved Stress Corrosion Test Medium for

Aluminum Alloys. T. S. Humphries and E. E. Nelson. Astronautics Laboratory.

N73-22062

A major problem in evaluating the stress corrosion cracking resistance of aluminum alloys by alternate immersion in 3.5-percent water is excessive pitting salt (NaCl) corrosion. Several methods were examined to eliminate this problem and to find an improved accelerated test medium. These included the addition of chromate inhibitors, surface treatment of specimens, immersion in synthetic sea water. The results indicate that alternate immersion in synthetic sea water is a very promising stress corrosion test medium. Neither chromate inhibitors nor surface treatment (anodize and alodine) of the aluminum specimens improved the performance of alternate immersion in 3.5percent salt water sufficiently to be classified as an effective stress corrosion test method.

TM X-64734 February 23, 1973 Microbiological Surveillance of Food Handling at NASA-MSFC. F. J. Beyerle. Process Engineering Laboratory.

N73-20127

A microbiological surveillance program of cafeterias and snack bars at MSFC was conducted to supplement the inspections by NASA Medical Center personnel and to gather information for cafeteria management to pinpoint areas of possible contamination. This report summarizes the work conducted under the program from its inception in January, 1972, to its termination on September 15, 1972. Ten food handling facilities were included in the surveillance at NASA-MSFC.

TM X-64735 March 29, 1973

Heat Flow and Convection Demonstration (Apollo 14). Tommy C.

Bannister. Space Sciences Laboratory.

Apollo 14 Astronaut Stuart A. Roosa conducted a group of experiments during the lunar flyback on February 7, 1971, to obtain information on heat-flow and convection in gases and liquids in an environment of less than 10⁻⁶ g. Flow observations and thermal data have shown that (1) as expected, there are convective motions caused by surface tension gradients in a plane liquid layer with a free upper surface; (2) heat flow in enclosed liquids and gases occurs mainly by diffusive heat conductions; and (3) some convective processes, whose characteristics are not fully known, add to the heat transfer. The raw data are presented in this report, and the analysis approach is given.

TM X-64736 February 16, 1973
Microbiological Assay of the MSFC
Neutral Buoyancy Simulator. F. J.
Beyerle. Process Engineering Laboratory.
N73-21127

Personnel safety for divers and astronauts, from the microbiological and medical viewpoint, is the primary reason for monitoring the Neutral Buoyancy Simulator water. Of secondary importance is the detection of microorganisms which may degrade the mockups in the water and the carpeted area around the simulator. A Neutral Buoyancy Program was initiated in 1965 in the Process Engineering Laboratory, MSFC, to perform microbiological studies of the water in the 1.4-million gallon tank. A broad

spectrum of water sampling procedures was performed, and personal communications with mycology experts were conducted to familiarize laboratory personnel with fungal problems in water. With the addition of control procedures and remedial actions taken, the water was considered sanitary and in a safe condition for the divers and astronauts to perform their underwater neutral-buoyancy work.

TM X-64737 April 1973
Preliminary Flight Trajectories for the Apollo Soyuz Test Project. Joe D. Brooks. Aero-Astrodynamics Laboratory.

This report documents preliminary data for a typical launch window opening, a typical in-plane case, and a typical launch window closing trajectory, not necessarily in the same daily launch window, for the Apollo Sovuz Test Project Mission. The Sovuz will be launched first and the Apollo will be launched on the first opportunity, 7 hours 21 minutes later. If the Apollo is unable to be launched on the first opportunity, four additional opportunities are available at 30 hours 56 minutes, 54 hours 31 minutes, 78 hours 05 minutes, and 101 hours 40 minutes. If the Apollo cannot be launched in this time frame, no further attempt will be made to launch and rendezvous with the first Sovuz. Soyuz will then be deorbited; however, a second Soyuz has been made available for the same purposes.

TM X-64738 April 5, 1973
Structural Load Reduction of the Space
Shuttle Booster/Orbiter Configuration
Using a Load Relief Guidance
Technique. A. W. Deaton and P. B.
Kelley. Aero-Astrodynamics Laboratory.

N73-21812

A space shuttle booster/orbiter atmospheric ascent guidance algorithm is developed that will reduce the aerodynamically induced structural loads as compared to an open loop guidance algorithm.

TM X-64739 April 1973 1973 NASA Mission Model. Shuttle Utilization Planning Office, Program Development.

The April 1973 NASA Mission Model and the NASA estimate of the April 1973 Non-NASA/Non-DoD Mission Model for calendar years 1973 through 1991 are presented along with summary Mission Model totals for NASA, Non-NASA/Non-DoD, and DoD for calendar years 1980 through 1991.

TM X-64740 December 1972
Phase A Reaction Control System Design
for the Large Space Telescope (LST).
William B. Price. Preliminary Design
Office, Program Development.

N73-21394

In response to a request from the Office of Space Science, a Phase A study of the Large Space Telescope was undertaken by the George C. Marshall Space Flight Center. The design of a Reaction Control System (RCS) for the LST was a part of this study, the results of which are reported in this document. The primary requirement for an RCS on the LST is to serve as an emergency backup control system to the LST primary attitude control system. A regulated gaseous nitrogen RCS was selected, and a description of the operation of the system and its individual components is presented. on-orbit maintenance procedure for the system is also described. The alternate RCS concepts considered during the study are

summarized. Principal design goals of the RCS for the LST were to minimize contamination effects, make use of existing components, and modularize the system to provide ease in manned orbital maintenance. The RCS described herein will provide a point of departure for a more in-depth Phase B system design study. A summary of this report is presented in NASA TM X-64726, entitled "Large Space Telescope Phase A Report," and reference is made to that report for a description of all aspects of the LST.

TM X-64741 April 13, 1973
Scintillator Handbook with Emphasis on
Cesium Iodide. John L. Tidd, Joseph R.
Dabbs, and Norman Levine. Program
Development and HEAO Project Office.

N73-22398

The objective of this report is to provide a background of reasonable depth and reference material on scintillators in general. Particular attention is paid to the cesium iodide scintillators as used in the High Energy Astronomy Observatory (HEAO) experiments. It is intended especially for use by persons such as laboratory test personnel who need to obtain a working knowledge of these materials and their characteristics in a short time.

TM X-64742 March 16, 1973
The Gaertner L119 Ellipsometer and Its
Use in the Measurement of Thin Films.
Michael Linkous. Space Sciences Laboratory.
N73-21392

An introduction to the study of ellipsometry is presented, with special attention given to the Gaertner model L119

ellipsometer and the techniques of measuring thin films with this instrument. Values obtained from the ellipsometer are analyzed by a computer program for a determination of optical constants and thickness of the film.

TM X-64743 February 23, 1973
Hypervelocity Impact Testing of L-Band
Truss Cable Meteoroid Shielding on
Skylab. David W. Jex. Space Sciences
Laboratory. N73-24867

The purpose of this series of tests was to determine if the L-band truss cable meteoroid shielding as currently designed and supplied for Skylab provides adequate protection when it is at the expected space environment temperature of -118°C (-180°F).

TM X-64744 January 1, 1973
Computer User's Manual for a Generalized Curve Fit and Plotting Program.
Ronald A. Schlagheck, B. D. Beadle II,
B. D. Dolerhie, Jr., and J. W. Owen.
Astronautics Laboratory. N73-24213

A Fortran-coded program has been developed for generating plotted output graphs on 8-1/2 by 11-inch paper. The program is designed to be used by engineers, scientists, and non-programming personnel on any IBM 1130 system that includes a 1627 plotter. The program has been written to provide a fast and efficient method of displaying plotted data without having to generate any instructions. additional Fortran output options are available to the program user for displaying data in four different types of formatted plots. These options include discrete, linear, continuous, histogram graphical outputs. The manual

contains information about the use and operation of this program. Example cases illustrate the sample input and output for five selected plots. A mathematical description of the least-squares "goodness of fit" test is presented. A program listing is also included.

TM X-64745 May 9, 1973
Offgassing of Non-Metallic Materials in 5 psia Oxygen. F. T. Wells and D. R. Hamilton. Astronautics Laboratory.

N73-23631

Offgas analyses results of non-metallic materials to determine their conformance with MSFC-SPEC-101B, "Flammability, Odor, and Offgassing Requirements and Test Procedures for Materials in Environments Which Support Combustion," are reported. This report contains results obtained since early 1969 to the present time. Only results of Test No. 7 of MSFC-SPEC-101B are shown in this report. A brief test and analysis description including procedure development is also presented.

TM X-64746 January 12, 1973
Skylab Attitude Control and Angular
Momentum Desaturation with One
Double-Gimbaled Control Moment Gyro.
Hans F. Kennel. Astrionics Laboratory.

N73-23851

In case two control moment gyros fail, attitude control of Skylab can be maintained with the thruster attitude control system. This results, however, in a severely increased fuel consumption, depleting the fuel in a few days. A reduction in fuel consumption can be achieved by allowing the attitude reference to yield with the gravity-gradient torques at

twice orbital frequency. For an ideal case, fuel consumption can be drastically reduced, but any unanticipated disturbance torques and principal moment-of-inertia axes misalignwill again increase the consumption sizeably. Therefore, an alternate concept was developed, which does not have large fuel consumption under any circumstances. In this concept the attitude reference is commanded to oscillate in the orbital plane with twice the orbital frequency and the remaining control moment gyro controls about orbital north and about the minimum moment-of-inertia axis, while the thruster attitude control system controls rate only about the remaining axis. This rate control in conjunction with the restoring torque due to the gravity gradient will keep bounded the excursion of the minimum moment-of-inertia axis out of the orbital plane. This alternate concept has the additional advantage that it needs no information on the principal moment-of-inertia axes misalignment and is completely insensitive to star tracker failure. Proper phasing of the attitude reference oscillation even allows angular momentum desaturation, which is responsible for the insensitivity of the thruster fuel consumption to unknown disturbances, like vent torques, magnetic torques, etc.

TM X-64747 May 10, 1973

X-Ray Reflection Efficiency of NickelCoated Quartz Optical Flats. John M.
Reynolds, Stanley A. Fields, and Robert
M. Wilson. Space Sciences Laboratory.

N73-24694

Results of tests to determine the reflection efficiency of quartz optical flats vacuum coated with 1000-Å nickel are

presented. Of the three vacuum-coated samples tested, two had been contaminated during the firing of the Lunar Module Reaction Control System in the JSC vacuum chamber (Chamber A). Measurements were made for 1.54-, 1.79-, and 2.29-Å incident radiation. The reflection efficiency of the contaminated samples was reduced by as much as 50 percent for some angles of incidence.

TM X-64748 August 1972
A Model for Estimating the Cost Impact of Schedule Perturbations on Aerospace Research and Development Programs.
Donald F. Bishop. Engineering Cost Group, Program Development.

N73-24948

The problem of determining the cost impact attributable to perturbations in an aerospace R&D program schedule is becoming increasingly important as the availability of R&D funds diminishes. This memorandum develops the methodology from which a model is presented for updating aerospace R&D cost estimates as a function of perturbations in program time.

TM X-64749 February 16, 1973

A Simple Performance Calculation
Method for LH₂/LOX Engines with
Different Power Cycles. Robert H.
Schmucker. Astronautics Laboratory.

N73-24786

A simple method for the calculation of the specific impulse of an engine with a gas generator cycle is presented. The solution is obtained by a power balance between turbine and pump. Approximate equations for the performance of the combustion products of LH₂/LOX are derived. Performance results are compared with solutions of different engine types.

TM X-64750 April 16, 1973

Flat Conductor Cable Design, Manufacture, and Installation. W. Angele and James D. Hankins. Process Engineering Laboratory.

This report presents pertinent inforhardware selection. mation for manufacture, and quality control necessary for flat-conductor cable interconnecting harness application. Detailed information is provided on cable, connectors, and support hardware that has been developed on various programs conducted and funded by the National Aeronautics and Space Adminis-Marshall Space Flight tration, Center, Huntsville, Alabama. The relation of this hardware to the new MIL-C-55543 and MIL-C-55544 specifications for flat-conductor cable and flat-conductor cable connectors is defined. Comparisons are made between round-wire cable and flat-conductor cable. The flat conductor cable interconnecting harness systems show major cost, weight, and space savings, plus increased system performance and reliability. The design application section includes electrical characteristics. harness design and development, and a full on **EMC** considerations. Manufacturing and quality control sections pertain primarily to the NASA/MSFC developed conductor-contact connector system special flat-conductor cable to round-wire cable transitions. This report presents flat-conductor cable technology as of June 1968, and predicts the role of flat-conductor cables in interconnecting harness applications for future programs.

TM X-64751 July 1973
The 1973 Space Shuttle Traffic Model.
Shuttle Utilization Planning Office,
Program Development. N73-26845

Traffic model data for the Space Shuttle for calendar years 1980 through 1991 are presented along with some supporting and summary data. This model was developed from the 1973 NASA Payload Model and the NASA estimate of the 1973 Non-NASA/Non-DoD Payload Model. The estimates for the DoD flights included in this document are based on the 1971 DoD Mission Model.

TM X-64752

The 1973 Expendable Launch Vehicle
Traffic Model. Shuttle Utilization
Planning Office, Program Development.

Traffic model data for current expendable launch vehicles (assuming no Space Shuttle) for calendar years 1980 through 1991 are presented along with some supporting and summary data. This model was based on a payload program equivalent in scientific return to the 1973 NASA Payload Model, the NASA estimated non NASA/non DoD Payload Model, and the 1971 DoD Mission Model.

TM X-64753 June 8, 1973
Phased-Array Laser Radar: Concept and
Application. Kenneth A. Kadrmas. AeroAstrodynamics Laboratory. N73-25561

Basic principles of laser radar, LIDAR, have been documented by numerous authors. In spite of this intensity of effort, present day system concepts have not been sufficiently concentrated on improving the

"optical compatibility" of the LIDAR transmitter-receiver combination. A unique new approach has been undertaken in the design and construction of a coaxial transmitter-receiver combination. Major emphasis has been placed on simple permanent optical alignment, transmitterreceiver field of view matching, use of a pulsed gas laser as a transmitter, maximum optical efficiency, complete digital control of data acquisition, and optical mount pointing and tracking. Also, a means of expanding the coaxial transmitter-receiver concept to allow phased-array LIDAR, par-LIDAR, described.

TM X-64754 May 1, 1973 Vamistor Resistor Investigation. Quality and Reliability Assurance Laboratory.

This report presents the results of the failure investigation conducted by MSFC on resistors produced by the Vamistor Division, Wagner Electric Corporation. This failure investigation included: failure analyses, chemical and metallurgical analyses, failure mechanism studies, seal leak analyses, and nondestructive stress tests. The data, information, conclusions, and recommendation presented herein can be helpful in assessing current usage of these resistors.

TM X-64755 February 1, 1973
Guidelines for Selection and Application
of Tantalum Electrolytic Capacitors at
MSFC. A. M. Holladay, Leon C. Hamiter,
Jr., and Benton A. Vizzier, Sr. Quality
and Reliability Assurance Laboratory.

This document presents guidelines for selection and application of three types of

N73-26200

tantalum electrolytic capacitors in current use at MSFC in the design of electrical and electronic circuits for manned space flight missions. In addition, the guidelines supplement requirements of existing Military **Specifications** procurement used in capacitors. A need exists for these guidelines, to assist designers in preventing some of the recurring, serious problems experienced with tantalum electrolytic capacitors in the recent past. The three types of capacitors covered by these guidelines are: solid (CSR), wet foil (CLR 25, 27, 35, and 37), and wet slug (CLR 65).

TM X-64756 June 26, 1973 Hot and Cold Atmospheres for Vandenberg AFB, California (1973 Version). D. L. Johnson. Aero-Astrodynamics Laboratory.

Extreme atmospheres, pertaining to summer (hot) and winter (cold) conditions for Vandenberg Air Force Base, California, are presented from 0- to 90-km altitudes. Computed values of pressure, e, kinetic temperature, virtual temperature, density, and relative differences [percentages Vandenberg Reference Atmosphere, 1971 (VRA 71)] of the atmospheric parameters versus altitude are tabulated in increments of 250 m. Hydrostatic and gas law equations were used in conjunction with radiosonde and rocketsonde thermodynamic data in determining the vertical structure of the two atmospheric models. The summer-type density profile deviated from -9.0 percent (of the VRA-71) at the ground to 28.4 percent at 74.5-km altitude. The winter density profile went from 5.2 percent at the surface to -31.4 percent at 72 km.

TN D-6824 August 1972
Experimental Findings From Zero-Tank
Net Positive Suction Head Operation of
the J-2 Hydrogen Pump. Henry P.
Stinson and Raymond J. Strickland.
Astronautics Laboratory. N72-29807

The results of a series of liquid hydrogen turbopump tests to demonstrate the feasibility of zero-tank net positive suction head are presented. A J-2 engine hydrogen pump and S-IVB stage fuel feed system were used for this investigation. The pump was operated at flows and speeds equivalent to normal J-2 engine operating conditions and at hydrogen bulk temperatures between 39 and 45°R. These tests show zero-tank net positive suction head to be a realistic operating mode that should be considered for future applications.

TN D-6825

Wall Temperature Distribution Calculation for a Rocket Nozzle Contour.

Satoaki Omori, Klaus W. Gross, and Alfred Krebsbach. Astronautics Laboratory.

N72-30773

The JANNAF Turbulent Boundary Layer (TBL) computer program, applicable to rocket nozzles, requires a wall temperature distribution among other input parameters to determine boundary layer behavior, heat transfer, and performance degradation. The inclusion of a complete regenerative cooling cycle model with associate geometry, material and fluid property data provides a capability to internally calculate wall temperature profiles on the hot gas and coolant flow-side, as well as the coolant flow bulk temperature variation. Besides the regular heat transfer and

performance degradation calculations, the new concept can be used to optimize the cooling cycle, coolant flow requirements, and cooling jacket geometry.

TN D-6829 July 1972
Spherical Balloon Response to ThreeDimensional Time-Dependent Flows.
George H. Fichtl. Aero-Astrodynamics
Laboratory. N72-27001

The dynamic response of a balloon to atmospheric flow is a function of the aerodynamic drag and lift forces, virtual mass effects, the Archimedean buoyancy forces, and dynamic buoyancy forces. The equations of motion for a spherical balloon which include these effects are derived by examining the various forces that can act on a spherical balloon in relation to the atmospheric equations of motion. It is assumed that the atmosphere affects the balloon but the balloon does not affect the atmosphere. An analysis shows that Coriolis effects in the balloon equations of motion can be neglected for most rising or falling balloons. The concept of the Lagrangian displacement of a balloon is introduced. It is shown that the general balloon response problem is extremely complicated because the wind-forcing functions in the balloon equations of motion are functions of the wind velocity vector and its Eulerian first derivatives evaluated at the location of the balloon. The balloon location is the dependent variable of the problem. The linear perturbation equations for a spherical balloon are derived by perturbing the components of velocity of the balloon about a terminal velocity state which is in equilibrium with a space-time invariant mean horizontal flow. The atmospheric flow is also

perturbed such that the resulting equations can be used to analyze the responses of spherical balloons to three-dimensional timedependent flows. The wind field is represented in terms of a four-fold Fourier integral that involves three orthogonal wave numbers and frequency, while the components of velocity are represented as Fourier integrals involving a frequency which, in turn, is a function of the wind field wave numbers and frequency and the unperturbed flow components of velocity. The general nonstationary spectra of the components of velocity are obtained in terms of integrals of the nonhomogeneous and nonstationary spectra of the wind field. The flow associated with a statistically stationary and homogeneous atmospheric velocity field is treated as a special case. The introduction of Taylor's frozen eddy hypothesis reduces the response integrals to algebraic equations which are relatively simple forms for the balloon transfer functions.

TN D-6868 July 1972

Mass Influx Obtained from LLLTV

Observations of Faint Meteors. Robert J.

Naumann and K. Stuart Clifton. Space
Sciences Laboratory. N72-28830

Since the advent of low light level television (LLLTV) systems, it has been recognized that such devices offer the ability to observe meteors as faint as 10th magnitude which allows the extension of optical meteor data to masses as small as 10⁻⁴ gram. The Space Sciences Lab at Marshall Space Flight Center has been actively engaged in such observations using image orthicons and intensified SEC vidicons. The results of these observations are presented along with an

interpretation in terms of mass-flux. This interpretation includes the development of a relationship between peak luminosity of a meteor and mass, velocity, and zenith angle that was derived from single body meteor theory and compares favorably with results obtained from the Artificial Meteor Program. Also included in the mass flux interpretation is an analysis of the observation response of a LLLTV system to fixed and moving point sources.

TN D-6873 October 1972
A Workload Model and Measures for Computer Performance Evaluation. H. Kerner and K. Kuemmerle. Computation Laboratory. N72-33195

A generalized workload definition is presented which constructs measurable workloads of unit size from workload elements. called Elementary Processes. An Elementary Process makes almost exclusive use of one of the processors, CPU, I/O processor, etc., and is measured by the cost of its execution. Various kinds of user programs can be simulated by quantitative composition of Elementary Processes into a Type. The character of the Type is defined by the weights of its Elementary Processes and its structure by the amount and sequence of transitions between its Elementary Processes. A set of Types is batched to a Mix. Mixes of identical cost are considered as equivalent amounts of workload. These formalized descriptions of workloads allow investigators to compare the results of different studies quantitatively. Since workloads of different composition are assigned a unit of cost, these descriptions enable determination of cost effectiveness of different workloads on a

machine. Subsequently performance parameters such as Throughput Rate, Gain Factor, Internal and External Delay Factors are defined and used to demonstrate the effects of various workload attributes on the performance of a selected large scale computer system.

TN D-6901 September 1972 Atmospheric Electricity Criteria Guidelines for Use in Aerospace Vehicle Development. Glenn E. Daniels. Aero-Astrodynamics Laboratory. N72-31617

Lightning has always been of concern for aerospace vehicle ground activities. The unexpected triggering of lightning discharges by the Apollo 12 space vehicle shortly after launch and the more recent repeated lightning strikes to the launch umbilical tower while the Apollo 15 space vehicle was being readied for launch have renewed interest in studies of atmospheric electricity as it relates to space vehicle missions. This report reflects some of the results of these studies with regard to updating the current criteria guidelines.

TN D-6930 September 1972
Optimum Runway Orientation Relative to Crosswinds. L. W. Falls and S. C. Brown. Aero-Astrodynamics Laboratory.

N72-30250

Specific magnitudes of crosswinds may exist that could be constraints to the success of an aircraft mission such as the landing of the proposed space shuttle. A method is required to determine the orientation or azimuth of the proposed runway which will minimize the probability of certain critical crosswinds. Two procedures for obtaining the

optimum runway orientation relative to minimizing a specified crosswind speed are described and illustrated with examples. The empirical procedure requires only hand calculations on an ordinary wind rose. The theoretical method utilizes wind statistics computed after the bivariate normal elliptical distribution is applied to a data sample of component winds. This method requires only the assumption that the wind components are bivariate normally distributed. This assumption seems to be reasonable. Studies are currently in progress for testing wind components for bivariate normality for various stations. The close agreement between the theoretical and empirical results for the example chosen substantiates the bivariate normal assumption.

TN D-7061 October 1972
The Optical Properties of Platinum and
Gold in the Vacuum Ultraviolet. Roger
C. Linton. Space Sciences Laboratory.

N72-33662

The optical constants of platinum and gold thin films have been determined in the spectral region of 40 to 200 nm by reflection measurements. The highly polarized continuum of synchrotron radiation emitted by the 240-MeV electron storage ring at the Physical Sciences Laboratory of the University of Wisconsin was used as a light source for the spectrum below 120 nm, while a windowless discharge lamp coupled to a normal incidence monochromator provided a source for the longer wavelengths. Optical constants were determined by a computer program based on iterative solutions to the Fresnel equations for reflection as a function of the angle of incidence.

TN D-7091 January 1973
Longitudinal Oscillation of Launch
Vehicles. Rudolf F. Glaser. Astronautics
Laboratory. N73-15924

During powered flight a vehicle may develop longitudinal self-excited oscillations, so-called "POGO" oscillations, of its structure. The energy supplying the vibration is tapped from the thrust by the activity of the system itself; that is, oscillation of the structure causes oscillation of the propellant system, especially of the pumps. In this way an oscillating thrust can be created that, by a feedback loop, may sustain the structural oscillation under certain circumstances. Two special features of the system prove to be essential for creation of instability. One is the effect of the inherent time interval that the thrust oscillation is lagging behind the structural oscillation. The other is the decrease of system mass caused by the exhausting of gas. The latter feature may cause an initially stable system to become unstable. To examine the stability of the system, a single mass-spring model, which is the result of a one-term Galerkin approach to the equation of motion, has been considered. The Nyquist stability criterion leads to a stability graph that shows the stability conditions in terms of the system parameter and also demonstrates the significance of time lag, feedback magnitude, and loss of mass. An important conclusion can be drawn from the analysis: large relative displacements of the pump-ergine masses favor instability. This is also confirmed by flight measurements. During some of the Apollo flights, severe POGO oscillations of the S-II stage occurred. The relative soft support of the center engines pin-ended crossbeam led to this bv

situation. Data obtained at the time the oscillation occurred show extremely large displacements of the crossbeam at the attachment point.

TN D-7115 December 1972

Minimum Weight Design of Structures
Via Optimality Criteria. J. Kiusalaas.

Astaonautics Laboratory. N73-14901

This report reviews the state of the art of automated structural design through the use of optimality criteria, with emphasis on aerospace applications. The contents include constraints on stresses, displacements, and buckling strengths under static loading, as well as lower bound limits on natural frequencies and flutter speeds. It is presumed that the reader is experienced in finite element methods of analysis, but is not familiar with optimal design techniques.

TN D-7159 February 1973

Development and Application of Vibroacoustic Structural Data Banks in Predicting Vibration Design and Test Criteria for Rocket Vehicle Structures.

H. J. Bandgren and W. C. Smith. Astronautics Laboratory. N73-20914

This report presents a method of predicting broadband random vibration criteria for components on space vehicles. Large amounts of vibration and acoustic data obtained from flights and static firing tests of space vehicles were formulated into vibroacoustic data banks for structural categories of ring frame, skin stringer, and honeycomb. The vibration spectra with their associated acoustic spectra are normalized to a reference acoustic spectrum. The individual normalized

spectra are grouped according to definite structural characteristics and statistically analyzed to form the vibroacoustic data banks in this report. These data banks represent the reference vibration criteria available for determining the new vehicle vibration criteria.

TN D-7178 February 1973
Hypervelocity Impact Testing of Cables.
David W. Jex, Albert B. Adkinson, James
E. English, and Carl E. Linebaugh. Space
Sciences Laboratory. N73-16186

This report presents the physics and electrical results obtained from simulated micrometeoroid testing of certain Skylab cables. The test procedure, electrical circuits, test equipment, and cable types utilized are also explained.

TN D-7195 March 1973
Calculation of Energy Deposition Distributions for Simple Geometries. John W. Watts, Jr. Space Sciences Laboratory.

N73-17832

When high-energy charged particles pass through a thin detector, the ionization energy loss in that detector is subject to fluctuations or "straggling" which must be considered in interpreting the data. This problem has been treated by Landau, Symon, Vavilov, and others. Under many conditions, which depend upon the charge and energy of the incident particle and the detector geometry, the ionization energy lost by the particle is different significantly from the energy deposited in the detector. Since most detectors respond according to the ionization energy deposited, the difference between energy lost in the detector and energy

deposited there must be considered. This difference is caused by high-energy secondary electrons produced in the ionization process that travel far from their point of production, often leaving the detector. This problem divides naturally into a calculation of the energy loss that results in excitation and low-energy secondary electrons which do not travel far from their production points, and a calculation of energy loss that results in high-energy secondary electrons which can escape from the detector. The first calculation is performed using a modification of the Vavilov energy loss distribution. A cutoff energy is introduced above which all electrons are ignored and energy transferred to low energy particles is assumed to be equivalent to the energy deposited by them. For the second calculation, the trajectory of the primary particle is considered as a source of secondary high-energy electrons. The electrons from this source are transported using Monte Carlo techniques and multiple scattering theory, and the energy deposited by them in the detector is calculated. The results of the two calculations are then combined to predict the energy deposition distribution. The results of these calculations are used to predict the charge resolution of parallel-plate pulse ionization chambers that are being designed to measure the charge spectrum of heavy nuclei in the galactic cosmic-ray flux.

TN D-7200 March 1973
Proposal for Hierarchical Description of
Software Systems. H. Trauboth. Computation Laboratory. N73-21200

The programming of digital computers has developed into a new dimension full of difficulties, because the hardware of

computers has become so powerful that more complex applications are entrusted computers. The costs of software development, verification, and maintenance outpacing those of the hardware and the trend is toward further increase of sophistication of application of computers and consequently of sophistication of software. To obtain better visibility into software systems and to improve the structure of software systems for better tests, verification, and maintenance, a clear, but rigorous description and documentation of software is needed. The purpose of this report is to extend the present methods in order to obtain a documentation that better reflects the interplay between the various components and functions of a software system at different levels of detail without losing the precision in expression. This is done by the use of block diagrams, sequence diagrams, and cross-reference charts. In the appendices, examples from an actual large software system, i.e., the Marshall System Aerospace Systems Simulation (MARSYAS), are presented. The proposed documentation structure is apt to automation of updating significant portions of the documentation for better software change control. This report should also stimulate research into new practical methods and principles for the development, verification, and maintenance of complex software systems.

TN D-7240

May 1973

Retrieval of Dispersive and Convective Transport Phenomena in Fluids Using Stationary and Nonstationary Time Domain Analysis. J. Briscoe Stephens and Robert M. St. John. Aero-Astrodynamics Laboratory. N73-25284

Simultaneously occurring dispersive and convective components of fluid kinematics are obtained by a time domain analysis of optically retrieved temporal histories of the transport phenomena. Utilizing triangulation of collimated optical fields of view from two radiometers to obtain the temporal histories of the intensity fluctuations associated with the transport phenomena has enabled investigators to retrieve the local convective transport by employing correlation statistics. The location of the peak in the covariance curve determines the transit time from which the convection velocity is calculated; whereas, the change in shape of the peak in the covariance curve determines the change in average frequency of the wave packet from which the dispersion velocity is calculated. Thus, our two-component analysis requires the maximum possible enhancement of the delineation for the transport. The convection velocity is the result of a fixed reference frame calculation; whereas, the dispersion velocity is the result of a moving reference frame calculation. This moving reference frame is constrained to move along the streamline the convection common at velocity. The transport probability has been developed as an estimate of whether the transport phenomena have been measured along the common stream, and also provides an indication of whether the period of stationarity is sufficient to provide adequate information enhancement. The time information is suppressed by the utilization of a fourth-order autocovariance curve. moving frame delineation is analyzed in the time domain with the wave packet algorithm for the dispersion parameters. The effectiveness of these models is demonstrated on empirical data sets obtained in glow discharge

investigations, cold jet experiments, and air quality investigations.

TN D-7263 June 1973
A Study of Zodiacal Light Models. G. A.
Gary and P. D. Craven. Space Sciences
Laboratory. N73-26843

This report presents a review of the basic equations used in the analysis of photometric observations of zodiacal light. A survey of the methods used to model the zodiacal light in and out of the ecliptic is given. Results and comparison of various models are presented, as well as recent results by the authors.

TN D-7312 May 1973
Unsupervised Spatial Clustering with Spectral Discrimination. Robert R. Jayroe, Jr. Aero-Astrodynamics Laboratory. N73-24410

The recent development of manned and unmanned space vehicles has brought about an almost unprecedented advance in studies of remotely sensed earth observations. These observations require a multidisciplinary study which includes such fields as agriculture, demography, cartogforestry. geography. raphy, geology, meteorology, hydrology, oceanography, environmental quality, ecology, sensor technology, and interpretation techniques development. With this unprecedented advance comes an unprecedented amount of data. The problem arises of how to analyze and extract information from such large volumes of data in an efficient manner. The main emphasis of this work development of a computer program for extracting features from remotely sensed data presented in digital image form.

computer program requires no human supervision or prejudgment and operates unassisted on the raw digital data. The presentation of this work also includes a condensed general background on remote sensing of earth features and a short synopsis on some of the most commonly used types of feature extraction techniques. This discussion is followed by a presentation of results obtained from the unsupervised feature extraction computer program along with a description and listing of the computer program.

TN D-7317 June 1973

Measurements of the Performance of Multiwire Proportional Chambers. R. W. Austin, A. Aglitis, J. C. Gregory, S. A. Metzger, T. A. Parnell, H. F. Rutledge, W. Selig, and N. P. Cumings. Space Sciences Laboratory. N73-24816

This report presents data that may be useful in formulating engineering specifications and test procedures for the proportional counter hodoscope to be flown as part of the High Energy Cosmic Ray Experiment on the High Energy Astronomy Observatory (HEAO), Mission A. A collection of preliminary data taken in laboratory tests of multiwire counters with an anode wire spacing of 5 mm and cathode gap spacing of 1 cm is presented. The data are from laboratory development models or counters for balloon flights and were selected to illustrate several aspects of proper and improper counter performance. Most of the were taken from a large proportional counter hodoscope which has an active area of 0.5 by 0.5 m and 104 wires per plane.

TN D-7318 June 1973
Axisymmetric Oscillation of a Partially
Liquid-Filled Cylindrical Shell Container
Having Hemispherical Bulkheads. Rudolf
F. Glaser. Astronautics Laboratory.

N73-25925

The longitudinal oscillations of launch vehicles represent an area of concern. During liftoff or cutoff. longitudinal vibrations occur as transients and may cause considerable dynamic loads. However, longitudinal oscillation can also be excited during powered flight. From experience it is well known that under certain circumstances energy can be tapped by the activity of the itself and can produce undesirable self-excited oscillation, the socalled "pogo" oscillation of the vehicle structure. Thus, it is understandable that the longitudinal dynamics of vehicles have received continued attention over the last years. A simplified vehicle model must be used to analyze the longitudinal dynamic behavior of vehicles or, in other words, to determine the longitudinal frequencies and

mode shapes. Usually only a few of the fundamental modes are of interest; thus, only significant dynamic properties must considered. The liquid propellants constitute a high percentage of the overall vehicle masses throughout much of the powered flight time and, coupled with the solid vehicle masses and springs, may generate the fundamental modes of the entire vehicle. Thus, the correct comprehension of the liquid oscillation inside the elastic container is extremely important. In this report a spring-supported, cylindrical container of the length I having hemibulkheads spherical is considered. The analysis, however, is also valid for l = 0, which represents the cases of sphere and hemisphere. Α computer program numerical evaluation of the analysis contained in this report can be found in the contractor report, Axisymmetric Oscillation of a Partially Liquid-Filled Cylindrical Shell Container Having Hemispherical Bulkheads: Computer Program and Numerical Evaluation, Dwight Caughfield of the Department of Mathematics, Abilene Christian College, Abilene, Texas.

NASA TECHNICAL REPORTS

TR R-387 August 1972

Maximum Range Three-Dimensional
Lifting Planetary Entry. E. D.
Dickmanns. Aero-Astrodynamics
Laboratory. N72-29845

Variational equations for maximum range three-dimensional quasisteady glide are given. Nonlinear oscillatory maximum range trajectories obtained with a refined gradient program are approximated by a superposition of quasisteady glide and linearized perturbation equation results. A "basic" control law is found which is closely followed for maximum cross-range trajectories. The effect of a reradiative heating constraint involving velocity, altitude and angle of attack on a maximum cross-range trajectory for a Space Shuttle orbiter-type vehicle reentering the earth's atmosphere is investigated numerically.

TR R-393 December 1972

A Study of the Microstructure and Optical Properties of Thin Lead-Dielectric Cermet Films. Robert B. Owen. Astrionics Laboratory.

N73-12811

transmission electron microscopy study involving direct and replicating techniques is directed to a definition of the microstructure of radio frequency-sputtered, lead-dielectric cermet films. defined, this microstructure is used to obtain theoretical film refractive indices. Maxwell Garnett theory provides a basis for the theoretical results. Measurements of film transmission and reflectivity are used to obtain rough experimental values for film refractive indices by the Tekucheva method. More exact values are obtained

ellipsometry. The rough Tekucheva values are used to determine the range over which computer calculations interpreting the ellipsometric results must be made. This technique vields accurate values for the film refractive The films are radio frequencysputtered from lead glass targets with varying amounts of lead attached to their faces. Three different targets are used, resulting in three sets of films, each containing a different percentage of lead. The lead content of the films is measured by microprobe analysis as well as visual inspection of micrographs. The lower content lead films are seen to consist of tiny balls of lead embedded in the dielectric, as are the intermediate lead content films, but the higher lead content films form metallic networks throughout the dielectric. The lower and intermediate lead content films have indices which agree with the predictions of the Maxwell Garnett theory, but the higher lead content films, whose structure fails to conform to the Maxwell Garnett configuration, have indices whose values diverge from the Maxwell Garnett predictions. It is thus shown that the theory of Maxwell Garnett is valid for thin cermet films whose structure consists of tiny metal balls embedded in a dielectric medium.

TR R-401 December 1972

Mobility Performance of the Lunar
Roving Vehicle: Terrestrial Studies —
Apollo 15 Results. Nicholas C. Costes,
John E. Farmer, and Edwin B. George.
Space Sciences Laboratory and Astrionics Laboratory.

N73-16817

The constraints of the Apollo 15 mission dictated that the average and limiting performance capabilities of the first manned

NASA TECHNICAL REPORTS

Lunar Roving Vehicle, when operated on the lunar surface, be known or estimated within narrow margins. For this reason, extensive studies were conducted during the year preceding the Apollo 15 launch and are described herein. The results of these studies are compared with the actual performance of the Lunar Roving Vehicle during Apollo 15 mission. From this comparison, conclusions are drawn relating to the capabilities and limitations of current terrestrial methodology in predicting the mobility performance of lunar roving vehicles under in-situ environmental conditions, and recommendations are offered concerning the performance of surface vehicles on future missions related to lunar or planetary exploration.

TR R-404 March 1973
The Techniques of Holographic Particle
Sizing. Robert L. Kurtz. Space Sciences
Laboratory. N73-18448

Depending on the mechanism of particle production, the resultant particle size and velocity distribution may range over several orders of magnitude. In general, if particle size information is desired from a given type generator, one must resort to some form of experimental determination of the distribution. If the source of particle production is a dynamic one involving a reasonable volume, holography provides a tailor-made particle size and velocity distribution detector. This is evidenced by the fact that holography allows the entire volume to be recorded on one exposure without any interference with the volume of interest. Herein lies a very important characteristic of the holographic particle detection technique: It provides a

holographic nondestructive testing technique in the fullest sense of the definition of nondestructive testing. This report provides a description of three different systems useful in this technique and includes the experimental results from one of the holographic systems which was used to detect particle size and velocity distribution from the Skylab waste tank.

TR R-410

Classical Eighth- and Lower-Order
Runge-Kutta-Nyström Formulas with a
New Stepsize Control Procedure for
Special Second-Order Differential Equations. Erwin Fehlberg. Computation
Laboratory.

N73-24614

New Runge-Kutta-Nyström formulas of the eighth, seventh, sixth, and fifth order are derived for the special second-order (vector) differential equation $\ddot{x} = f(t,x)$. In contrast to Runge-Kutta-Nyström formulas of an earlier NASA report by this author, these formulas provide a stepsize control procedure based on the leading term of the local truncation error in x. This new procedure is more accurate than the earlier Runge-Kutta-Nyström procedure of this author (with stepsize control based on the leading term of the local truncation error in x) when integrating close singularities. Two central orbits presented as examples. For these orbits, the accuracy and speed of the formulas of this report are compared with those of Runge-Kutta-Nyström and Runge-Kutta formulas of earlier NASA reports by this author.

TR R-414 June 1973
Digital Simulation of the Serpentuator
Using MARSYAS. Sudarshan P. Singh.
Computation Laboratory. N73-25210

NASA TECHNICAL REPORTS

Serpentuator is a serpentine teleoperator device for intravehicular and extravehicular activities in space. The serpentuator is simulated using the digital simulation software system MARSYAS and using the Component-Connection Simulation model and the Direct Simulation model. A comparison of the

results for the two cases shows that under identical conditions, simulation execution time in the Component-Connection model case is reduced by a factor of the order of 100. A visual display of the serpentuator positions is obtained using the AMTRAN system on the Datacraft DC 6024 computer.

NASA SPECIAL PUBLICATIONS

SP-299

1973

SP-313

1972

Holography and Optical Filtering. Proceedings of a conference sponsored by the National Aeronautics and Space Administration and the Optical Society of America and held at the Marshall Space Flight Center, Huntsville, Alabama, May 24-25, 1971. N73-25540

Space for Mankind's Benefit. Proceedings of a space congress held November 15-19, 1971, at Huntsville, Alabama, sponsored by the National Aeronautics and Space Administration and the Huntsville Association of Technical Societies. Jesco von Puttkamer and Thomas J. McCullough, eds. Center Plans and Resources Control Office.

(Abstracts for these reports may be obtained from STAR.)

- CR-2072 July 1972 Correlation of Stress-Wave-Emission Characteristics with Fracture in Aluminum Alloys. Final Report. NAS8-21405. Aerojet Solid Propulsion Co. N72-30470
- CR-2078 August 1972
 Project Fog Drops, Part I: Investigations of Warm Fog Properties. NASW-2126.
 Cornell Aeronautical Lab. N72-30554
- CR-2160 January 1973
 Extravehicular Activities Guidelines and
 Design Criteria. NAS8-27502. URS/
 Matrix Co. N73-15858
- CR-2162 December 1972
 Evaluation of Cryogenic Insulation
 Materials and Composites for Use in
 Nuclear Radiation Environments.
 NAS8-18024. Convair Div. of General
 Dynamics. N73-14707
- CR-2173 January 1973
 Computer Programs for the Solution of Systems of Linear Algebraic Equations.
 NCA8-44. Memphis State University.

N73-17181

CR-2182 January 1973

A Boundary Layer Approach to the Analysis of Atmospheric Motion Over a Surface Obstruction. NAS8-27387. The University of Tennessee Space Inst.

N73-16244

CR-2189 January 1973
Atmospheric Energetics as Related to
Cyclogenesis over the Eastern United
States. NAS8-26751. Texas A&M University. N73-16607

- CR-2192 January 1973

 An Investigation of the Sutcliffe
 Development Theory. NAS8-26751.

 Texas A&M University. N73-16605
- CR-2193 February 1973
 Processing for Spaceborne Synthetic
 Aperture Radar Imagery. NAS8-21805.
 Computer Sciences Corp. N73-18202
- CR-2201 February 1973
 A Field Investigation and Numerical
 Simulation of Coastal Fog. NAS8-27999.
 Cornell Aeronautical Lab. N73-18648
- CR-2203 February 1972
 Short and Long Period Atmospheric
 Variations Between 25 and 200 km.
 NAS8-26658. Georgia Inst. of Technology.
 N73-17504
- CR-2212 March 1973
 Computerized Logic Design of Digital
 Circuits. NAS8-21812. Sperry Rand
 Corp. N73-19230
- CR-2213 April 1973
 Digital Processing of Radiographic Images. NAS8-21805. Computer Sciences Corp. N73-22135
- CR-2223 March 1973
 Specification of Mesospheric Density,
 Pressure, and Temperature by Extrapolation. NAS8-21810. Northrop Services,
 Inc. N73-21364
- CR-2248 May 1973
 An Innovative Approach to Compensator
 Design. Final Report. NAS8-21377.
 Mississippi State University. N73-25651

CR-2269 May 1973

A Numerical Solution for Thermoacoustic Convection of Fluids in Low
Gravity. NAS8-27015. Lockheed Missiles
and Space Co. N73-26289

CR-2280 June 1973
Estimation in a Modified Binomial
Distribution. NAS8-29286. Appalachian
State University. N73-25678

CR-120003 October 1972 Aerodynamic Stability and Control Characteristics of the **TBC** Shuttle AR-11981-3. NAS8-4016. Booster Chrysler Corp. N72-33871

CR-120008 June 1972 Space Shuttle: Space Shuttle Abort Separation Pressure Investigation. Vol. I; Parts A and B: Booster Data at Mach 5. NAS8-4016. Chrysler Corp.

Part A N72-27924 Part B N72-27925

CR-120023 October 1972
An Investigation of the Landing Characteristics of the NASA-MSC August 1969
Baseline Orbiter Configuration in Ground Effect. NAS8-4016. Chrysler Corp.

N72-33869

CR-120025

Heat Transfer Rate Distribution on McDonnell Douglas Delta Wing Orbiter Determined by Phase-Change Paint Technique for Nominal Mach Number 8. NAS8-4016. Chrysler Corp. N72-30908

CR-120034 January 1973
Pressure Investigation of a Space Shuttle
Launch Configuration Consisting of a

Delta-Wing Orbiter and Swept-Wing Booster with Canard and Tip Fins. NAS8-4016. Chrysler Corp.

Vol. 1, Part A N73-20891 Vol. 1, Part B N73-20892

CR-120056 August 1972
Aerodynamic Characteristics of a
156-Inch Solid Rocket Motor at Angles
of Attack from -10° to 190°.
NAS8-4016. Chrysler Corp. X72-10609

CR-120057 August 1972
Aerodynamic Characteristics of a Double
Delta Wing Space Shuttle Orbiter
(M = 0.6 - 5.0). NAS8-4016. Chrysler
Corp. N72-29875

CR-120058 March 1973
Space Shuttle: An Investigation of the Load Distribution Over the SRB and External Tank of a 0.004 Scale Model of the 0.49 Space Shuttle Launch Configuration. NAS8-4016. Chrysler Corp.

N73-23872

CR-120061 June 1972
Space Shuttle: Space Shuttle Abort
Separation Pressure Investigation. Vol. 2:
Orbiter Data at Mach 5. NAS8-4016.
Chrysler Corp. Part A N72-28877
Part B N72-27926

CR-120062 June 1972
Space Shuttle: Space Shuttle Abort
Separation Pressure Investigation. Vol. 3:
Booster Data at Mach 3. NAS8-4016.
Chrysler Corp. N72-27927

CR-120063 June 1972 Space Shuttle: Space Shuttle Abort Separation Pressure Investigation. Vol. 4:

Orbiter Data at Mach 3. NAS8-4016. Chrysler Corp. N72-27928 Delta Orbiters (M = 8). NAS8-4016. Chrysler Corp. N72-27935

- CR-120064 June 1972
 Space Shuttle: Space Shuttle Abort
 Separation Pressure Investigation. Vol. 5:
 Booster Data at Mach 2. NAS8-4016.
 Chrysler Corp. N72-27929
- CR-120065 June 1972
 Space Shuttle: Space Shuttle Abort
 Separation Pressure Investigation. Vol. 6:
 Orbiter Data at Mach 2. NAS8-4016.
 Chrysler Corp. N72-27930
- CR-120066 January 1973
 Space Shuttle: Preliminary Pressure
 Distributions on the 049 Orbiter, Orbiter
 in Presence of H/O Tank and Orbiter in
 Launch Configuration. NAS8-4016.
 Chrysler Corp. N73-20890
- CR-120070 November 1972
 Space Shuttle: Aerodynamic Stability,
 Control Effectiveness and Drag Characteristics of a Shuttle Orbiter Configuration at Mach Numbers from 0.6 to
 4.96. NAS8-4016. Chrysler Corp.

N73-12923

- CR-120071

 Ascent Heat Transfer Rate Distribution on the North American Rockwell Delta Wing Orbiter and the General Dynamics/ Convair Booster at a Mach Number of 8 (Not Mated). NAS8-4016. Chrysler Corp. N72-29865
- CR-120072 July 1972 Space Shuttle: Heat Transfer Distributions on the LMSC 040C and 040-L4

CR-120073 October 1972
Space Shuttle: Stability and Control
Effectiveness at High and Low Angles of
Attack and Effects of Variations in
Engine Shroud, Fin and Drag Petal
Configurations for the Boeing
0.008899-Scale Pressure-Fed Ballistic
Recoverable Booster Model 979-160.
NAS8-4016. Chrysler Corp. N73-11896

CR-120074 October 1972
Space Shuttle: Performance, Static
Stability, and Control Effectiveness of a
Parametric Space Shuttle Launch
Vehicle. NAS8-4016. Chrysler Corp.

N72-33870

- CR-120075 December 1972
 Space Shuttle: Static Surface Pressures
 of the 0.004 Scale 049 Orbiter in the
 Launch Configuration. NAS8-4016.
 Chrysler Corp. N73-14879
- CR-120076 September 1972 Space Shuttle: Static Stability and Control Effectiveness of the 040A Delta Wing Orbiter (M = 0.6 to 4.96). NAS8-4016. Chrysler Corp. X72-10612
- CR-120078

 Space Shuttle: Re-Entry Stability in Nose Forward and Base Shield-Forward Orientations and the Effectiveness of Drag Devices for the Boeing 0.00694-Scale Ballistic Recoverable Booster, Model 979-071. NAS8-4016. Chrysler Corp.

 X72-10654

- CR-120080 October 1972
 Space Shuttle: A Comparison of Wind
 Tunnel Facility Data on the Grumman
 H-33 Delta Wing Orbiter. NAS8-4016.
 Chrysler Corp. N73-10889
- CR-120081 October 1972
 Space Shuttle: A Comparison of Wind
 Tunnel Facility Data on the 040A Space
 Shuttle Orbiter Configuration.
 NAS8-4016. Chrysler Corp. N73-10894
- CR-120082 November 1972
 Space Shuttle: Longitudinal Aerodynamic Characteristics of Low Aspect
 Ratio Wing Configuration in Ground
 Effect for a Moving and Stationary
 Ground Surface. NAS8-4016. Chrysler
 Corp. N73-11895
- CR-120083 October 1972
 Space Shuttle: Aerodynamic Characteristics of Various MDAC Space Shuttle
 Ascent Configurations With Parallel Burn
 Pressure-Fed and SRM Boosters. Vol. 1:
 Tanks T1 and T2 Ascent Configurations.
 NAS8-4016. Chrysler Corp. N73-11901
- CR-120084 October 1972
 Space Shuttle: Aerodynamic Characteristics of Various MDAC Space Shuttle
 Ascent Configurations with Parallel Burn
 Pressure-Fed and SRM Boosters. Vol. 2:
 Tank T3 Configurations. NAS8-4016.
 Chrysler Corp. N73-11902
- CR-120085 October 1972
 Space Shuttle: Aerodynamic Characteristics of Various MDAC Space Shuttle
 Ascent Configurations with Parallel Burn
 Pressure-Fed and SRM Boosters. Vol. 3:

- Tank T4 Configurations. NAS8-4016. Chrysler Corp. N73-11903
- CR-120086 October 1972
 Space Shuttle: Aerodynamic Characteristics of Various MDAC Space Shuttle
 Ascent Configurations with Parallel Burn
 Pressure-Fed and SRM Boosters. Vol. 4:
 Ascent Configuration Plume Studies and
 Model Buildup. NAS8-4016. Chrysler
 Corp. N73-11904
- CR-120087 October 1972 Shuttle: Aerodynamic Characteristics of Various MDAC Space Shuttle Ascent Configurations with Parallel Burn Pressure-Fed and SRM Boosters. Vol. 5: Orbiter. Tanks and Booster Alone Configurations. NAS8-4016. Chrysler N73-11905 Corp.
- CR-120088 December 1972
 Aerodynamic Static Stability and Control Effectiveness of a Parametric Shuttle
 Launch Configuration. NAS8-4016.
 Chrysler Corp. N73-13910
- CR-120089 April 1973
 Space Shuttle (ATP Configuration)
 Abort Staging Investigation.
 NAS9-13247. Chrysler Corp. N73-21831
- CR-120090 March 1973
 Space Shuttle: Aerodynamic Characteristics of a 162-Inch Diameter Solid
 Rocket Booster With and Without
 Strakes. NAS9-13247. Chrysler Corp.
 N73-20888
- CR-120092 March 1973 Results of Investigations on a 0.0405 Scale Model ATP Version of the NR-SSV

Orbiter in the North American Aeronautical Laboratory Low Speed Wind Tunnel. NAS9-13247. Chrysler Corp.

N73-21832

- CR-120179

 Space Shuttle: Aerodynamics in Nose-First, Nozzle-First, and Tumbling Re-Entry Modes and Effectiveness of Several Drag Devices for the Boeing 0.0144 Scale Parallel Burn Solid Rocket Motor, Model 979-185. NAS8-4106. Chrysler Corp.

 X72-10605
- CR-123719 April 1972
 Space Station Executive Summary.
 NAS8-25140. McDonnell Douglas Astronautics Co. N72-27912
- CR-123720 May 1972
 Conjugate Gradient Optimization
 Programs for Shuttle Reentry. Final
 Report. NAS8-26929. University of
 Michigan. N72-26716
- CR-123721 July 12, 1972
 Suppression of Combustion Oscillations
 With Mechanical Damping Devices. Final
 Report. NAS8-21310. Pratt and Whitney
 Aircraft. N72-26958
- CR-123723 November 1971 Sounding Rocket Flight Report MUMP 9 and MUMP 10. NAS8-21086. University of Michigan.
- CR-123724 June 1972 Summary of Moderate Depth Lunar Drill Development Program from its Conception to 1 July, 1972. NAS8-26487. Westinghouse Electric Corp. N72-27526

- CR-123725 June 1, 1972
 Establishment of Design Criteria for
 Acceptable Failure Modes and Fail Safe
 Considerations for the Space Shuttle
 Structural System. Final Report.
 NAS8-27269. North American Rockwell
 Corp. N72-28889
- CR-123726 January 1972
 Research on Bearing Lubricants for Use in High Vacuum. Annual Summary Report. NAS8-26619. Midwest Research Inst. X72-10444
- CR-123727 March 10, 1972 A 156-in-dia SRM Mass Properties Report. NAS8-28428. Aerojet Solid Propulsion Co. N72-28789
- CR-123728 March 1972 Study of Solid Rocket Motor for Space Shuttle Booster. Vol. 2, Book 3, Appendix A. NAS8-28430. Thiokol Chemical Corp. N73-24799
- CR-123729 March 15, 1972 Study of Solid Rocket Motor for Space Shuttle Booster. Vol. 2, Technical Book 1 of 5. NAS8-28430. Thiokol Chemical Corp.
- CR-123730 March 15, 1972 Study of Solid Rocket Motor for Space Shuttle Booster. Vol. 2, Technical Book 5, Appendices E thru H. NAS8-28430. Thiokol Chemical Corp. N73-24801

CR-123731 August 20, 1971 Apollo 14 Composite Casting Demonstration. Final Report. NAS8-26637.

Arthur D. Little, Inc.

- CR-123732 September 1971
 Test and Evaluation of Apollo 14
 Composite Casting Demonstration
 Specimens 6, 9, and 12. Final Report.
 NAS8-27085. TRW, Inc.
- CR-123733 May 12, 1972
 Research and Applications Modules
 (RAM) Phase B Study. Executive
 Summary. NAS8-27539. Convair Div. of
 General Dynamics. N72-27919
- CR-123734 December 1972 Long Life High Reliability Thermal Control Systems Study Data Handbook. NAS8-26252. General Electric Co.

N72-28913

- CR-123735 June 1972
 Shuttle Operations Simulation Model
 Programmers/Users Manual. Summary
 Report. NAS8-21804. Teledyne Brown
 Engineering. N72-28200
- CR-123736 May 17, 1972
 Reliability Techniques for Computer
 Executive Programs. Summary Report.
 NAS8-26669. Information Research
 Associates. N72-28196
- CR-123737 March 1972 Life Sciences Payload Definition and Integration Study. Vol. 3: Appendices. NAS8-26468. General Dynamics.

N72-28089

CR-123738 March 1972
Life Sciences Payload Definition and
Integration Study. Vol. 1: Management
Summary. NAS8-26468. General
Dynamics. N72-28087

- CR-123739 March 1972
 Life Sciences Payload Definition and
 Integration Study. Vol. 2: Requirements
 and Design Studies. NAS8-26468.
 General Dynamics. N72-28088
- CR-123740 June 13, 1972 Study of the Production of Unique New Glasses. Final Report. NAS8-28014. North American Rockwell Corp.

CR-123741 April 1972
Teleoperator Technology and System
Development. Final Report. Vol. 1.
NAS8-27021. Bell Aerospace Corp.

N72-28090

CR-123742 May 15, 1972
Development of Chip Passivated Monolithic Complementary MISFET Circuits
With Beam Leads. Final Report.
NAS8-26498. General Electric Co.

N72-28497

- CR-123743 May 15, 1972
 Research Study on Stellar X-Ray
 Imaging Experiment. Vol. 1.
 NAS8-24385. American Science and
 Engineering Corp. N72-29465
- CR-123744 April 1972
 The Use of Linear Programming Techniques To Design Optimal Digital Filters for Pulse Shaping and Channel Equalizations. NAS8-20172. University of Alabama. N72-29194
- CR-123745 March 31, 1972
 Determination of Design Allowable
 Strength Properties of Elevated

Part 1: Coated Temperature Alloys. NAS8-26266. Martin Marietta Corp. Columbium Alloys. NAS8-26325. N72-29772 Battelle Memorial Inst. N72-29891 CR-123753 February 1972 CR-123746 May 1972 Station User's Handbook. Space Prototype Data Terminal Multiplexer NAS8-25140. McDonnell Douglas Astro-Demultiplexer. Final Report. nautics Co. N72-29860 NAS8-27538. Martin Marietta Corp. N72-29115 CR-123754 June 1972 Teleoperator System Man-Machine Inter-CR-123747 face Requirements for Satellite Retrieval April 30, 1972 An Innovative Approach to Compensator and Servicing. Vol. 1: Requirements. Design. Interim Report. NAS8-21377. NASw-2220. Essex Corp. N72-29829 Mississippi State University. N72-29160 CR-123755 June 1972 CR-123748 April 1972 Teleoperator System Man-Machine Interface Requirements for Satellite Retrieval Teleoperator Technology and System Development. Final Report. Vol. 2: and Servicing. Vol. 2: Design Criteria. NASw-2220. Essex Corp. Appendix E. NAS8-27021. Bell Aero-N72-29830 N72-31236 space Co. CR-123756 June 28, 1972 June 23, 1972 CR-123749 Beryllium Heat Shield Technology in the Area of Thermal Protection Devices. In-Space Propellant Logistics and Safety in Space Propellant Logistics. Vol. 3: NAS8-27016. Martin Marietta Corp. Trade Studies. NAS8-27692. N72-30947 North American Rockwell Corp. N72-30802 CR-123757 1971 CR-123750 **April** 1972 Development of Thermally Resistant Study of Requirements for Assembly Phosphonitrile Polymers. NAS8-25184. and Docking of Spacecraft in Earth Horizons, Inc. X72-10568 Orbit. Vol. 2: Handbook of Orbital Assembly and Docking Requirements. CR-123758 January 1972 NAS8-27860. Grumman Aerospace Corp. Space Station User's Handbook. X72-10578 NAS8-25140. McDonnell Douglas Astro-N72-29859 nautics Co. CR-123751 March 10, 1972 Extravehicular Activities Guidelines and CR-123759 December 1972 Criteria. NAS8-27502. Matrix Modular Space Station Program Option. Design NAS8-25140. Corp. Summary Report.

May 1972

Report.

Investigation of Characteristics of Feed

Final

Instabilities.

McDonnell Douglas Astronautics Co.

N72-32842

CR-123752

System

- CR-123760 June 19, 1972 Space Station Data Flow. NAS8-26798. IBM Corp. N72-29862
- CR-123761 June 26, 1972
 Study of Effects of Uncertainties on
 Comet and Asteroid Encounter and
 Contact Guidance Requirements.
 NAS8-27664. Auburn University.

X72-10581

- CR-123762 June 1972
 Design, Manufacture, Development, Test, and Evaluation of Boron/Aluminum Structural Components for Space Shuttle. NAS8-27738. Convair Div. of General Dynamics. X72-10565
- CR-123763

 Establishment of Design Criteria for Acceptable Failure Modes and Fail Safe Considerations for the Space Shuttle Structural System. Final Report. NAS8-27269. North American Rockwell Corp.
- CR-123764 June 23, 1972
 In Space-Propellant Systems Safety.
 Vol. 1: Executive Summary.
 NAS8-27692. North American Rockwell
 Corp. N72-30797
- CR-123765 June 23, 1972 In-Space Propellant Logistics. Vol. 5: Cost Estimates. NAS8-27692. North American Rockwell Corp. X72-10582
- CR-123766 June 23, 1972 In-Space Propellant Systems Safety. Vol. 2: System Safety Guidelines and

- Requirements. NAS8-27692. North American Rockwell Corp. N72-30798
- CR-123767 June 23, 1972
 In-Space Propellant Logistics. Vol. 2:
 Technical Report. NAS8-27692. North
 American Rockwell Corp. N72-30801
- CR-123768 June 23, 1972
 In-Space Propellant Logistics. Vol. 4:
 Project Planning Data. NAS8-27692.
 North American Rockwell Corp.

N72-30803

- CR-123769 June 23, 1972
 In-Space Propellant Systems Safety.
 Vol. 3: System Safety Analysis.
 NAS8-27692. North American Rockwell
 Corp. N72-30799
- CR-123770 May 1972 Dynamic Holographic Storage in Lithium Niobate. NAS8-26635. Isomet Corp. N72-30444
- CR-123771 June 1972
 Infrared and Photoelectric Photometer
 Development. Final Report.
 NAS8-26344. Teledyne Brown Engineering. X72-78847
- CR-123772 May 1972

 Materials Data Handbook: Aluminum
 Alloy 6061. NAS8-26644. Western
 Applied Research and Development, Inc.
 N72-30458
- CR-123773 April 1972 Materials Data Handbook: Aluminum Alloy 7075. NAS8-26644. Western

Applied Research and Development, Inc. Final Report. NAS8-27437. Convair Div. N72-30459 of General Dynamics. CR-123774 April 1972 CR-123782 June 1972 Materials Data Handbook: Inconel Alloy Fabrication, Test, and Demonstration of 718. NAS8-26644. Western **Applied** Critical Environment Monitoring System. Research and Development, Inc. NAS8-27300. Lockheed Missiles and N72-30460 Space Co. N72-30389 CR-123775 May 1972 CR-123783 December 1971 Materials Data Handbook: Digital Control System Development for Titanium 6Al-4V. NAS8-26644. Western Applied Optical Mirror Figure Control. Research and Development, Inc. NAS8-27620. Massachusetts Inst. of X72-10559 N72-30464 Technology. CR-123776 June 1972 CR-123784 June 23, 1972 Materials Data Handbook: Stainless Steel In-Space Propellant Logistics. Vol. 1: Executive Summary. NAS8-27692. North A-286. NAS8-26644. Western Applied Research and Development, Inc. American Rockwell Corp. N72-30800 N72-30463 CR-123785 May 12, 1972 CR-123777 March 1972 Research and Applications Modules Materials Data Handbook: Aluminum (RAM), Phase B Study. NAS8-27539. General Dynamics. 2219. NAS8-26644. Western N72-30861 Applied Research and Development, Inc. N72-30461 CR-123786 June 1972 Application of the QSDC Procedure to the Formulation of Space Shuttle Design CR-123779 May 1972 Vol. 2: Applications Materials Data Handbook: Aluminum NAS8-26918. Technology, Inc. 2014. NAS8-26644. Western Applied Research and Development, Inc. N72-30857 N72-31535 CR-123787 June 1972 CR-123780 April 1972 Application of the QSDC Procedure to Materials Data Handbook: Stainless Steel the Formulation of Space Shuttle Design 301. NAS8-26644. Western Criteria. Vol. 1: Study Effort. NAS8-26918. Technology, Inc. Applied Research and Development, Inc. N72-30462 N72-30856 CR-123788 CR-123781 June 1972 December 1971

A Method for Determining the Response

Fatigue of Boron/Aluminum Composites.

CR-123795

of Space Shuttle to Atmospheric Turbulence. Vol. 2. NAS8-26363. General Dynamics. N72-30859	CR-123795 July 4, 1972 Design and Control of Remote Manipulators. NAS8-28055. Massachusetts Inst.
CR-123789 July 1972	of Technology. N72-30424
Simulation of a Flexible Spinning Vehicle. Final Report. NAS8-26700. McDonnell Douglas Astronautics Co. N72-30855	CR-123796 May 1972 Development of AMTRAN on the Datacraft DC6024. NAS8-26756. Tele- dyne Brown Engineering. N72-30190
CR-123790 June 1972 Solenoid Valve, Type 1, NASA P/N 20M32258-1 (Carleton P/N 2426-0001-1). NAS8-26348. Carleton Controls Corp. N72-30425	CR-123797 May 1972 Electromagnetic Damper System for Ground Wind Load Studies. NAS8-26774. Lockheed Missiles and Space Co. N72-30388
CR-123791 June 1972 Synthesis of Shuttle Vehicle Damping Using Substructure Test Results. NAS8-27569. Southwest Research Inst. N72-30860	CR-123798 Design and Development of Polyphenylene Oxide Foam as a Reusable Internal Insulation for LH ₂ Tanks, Phase One, Progress Report. NAS8-27566. Convair Div. of General Dynamics. X72-10566
CR-123792 June 1972 Shuttle Free-Flying Teleoperator System Experiment Definition. Vol. 3: Program Development Requirements. NAS8-27895. Bell Aerospace Co. N72-30217	CR-123799 April 15, 1972 Unsupervised Classification of Remote
•	CR-123800 1967
CR-123793 June 1972 Shuttle Free-Flying Teleoperator System Experiment Definition. Vol. 1: Executive Summary. NAS8-27895. Bell Aerospace Co. N72-30216	Early Lunar Shelter Design and Comparison Study. Vol. 4. NAS8-20261. AiResearch Manufacturing Co. N72-74858 CR-123801 1967
CR-123794 May 26, 1972	Early Lunar Shelter Design and Compari-
Chemical Analysis of Outgassing Contaminants. Final Report. NAS8-28058.	son Study. Vol. 6. NAS8-20261. AiResearch Manufacturing Co.
Athens College. X72-10545	N72-75210

- CR-123802 February 1972
 Neutron Radiographic Viewing System.
 Final Report. NAS8-30070. Zenith
 Radio Corp. N72-30398
- CR-123803 July 1972 Space Vehicle Engine and Heat Shield Environment Review. NAS8-27802. Teledyne Brown Engineering.
- CR-123804 October 1971
 Dynamic Testing of a Single Degree of Freedom Strapdown Gyroscope.
 NAS12-2033. Massachusetts Inst. of Technology. N72-30583
- CR-123805 April 1972
 Study of Requirements for Assembly and Docking of Spacecraft in Earth Orbit. Vol. 1: Executive Summary.
 NAS8-27860. Grumman Aerospace Corp.
 X72-10590
- CR-123806 April 1972
 Study of Requirements for Assembly and Docking of Spacecraft in Earth Orbit. Vol. 3: Simulation Plan.
 NAS8-27860. Grumman Aerospace Corp.
 X72-10579
- CR-123807 March 1972 Study of Requirements for Assembly and Docking of Spacecraft in Earth Orbit. Vol. 4: Appendices. NAS8-27860. Grumman Aerospace Corp.
- CR-123810 May 24, 1972
 Aeronautical Noise Suppression at Transonic Mach Numbers. Final Report.
 NAS8-27503. Chrysler Corp. N72-30245

- Precision Star-Tracking Telescope.
 NAS8-25705. Stanford University.
 N72-30390
- CR-123812 July 1972 Air Data Measurement System for Space Shuttle. NAS8-26326. Honeywell, Inc. N72-30863
- CR-123813 June 1972
 Thermal Support for Space Shuttle.
 Interim Final Report. NAS8-25569.
 Lockheed Missiles and Space Co.

 N72-31876
- CR-123814 March 5, 1971

 Development of Optimized Techniques and Requirements for Computer Enhancement of Structural Weld Radiographs. Vol. 1: Technical Report. ESL, Inc. N72-32490
- CR-123815 November 30, 1971 Survey, Analysis and Evaluation Test on High Voltage/Current Pulse Transmission Cables. NAS8-21298. General Laboratory Associates, Inc. N72-32221
- CR-123816 May 15, 1972
 Research Study on Stellar X-Ray
 Imaging Experiment. Vol. 2.
 NAS8-24385. American Science and
 Engineering, Inc.
- CR-123817 August 15, 1972
 Optimal Braking Studies. Final Summary
 Report. NAS8-28230. University. of
 Missouri. N72-31279

- CR-123818 1972
 Television Broadcast Satellite Systems.
 Vol. 1. NAS8-24878. Auburn University.
 N72-31176
- CR-123819 January 21, 1972 Microstrip Technology and Its Application to Phased Array Compensation. NAS8-25894. University of Alabama.

N73-11222

- Phased Array Antenna Matching Simulation and Optimization of a Planar Phased Array of Circular Waveguide Elements. Final Report. NAS8-25894. University of Alabama. N73-11139
- CR-123821 June 30, 1972
 Study of Uncertainties of Predicting
 Space Shuttle Thermal Environment.
 NAS8-26699. McDonnell Douglas Astronautics Co.
 X72-10592
- CR-123822 January 1972 Manned Space Flight Nuclear System Safety. Vol. 1; Part 2. NAS8-26283. General Electric Co. N72-33843
- CR-123823 October 1, 1963
 Apollo Study Report. Vol. 2.
 NAS8-5276. IBM Corp. N72-75111
- CR-123824 October 1, 1963
 Apollo Study Report. Vol. 1.
 NAS8-5296. IBM Corp. N72-75110
- CR-123825 April 1972
 Investigate Optimum Way of Adding
 Wideband Capability and Recommend a
 Design for Modification of One

- Government Furnished AM Baseband Demultiplexer, Phase 1. NAS8-29039. Martin Marietta Corp. N73-32172
- CR-123826 August 8, 1972 Space LOX Vent System. NAS8-26972. General Dynamics. N72-32844
- CR-123827 June 1972
 Materials Data Handbook: Aluminum
 Alloy 5456. NAS8-26644. Western
 Applied Research and Development, Inc.
 N72-30457
- CR-123828 June 1972
 Development of Lightweight Material
 Composites to Insulate Cryogenic Tanks
 for 30-Day Storage in Outer Space. Final
 Report. NAS8-26006. McDonnell
 Douglas Astronautics Co. N72-30495
- CR-123829 June 30, 1972
 Properties of Materials in High Pressure
 Hydrogen at Room and Elevated
 Temperatures. NAS8-26191. Pratt and
 Whitney Aircraft. N72-32145
- CR-123830 March 31, 1972 Study of Dense Aluminum Plasmas. Final Report. NAS8-25055 and NAS8-26773. University of Alabama.

N72-32690

- CR-123831 April 10, 1972
 A Method of Hardware Qualification for
 Flight by Analyses Similarity and
 Integrated Testing. NAS8-21811.
 Planning Research Corp. N72-52843
- CR-123832 April 30, 1972 Study of Mission Modes and Systems

- Analysis for Lunar Exploration (MIMOSA). NAS8-20262. Lockheed Missiles and Space Co. N72-75118
- CR-123833 April 30, 1967
 Study of Mission Modes and Systems
 Analysis for Lunar Exploration
 (MIMOSA). Vol. 1. NAS8-20262.
 Lockheed Missiles and Space Co.

N72-75115

- CR-123834 April 30, 1967 Study of Mission Modes and Systems Analysis for Lunar Exploration (MIMOSA). Vol. 3. NAS8-20262. Lockheed Missiles and Space Co. N72-75117
- CR-123835 April 30, 1967 Study of Mission Modes and Systems Analysis for Lunar Exploration (MIMOSA). Vol. 2: Candidate Lunar Exploration Programs. NAS8-20262. Lockheed Missiles and Space Co.

N72-75116

- CR-123837 June 26, 1972
 Investigation of Structural Factors of
 Safety for the Space Shuttle.
 NAS8-27048. Convair Div. of General
 Dynamics. N72-32845
- CR-123838 January 1972 Manned Space Flight Nuclear System Safety. Vol. 2; Part 1. NAS8-26283. General Electric Co. N73-11695
- CR-123839 January 1972 Manned Space Flight Nuclear System Safety. Vol. 3; Part 2. NAS8-26283. General Electric Co. N73-11697

- CR-123840 June 1972
 Design, Fabrication and Delivery of an Improved Single Elastic Mobility System (ELMS). Vol. 1. NAS8-27737. Lockheed Missiles and Space Co. N72-33243
- CR-123841 July 1972
 Design, Fabrication and Delivery of an Improved Single Elastic Mobility System (ELMS). Vol. 2. NAS8-27737. Lockheed Missiles and Space Co. N72-33244
- CR-123842 January 1972
 Manned Space Flight Nuclear System.
 Vol. 1. NAS8-26283. General Electric
 Co. N73-11694
- CR-123843 January 1972
 Manned Space Flight Nuclear System
 Safety. Vol. 5; Part 2. NAS8-26283.
 General Electric Co. N73-11702
- CR-123844 January 1972 Manned Space Flight Nuclear System Safety. Vol. 3; Part 1. NAS8-26283. General Electric Co. N73-11696
- CR-123845 January 1972 Manned Space Flight Nuclear System Safety. Vol. 3; Part 2A. NAS8-26283. General Electric Co. N73-11698
- CR-123846 January 1972 Manned Space Flight Nuclear System Safety. Vol. 3; Part 3. NAS8-26283. General Electric Co. N73-11699
- CR-123847 January 1972 Manned Space Flight Nuclear System Safety. Vol. 4; Part 1. NAS8-26283. General Electric Co. N73-11700

- CR-123848 January 1972
 Manned Space Flight Nuclear System
 Safety. Vol. 5; Part 1. NAS8-26283.
 General Electric Co. N73-11701

 CR-123849 January 1972
- CR-123849 January 1972 Manned Space Flight Nuclear System Safety. Vol. 6. NAS8-26283. General Electric Co. N73-11703
- CR-123850 January 1972 Manned Space Flight Nuclear System Safety. Vol. 7; Part 1. NAS8-26283. General Electric Co. N73-11704
- CR-123851 March 1973
 Space Shuttle Results of Investigations on a 0.0405 Scale Model PRR Version of the NRSSV Orbiter in the North American Aeronautical Laboratory Low Speed Wind Tunnel. NAS9-13247. Chrysler Corp. N73-21829
- CR-123901 February 8, 1967
 Early Lunar Shelter Design and Comparison Study. NAS8-20261. AiResearch Mfg. Co. N72-75858
- CR-123902 June 28, 1968
 Orbital Astronomy Support Facility
 (OASF) Study. Vol. 3; Book 1.
 NAS8-21023. McDonnell Douglas Astronautics Co. N72-75710
- CR-123903 February 1966
 Saturn IB/V Instrument Unit Switch
 Selector, Model 2. NAS8-14000. IBM
 Corp. N72-75854
- CR-123904 June 1, 1966 Saturn IB/V Instrument Unit

- Instrumentation System Description. NAS8-14000. IBM Corp. N73-70013
- CR-123905 August 1972
 Auxiliary Engine Digital Interface Unit
 (DIU). NAS8-27323. Electronic Communications, Inc. N72-33231
- CR-123906 July 1972
 Power Supply Standardization and Optimization Study. NAS8-27798. Teledyne Brown Engineering. N72-33055
- CR-123907 June 1972 Space Vehicle Electrical Power Processing Distribution and Control Study. Final Report. Vol. 1: Summary. NAS8-26270. TRW Systems. N72-33053
- CR-123908 June 1972
 Space Vehicle Electrical Power Processing Distribution and Control Study.
 Technical Report. Vol. 2. NAS8-26270.
 TRW Systems. N72-33054
- CR-123909 1972
 Television Broadcast Relay System.
 Vol. 2. NAS8-24818. Auburn University.
 N73-10214
- CR-123910 July 1, 1972
 A Preliminary Design Study for a Cosmic
 X-Ray Spectrometer. NAS8-24585.
 Massachusetts Inst. of Technology.

N72-33378

CR-123911 September 15, 1972
Analysis of Requirements for Computer
Control ADN Data Processing Experiment Subsystems. NAS8-25471. System
Development Corp. N73-10232

- CR-123912 June 30, 1972
 Study of Structural Active Cooling and
 Heat Sink Systems for Space Shuttle.
 NAS8-27708. McDonnell Douglas Astronautics Co.
 N73-10884
- CR-123913 August 1972
 Analysis of Propellant Feeding
 Dynamics. NAS8-25919. Southwest
 Research Inst. N73-11785
- CR-123914 September 1972
 Application of Engineering Cost
 Analysis. Vol. 1. NAS8-21823. Planning
 Research Corp. X72-82252
- CR-123915 September 1972
 Application of Engineering Cost
 Analysis. Vol. 6. NAS8-21823. Planning
 Research Corp. X72-82254
- CR-123916 September 1972
 Application of Engineering Cost
 Analysis. Vol. 5. NAS8-21823. Planning
 Research Corp. X72-82253
- CR-123917 August 31, 1972 Magnitude Error Bounds for Sampled Data Frequency. NAS8-21377. Mississippi State University. N73-11573
- CR-123918 July 1972
 On Charged Particle Tracks in Cellulose
 Nitrate and Lexan. NAS8-26758. San
 Francisco University. N73-11725
- CR-123919 August 23, 1972
 Development of High Temperature
 Fasteners Using Directionally Solidified
 Eutectic Alloys. NAS8-27358. United
 Aircraft Research Lab. N73-11437

CR-123920 June 24, 1972 Convectionless Electrophoretic Separation of Biological Preparations. NAS8-27797. General Electric Co.

N73-11055

CR-123921 August 1972
Feasibility of Wake Vortex Monitoring
Systems for Air Terminals. NAS8-26668.
Lockheed Missiles and Space Co.

N73-11229

- CR-123922 August 18, 1972
 Inflight Nuclear Vehicle Radiation
 Environment Study, Phase III. Final
 Report. NAS8-26811. Lockheed Missiles
 and Space Co. X73-10025
- CR-123923 April 16, 1970
 Space Shuttle Impact on Large Telescope
 Experiment Program. NAS8-21497.
 Perkin-Elmer Corp. N73-11386
- CR-123924 September 4, 1972 Long Life Valve Design Concepts. NAS8-28518. Fairchild Stratos Corp.

N72-75830

- CR-123925 August 1972
 Application of AVCO Data Analysis and
 Prediction Techniques (ADAPT) to
 Prediction of Sunspot Activity.
 NAS8-28087. AVCO Corp. N73-11811
- CR-123926 March 15, 1972 Study of Solid Rocket Motor for Space Shuttle Booster. Vol. 2; Book 2. NAS8-28430. Thiokol Chemical Corp.

- CR-123928 June 1972
 Development of Advanced Materials
 Composites for Use as Insulations for
 LH₂ Tanks. NAS8-25973. McDonnell
 Douglas Astronautics Co. N73-11547
- CR-123929 August 13, 1970
 Experiment Module Concepts Study
 Review. NAS8-25051. Convair Div. of
 General Dynamics. X72-75838
- CR-123930 January 1967
 Specified Local Scientific Survey Module
 for Apollo Applications Program.
 NAS8-20378. Lockheed Missiles and
 Space Co. X72-82680
- CR-123932 June 1972
 Application of Rochrome Liquid Crystal
 Tapes for Thermographic Testing of
 Bonded Structures. NAS8-26848.
 Hoffman-LaRoche, Inc. N73-12451
- CR-123933 1969 Intermediate-20 Launch S-IC/S-IVB. NAS8-30506. The Boeing Co. X73-70129
- CR-123934 September 30, 1972
 Dual Mode Nuclear Rocket Applications
 Study. Vol. 2. NAS8-28119. TRW
 Systems Group. X73-10027
- CR-123935 September 30, 1972
 Dual Mode Nuclear Rocket Applications
 Study. Vol. 1. NAS8-28119. TRW
 Systems Group. X73-10026
- CR-123936 September 30, 1972.

 Development of Unique Wet Tantalum Slug, Tantalum Cased Capacitor.

 NAS8-27686. Aerotron, Inc. X73-10019

- CR-123937 September 1972
 Development of Explosively Bonded
 TZM Wire Reinforced Colombian Sheet
 Composites. NAS8-27277. Denver University. N73-12490
- CR-123938 July 28, 1972 Cryogenic Insulation Development. NAS8-26129. General Dynamics. N73-12606
- CR-123939 August 31, 1972 Study of Cavitating Inducer Instabilities. NAS8-27625. Pratt and Whitney Aircraft. N73-13299
- CR-123940 September 29, 1972 Evaluation of the Trash Rocket Concept. NAS8-27324. United Technology Center. X73-10053
- CR-123941 September 1972
 Analytical and Experimental Study of
 Axisymmetric Truncated Plug Nozzle
 Flow Fields. NAS8-25601. Notre Dame
 University. N73-12282
- CR-123942 October 31, 1972
 Design and Development of Pressure and Repressurization Purge System for Reusable Space Shuttle Multilayer Insulation Systems. NAS8-27419. General Dynamics. N73-12914
- CR-123943 October 1972
 Design, Processing and Testing of LSI
 Arrays For Space Station. NAS12-2207.
 RCA Corp. N73-13732
- CR-123944 July 22, 1968
 Development of Checkout Specifications
 for New Telemeter. NAS8-21205. The
 Boeing Company. N73-70345

- CR-123945 July 19, 1972

 High Temperature Insulation Materials
 for a Radiative Thermal Protection
 System. NAS8-26115. McDonnell
 Douglas Astronautics Co. N73-12957
- CR-123946 October 1972
 Purification Kinetics of Beryllium During
 Vacuum Induction Melting.
 NAS8-27891. Grumman Aerospace Corp.
 N73-13512
- CR-123947 June 1972 Study of Low Gravity Propellant Transfer. NAS8-26236. Convair Div. of General Dynamics. N73-13764
- CR-123948 September 1970 Random Experiment Program Resource Impact (REPRI) Program. NAS8-20082. Northrop Corp. N73-12174
- CR-123949 October 1972 Space Vehicle Engine and Heat Shield Environment Review. Teledyne Brown Engineering.
- CR-123950 September 1971
 Nonelastic Nuclear Reactions and
 Accompanying Gamma Radiation.
 NAS8-25534. Teledyne Brown Engineering.
- CR-123951 July 1972 Economic Analysis of Crystal Growth in Space. NAS8-27942. General Electric Co. N73-12806
- CR-123952 September 15, 1972 Space Shuttle Ascent Flight Turbulence Response. NAS8-26363. Convair Div. of General Dynamics. N73-12913

- CR-123953 January 1972
 Space Shuttle Avionics: A Redundant
 IMU On-Board Checkout and Redundancy Management System.
 NAS8-27624. Massachusetts Inst. of
 Technology. N73-12676
- CR-123954 January 21, 1972

 The Effect of Gravity Induced Free Convection Upon the Melting Phenomena of Finite Paraffin in Slab for Thermal Control. NAS8-30511. Colorado School of Mines. N73-13130
- CR-123955 September 15, 1972
 Design and Development of Polyphenylene Oxide. NAS8-27566. Convair Div. of General Dynamics. N73-14586
- CR-123956 August 1972
 Long Life High Reliability Thermal
 Control Systems Study. NAS8-26252.
 General Electric Co. N73-13950
- CR-123957 June 1972 A Comparative Analysis of Digital Baseband Signals. NAS8-20172. University of Alabama. X73-70058
- CR-123958 September 25, 1972
 Vacuum Jacketed Ducting Technology
 Investigation. NAS8-27504. Convair Div.
 of General Dynamics. X73-10022
- CR-123959 September 29, 1972
 Development and Fabrication of a
 Graphite Polyimide Box Beam.
 NAS8-24511. North American Rockwell
 Corp. N73-13923
- CR-123960 August 31, 1972 Cost Analysis of Carbon Dioxide

- Concentrators. NAS8-28377. McDonnell Douglas Astronautics Co. N73-13971
- CR-123961 September 1972 Shock Wave Oscillation Driven by Turbulent Boundary Layer Fluctuations. NAS8-26919. Wyle Labs, Inc.

N73-12281

- CR-123962 February 18, 1972
 ACS Avionics System Review.
 NAS8-26362. Lockheed Missiles and
 Space Co. N73-12449
- CR-123963 July 1972 Empirical Evaluation of Pump Inlet Compliance. NAS8-27731. Aerospace Corp. N73-13468
- CR-123964 June 1972 Prototype GaAs Bipolar Transistors. NAS8-27086. RCA Corp. X73-10018
- CR-123965 June 20, 1969 S-2-8 Static Firing. Vol. 2. Final Report. NAS7-200. North American Rockwell Corp. N73-70010
- CR-123966 September 10, 1972
 Development and Characterization of
 Lubricants. NAS8-25318. Hughes Aircraft Co. N73-13654
- CR-123967 November 1972
 Design of a Contaminate Control
 Subsystem and Study of Checkout
 Controls and Instrumentation for Integrated Water and Oxygen Recovery.
 NAS8-27690. Hamilton Standard Div. of
 United Aircraft Corp. X73-10080

- CR-123968 June September 1972
 Development of Techniques and Associated Instrumentation for High Temperature Emissivity Measurements. Quarterly Progress Report. NAS8-26304. Lockheed Missiles and Space Co. N73-13421
- CR-123969 May 1972
 A Study of Thermal Expansion Characteristics of Ceramic Chip Capacitors and Alumina Substrates. NAS8-28571.
 Vanderbilt University. X73-10092
- CR-123970 November 1972
 Evaluation of Absorption Cycle for Space Station Environmental Control System. NAS8-25986. Lockheed Missiles and Space Co. N73-14859
- CR-123971 August 1972
 Degradation and Reuse of RadiativeThermal-Protection-System Materials for the Space Shuttle. NAS8-26205. Battelle Memorial Inst. X73-10097
- CR-123972 October 1972
 Preparative Electrophoresis Experiment
 Design. NAS8-28474. Beckman Instruments, Inc. N73-14090
- CR-123974 February 1966 Saturn S-2 Derivatives. NAS8-20265. North American Aviation, Inc.

X73-70362

CR-123975 October 15, 1972
Apollo/Saturn 5 Postflight Lunar Impact
Trajectory AS-511 S-4B/IU. NAS8-5608.
The Boeing Co. N73-14826

- CR-123976 September 3, 1970
 Nuclear Shuttle System Definition
 Study, Phase 3. NAS8-24715. Lockheed
 Missiles and Space Co. X73-70153
- CR-123977 May 19, 1970
 Nuclear Flight Systems Definition Study:
 Final Briefing. NAS8-24715. Lockheed
 Missiles and Space Co. X73-70154
- CR-123978 October 6, 1969
 Nuclear Flight Systems Definition Study:
 First Interim Briefing. NAS8-24715.
 Lockheed Missiles and Space Co.

X73-70371

- CR-123979 December 16, 1970
 Nuclear Shuttle System Definition
 Study, Phase 3. Interim Review.
 NAS8-24975. North American Rockwell
 Corp. X73-70372
- CR-123980 September 1972
 Optimal Trajectory Generation for
 Mechanical Arms. NAS8-28055. Massachusetts Inst. of Technology.

N73-14470

CR-123981 September 1971 Study to Determine Instrumentation Requirements for Fault Isolation Computer Methods. Revision 3. NAS8-26244. Lockheed Missiles and Space Co.

X71-10832

CR-123982 May 10, 1971 Study to Determine Instrumentation Requirements for Fault Isolation Computer Methods. NAS8-26244. Lockheed Missiles and Space Co.

- CR-123983 April 1, 1971
 Study to Determine Instrumentation
 Requirements for Fault Isolation Computer Methods. NAS8-26244. Lockheed
 Missiles and Space Co. X71-10892
- CR-123984 March 23, 1971 Study to Determine Instrumentation Requirements for Fault Isolation Computer Methods. Revision B. NAS8-26244. Lockheed Missiles and Space Co.

X71-10950

- CR-123985 June 1970
 Study to Determine Instrumentation
 Requirements for Fault Isolation Computer Methods. NAS8-26244. Lockheed
 Missiles and Space Co. X71-10949
- CR-123986 March 1971
 Study to Determine Instrumentation
 Requirements for Fault Isolation Computer Methods. Revision 1. NAS8-26244.
 Lockheed Missiles and Space Co.

X72-10151

CR-123987 September 30, 1971
Spaceborne Computer Multi-Element
System Configuration Architecture
Refinement. Task 1 Report.
NAS8-26698. Computer Sciences Corp.
N71-37737

CR-123988 August 30, 1971
Instruction Manual for the Laboratory
Model of the Contamination System.
Final Report. NAS8-26132. Convair Div.
of General Dynamics. X72-10059

- CR-123989 October 1971
 Space Vehicle Engine and Heat Shield
 Review. NAS8-27802. Teledyne Brown
 Engineering. X72-10174
- CR-123990 October 1, 1973

 Development of a Method for Fabrication of Metallic Matrix Composites

 Shapes by Continuous Mechanical

 Process. NAS8-27010. Computer
 Sciences Corp.
- CR-123991 October 1971 Study of Bonding Methods for Flip Chip and Beam Leaded Devices. Final Report. NAS8-25615. Electronic Communications, Inc.
- CR-123992 October 1972
 Analysis of Thermal Environment in the
 Thrustor Cavity of Space Vehicles,
 Modification Number 1. University of
 Alabama.
- CR-123993 October 1972
 Evaporative Segregation in 80 Percent Ni
 20 Percent Cr and 60 Percent Fe 40
 Percent Ni Alloys. NAS8-27891.
 Grumman Aerospace Corp. N73-14562
- CR-123994 October 1, 1971
 Redesign of Ground Winds Model and
 Damper System for the Saturn 5/Dry
 Workshop Simulation. Final Report.
 NAS8-25319. Lockheed Missiles and
 Space Co. X72-10150
- CR-123995 March 17, 1971 Study to Determine Instrumentation Requirements for Fault Isolation Computer Methods. NAS8-26244. Lockheed Missiles and Space Co.

- CR-123996 August 1971
 An Experimental Study of the Launch
 Environment of a Saturn 5 Booster
 Utilizing Solid Propellant Strap-Ons.
 NAS8-20027. Cornell Aeronautical Lab,
 Inc. X71-10955
- CR-123997 October 31, 1972
 Results of a Study of Mach Number and
 Reynolds Number Effects on the Lee
 Side Vortex Flow Field Characteristics
 of an Ogive-Cylinder-Frustrum-Cylinder
 at Angles of Attack to 25 Degrees.
 NAS8-24391. Chrysler Corp.

Vol 1 N73-15307 Vol 2 N73-15308

- CR-123998 November 14, 1971
 Electron Transport and Space Shielding
 Handbook. NAS8-26753. Science Applications, Inc.
 N73-15722
- CR-123999 October 1969 Nuclear Flight System Definition, Potential Flight Test and Early Operational Payloads: Phase 1 Review. NAS8-24975. North American Rockwell Corp.

X73-71551

- CR-124000 July 1972

 Results of a Space Shuttle Plume Impingement Investigation at Stage Separation in the NASA MSFC Impulse Base Flow Facility. NAS8-HREC D225839. Lockheed Missiles and Space Co. N73-15949
- CR-124001 October 12, 1972 LOXT Mirror Design Study. NAS8-27795. American Science and Engineering, Inc. N73-19424

- CR-124002 May 2, 1972
 Technical Report Analysis and Design:
 Study of Solid Rocket Motors for a
 Solid Rocket Booster. Vol. 2, Book 1,
 Supplement 1. Final Report.
 NAS8-28429. Lockheed Propulsion Co.
 N73-16769
- CR-124003 September 24, 1972
 Development of Space Stable Thermal
 Control Coatings for Use on Large Space
 Vehicles. NAS8-26791. IIT Research
 Inst. N73-16922
- CR-124004 October 1972
 Correlation Signature of WER Soils and Snows. NAS8-26797. IIT Research Inst.
- CR-124005 August 1972
 Thermal Elastoplastic Structural Analysis of Nonmetallic Thermal Protection Systems. NAS8-27792. University of Alabama. N73-15948
- CR-124006 November 1972
 Mathematical Characterization of
 Mechanical Behavior of Porous Frictional
 Granular Media. NAS8-25102. University
 of Alabama. N73-15368
- CR-124007 October 1972

 Measurements of Electron Bremstrahlung
 Coincidence Rates at Intermediate
 Electron Energies. NAS8-27866.
 Advanced Technology Center, Inc.

N73-15723

CR-124008 June 1972
Development of Thermally Stable Phosphonitrile Elastomers for Advanced Aerospace Structures. NAS8-25184.
Horizons, Inc. N73-15593

- CR-124009 September 30, 1972 Evaluation of Beryllium for Space Shuttle Components. NAS8-27739. Lockheed Missiles and Space Co.
- CR-124010 January 28, 1970
 Nuclear Flight Stage and Payloads Study.
 NAS8-24975. North American Rockwell
 Corp. X73-71552
- CR-124011 November 8, 1972
 Discrete Device Qualification Testing,
 Part No. IN944B. Final Report.
 NAS8-27357. SCI Systems, Inc.

X73-71084

- CR-124012 October 31, 1972
 Discrete Device Evaluation Testing, Part
 No. SPC 5001. NAS8-27357. SCI
 Systems, Inc. X73-73500
- CR-124014 November 8, 1972
 Discrete Device Qualification Testing,
 Part No. 2N37320. NAS8-27357. SCI
 Systems, Inc. X73-73502
- CR-124015 November 8, 1972
 Discrete Device Qualification Testing,
 Part No. IN827A. NAS8-27357. SCI
 Systems, Inc. X73-73501
- CR-124016 October 31, 1972
 Discrete Device Evaluation Testing, Part
 No. SP4908. NAS8-27357. SCI Systems,
 Inc.
- CR-124017 November 8, 1972
 Discrete Device Qualification Testing,
 Part No. IN939A. NAS8-27357. SCI
 Systems, Inc. X73-70633

- CR-124018 November 8, 1972
 Discrete Device Qualification Testing,
 Part No. 2N2034A. NAS8-27357. SCI
 Systems, Inc. X73-73503
- CR-124019 October 1972 Improved Burn-in Test Methods Study for TTL. NAS8-28515. Martin Marietta Corp. X73-70617
- CR-124020 September 1972 Scanning Electron Microscope: Microelectronic Inspection Criteria Report. NAS8-28515. Martin Marietta Corp.
- CR-124021 June 1972
 Prototype Ultrasonic Instrument for
 Quantitative Testing. NAS8-26931. Parametrics, Inc. N73-17562
- CR-124022 May 1972 LH₂ and LO₂ Turbopump Assemblies Program. NAS8-27794. Rocketdyne Div. of North American Rockewell Corp.
- CR-124023 February 11, 1972 Space Tug Point Design Study. NAS7-200. North American Rockwell Corp.
- CR-124024 February 23, 1970
 Saturn Workshop No. 2 Alternate
 Mission: Artificial Gravity Experiment
 Study. McDonnell Douglas Astronautics
 Co. X73-71088
- CR-124025 June 6, 1972
 Modification Static Testing and Delivery
 of One Servoactuator. NAS8-27928.
 Hydraulic Research and Manufacturing
 Co. N73-20524

- CR-124026 November 28, 1972
 Multiprocessing System Study.
 NAS8-27359. M&S Computing, Inc.
 N73-16873
- CR-124027 September 12, 1972
 Design and Evaluation of an Electrohydraulic Servoactuator Using Active
 Standby Redundancy NAS8-27821.
 Bertea Corp. N73-16515
- CR-124028 June 25, 1972
 Design and Fabrication of an Experimental Image Forming Light Modulator.
 NAS8-27375. Georgia Inst. of Technology.
 X73-10122
- CR-124029 August 1965
 Contribution of Combustion Noise to
 Overall Rocket Exhaust Jet Noise.
 NAS8-11150. Ohio State University.
- CR-124030 November 1972

 A Study of Multiplex Data Bus
 Techniques for the Space Shuttle.
 NAS8-26378. SCI Systems, Inc.

N73-16874

CR-124031 October 30, 1970
Development of a Highly Reliable
Composite Board for Printed Circuitry
for Use in Space Environment.
NAS8-21424. Battelle Memorial Inst.

N72-12137

CR-124032 April 1968
Quasi-Slender Body Theory for Unsteady
Linearized Transonic Flow Past Pointed
Bodies of Revolution. NAS8-20082.
Lockheed Missiles and Space Co.

- CR-124033 February 1971
 Calculation of Stability Derivatives for Slowly Oscillating Bodies of Revolution at Mach 1.0. NAS8-20082. Lockheed Missiles and Space Co. N73-16249
- CR-124034 November 10, 1972 A Study on Teleoperator Systems Performance Requirements. Vol. 2. NAS8-27013. Matrix Corp. X73-10116
- CR-124035 November 18, 1972 A Study on Teleoperator Systems Performance Requirements. Vol. 1. NAS8-27013. Matrix Corp. X73-10115
- CR-124036 September 1972 Improvement of Screening Methods for Silicon Planar Semiconductor Devices. NAS12-2197. Philco Ford Corp.

N73-16516

CR-124037 December 5, 1971
Reliability Improvement of 1 Mil
Aluminum Wire Bonds for Semiconductors. NAS8-26636. Motorola, Inc.

N73-18469

- CR-124038 July 31, 1972
 M553 Sphere Forming and M554
 Composite Casting Experiments.
 Summary Report. NAS8-28735. Georgia
 Inst. of Technology. N73-70936
- CR-124039 August 10, 1972
 Investigation of Solidification in ZeroGravity Environment. NAS8-28734.
 University of Connecticut. N73-70935
- CR-124040 November 1972 Normal Evaporation of Binary Alloys. NAS8-27891. Grumman Aerospace Corp. N73-16558

- CR-124041 July 1972
 Airborne Electronically Steerable Phase
 Array. NAS8-25847. Texas Instruments,
 Inc. N73-18219
- CR-124042 September 1972
 Astronomy Sortie Missions Definition
 Study Vol. 1. NAS8-28144. Martin
 Marietta Corp. N73-19851
- CR-124043 September 1972
 Astronomy Sortie Missions Definition
 Study. Vol. 2; Book 1. NAS8-28144.
 Martin Marietta Corp. N73-18842
- CR-124044 September 1972
 Astronomy Sortie Missions Definition
 Study. Vol. 3, Book 2, Appendix.
 NAS8-28144.
- CR-124045 September 1972
 Astronomy Sortie Missions Definition
 Study. Vol. 2, Book 2, Appendix.
 NAS8-28144. Martin Marietta Corp.

- CR-124046 September 1972
 Astronomy Sortie Missions Definition
 Study. Vol. 4. NAS8-28144. Martin
 Marietta Corp.
- CR-124047 September 1972
 Astronomy Sortie Missions Definition
 Study Book 1. NAS8-28144. Martin
 Marietta Corp.
- CR-124048 March 15, 1972
 Detection of Aircraft Trailing Vortices
 Using Laser Doppler Instrumentation.
 Final Report. NAS8-30514. Raytheon
 Co. X73-10167

- CR-124049
 Flight Mechanics Analysis of the AS-205/CSM-101. NAS8-4016. Chrysler Corp.
- CR-124050 March 1972
 Control System Optimization Studies.
 Vol. 1. NAS8-30515. Lockheed Missiles and Space Co. N73-18860
- CR-124051 March 1972
 Control System Optimization Studies.
 Vol. 2. NAS8-30515. Lockheed Missiles and Space Co. N73-18861
- CR-124052 November 1971
 Design Improvement Qualification
 Testing Purge and Vent Investigations,
 Fabrication and Documentation of a
 GAC-9 Insulation System. NAS8-26091.
 Goodyear Aerospace Corp. N73-18565
- CR-124053 August 4, 1972
 Improvement of Reusable Surface Insulation (RSI) Materials. Final Report.
 NAS8-27688. McDonnell Douglas Astronautics Co.
 N73-17646
- CR-124054 April 30, 1967 MIMOSA: Study of Mission Modes and System Analysis for Lunar Exploration. Final Report. NAS8-20262. Lockheed Missiles and Space Co. N73-71700
- CR-124055 March 1972 Study on Propellant Dynamics During Docking. Final Report. NAS8-25712. Lockheed Missiles and Space Co.

N73-18268

CR-124056 December 12, 1972 System for Measuring Turbine Blade Temperatures. NAS8-28952. Kollsman Instrument Corp. N73-17805

CR-124057 April 12, 1972 Space Tug Aerobraking Study. NAS8-27501. The Boeing Co.

- CR-124058 December 1972
 Convection Phenomena in Electrophoresis Separation. NAS8-27015. Lockheed Missiles and Space Co. X73-10120
- CR-124059 December 1972 Conceptual Design Study for a Teleoperator Visual System. NAS8-29024. Martin Marietta Corp. N73-17117
- CR-124060 August 1972 A Millimeter Wave Mixer. NAS8-28295. Westinghouse Electric Corp. N73-17581
- CR-124061 January 31, 1972
 Phenomena After Meteoroid Penetration
 of a Bumper Plant. NAS8-26773.
 University of Alabama. N73-17894
- CR-124062 January 1973
 Theory of Zone Radiometry.
 NAS8-28089. Lockheed Missiles and
 Space Co. N73-17555
- CR-124063

 The Development of a Residential Heating and Cooling System Using NASA

 NASA Derived Technology.

 NAS8-24986. Lockheed Missiles and Space Co.

 N73-17911

CR-124064 September 30, 1968
Preliminary AS-503 C' Mission Launch
Vehicle Operational Trajectory: Basic
Mission. NAS8-5608. The Boeing Co.

N73-71300

CR-124065 December 1972
Investigation of Crystal Growth in Zero
Gravity Environment and Investigation
of Metallic Whiskers. NAS8-24512 and
NAS8-26793. University of Alabama.

N73-17778

- CR-124066 July 12, 1972
 Space Shuttle Attitude Control System
 (ACS) Thruster Penetration Heating.
 NAS8-27683. Convair Div. of General
 Dynamics. X73-10209
- CR-124067 May 1972
 Preparation of Pigments for Space-Stable
 Thermal Control Coatings. NAS8-21317.
 Ohio State University. N73-18144
- CR-124068 July 30, 1969
 Saturn 5 AS-507 Launch Vehicle
 Operational Abort and Malfunctioned
 Flight Analysis. The Boeing Co.
- CR-124069 February 1972 Kinetic Theory Analysis of Rarefied Gas Flow Through Finite Length Slots. NAS8-21432. University of California.

N73-18265

CR-124070 April 1972
Study of Propellant Dynamics in a
Shuttle Type Launch Vehicle.
NAS8-27012. Lockheed Missiles and
Space Co. N73-17801

CR-124071 December 1972
The Response of the Thermosphere Due to a Geomagnetic Storm; A MHD Model.
NAS8-25750. University of Alabama.

N73-17498

CR-124072 December 12, 1972
Analytical Study of Spacecraft Deposition Contamination. NAS8-28533.
Teledyne Brown Engineering.

N73-17645

- CR-124073 November 22, 1972 Study of Large Flexible Tunnel for Shuttle Payload Interface. NAS8-28951. Goodyear Aerospace Corp. N73-17879
- CR-124074
 Development of High Temperature Heat
 Radiation Resistant Silicon Semiconductors. NAS8-25917. Solitron Devices,
 Inc.
 N73-17777
- CR-124075 February 1973
 Isogrid Design Handbook. NAS8-28619.
 McDonnell Douglas Astronautics Co.
 N73-19911

CR-124076

Study of Techniques for Reduction of Creep in Plated Wire Memories. Reports 1, 2 and 3. NAS8-21151. Honeywell, Inc.

CR-124077 November 15, 1972
Re-Entry Guidance Scheme Development and Analysis. Vol. 1. NAS8-28612. IBM Corp. X73-10177

- CR-124078 November 15, 1972 Re-Entry Guidance Scheme Development and Analysis. Vol. 2. NAS8-28612. IBM Corp. X73-10178
- CR-124079 December 1972
 Acoustic Fatigue and Sound Transmission Characteristics of a RAM
 Composite Panel Design. NAS8-29146.
 Wyle Labs, Inc. N73-22529
- CR-124080 February 1972
 Environmental Impact Statement for SRM Boosters in Conjunction With the Space Booster Program. NAS8-28429.
 Lockheed Missiles and Space Co.
- CR-124081 November 1, 1972
 An Investigation of a Movable Mass
 Attitude Stabilization System for Artificial G Space. NAS8-27952. University of Louisville. N73-17880
- CR-124082 October 1972
 Studies Relating to FM Television and
 Telemetry Transmitters. NAS8-26193.
 Auburn University. N73-18171
- CR-124083 November 1972 Optical Memory Development. Vol. 2. NAS8-26808. RCA Corp. N73-18681
- CR-124084 November 1972 Optical Memory Development. Vol. 1. NAS8-26808. RCA Corp. N73-18680
- CR-124085 November 1972 Optical Memory Development. Vol. 3. NAS8-26808. RCA Corp. N73-18682

- CR-124086 January 1973
 Mathematical Representations of Turbulent Mixing. NAS8-28089. Lockheed
 Missiles and Space Co. N73-18267
- CR-124087 December 8, 1972
 Multivariable Control Theory Applied to
 Hierarchical Attitude Control for Planetary Spacecraft. NAS8-27827. Auburn
 University. N73-18859
- CR-124088 September 2, 1970
 Nuclear Shuttle System Definition,
 Study Phase 3. NAS8-24975. North
 American Rockwell Corp. X73-72274
- CR-124089 December 31, 1972
 Design and Fabrication of an Engineering
 Model Fiber Optics Detector.
 NAS8-28215. Georgia Inst. of
 Technology. N73-18683
- CR-124090 December 31, 1972
 Summary of Results of Parametric
 Studies of Space Shuttle Booster, Orbiter
 and Launch Vehicles Concepts.
 NAS8-26370. Lockheed Missiles and
 Space Co. N73-18862
- CR-124091 June 30, 1971 Single Stage Earth Orbital Reusable Vehicle. NAS8-26341. Chrysler Corp. N73-18858
- CR-124092 June 30, 1971 Single-Stage Earth Orbital Reusable Vehicle Space Shuttle Feasibility Study. Vol. 5. NAS8-26341. Chrysler Corp. X73-10183

- CR-124093 January 1973 Study of High Altitude Plume Impingement. NAS8-38057. Lockheed Missiles and Space Co. N73-19940
- CR-124094 December 1972
 Directional Solidification of Eutectic
 Composites in Space Environment.
 NAS8-26402. University of California.
 N73-18527
- CR-124095 February 21, 1973
 Correlation of Materials Properties with the Atomic Density Concept. Report 5 for 27 December, 1972 21 February, 1973. NAS8-28517. Nevada Engineering and Technology Corp. N73-18156
- CR-124096 February 27, 1972
 Development of Beryllium Honeycomb
 Sandwich Composite for Structural and
 Other Related Applications.
 NAS8-21215. International Harvester Co.
- CR-124097 November 19, 1972 Study of Mathematical Modeling of Communication Systems Transponders and Receivers. NAS8-28148. Georgia Inst. of Technology. N73-18172
- CR-124098 December 15, 1972
 Cost Analysis of Water Recovery System.
 NAS8-28377. McDonnell Douglas Astronautics Co.
 N73-18134
- CR-124099 1971

 Power-On Base Pressure for Space
 Shuttle Launch Configurations. Final
 Report. NAS8-26466. Lockheed Missiles
 and Space Co. X73-72260

- CR-124100 August 1968
 Structure of Shock Waves with Nonequilibrium Radiation and Ionization. Final Report. NGR-15-005-063. Purdue University. N73-71889
- CR-124101 1972
 Centrifugal Shower Separator of the Orbital Workshop Habitability Support System. NAS8-27927. Hamilton Standard Div. of United Aircraft Corp.
- CR-124102 May 1972
 Generation and Application of the Equations of Condition for High Order Runge-Kutta Methods. NAS8-27931.
 University of Texas.
- CR-124103 November 14, 1972
 Eutectic Experiment Development for Space Processing. NAS8-21905. Westinghouse Research Lab. N73-18526
- CR-124104 January 18, 1973
 Extended Definition Feasibility Study
 for a Solar Electric Propulsion Stage.
 Vol. 3. NAS8-27360. North American
 Rockwell Corp. X73-10174
- CR-124105 January 18, 1973
 Extended Definition Feasibility Study
 for a Solar Electric Propulsion Stage.
 Vol. 1. NAS8-27360. North American
 Rockwell Corp. X73-10173
- CR-124106 November 1972
 Development of Techniques and Instrumentation for the Nondestructive Evaluation of Multilayer Insulation.
 NAS8-27479. Battle Pacific Northwest Lab.
 N73-18567

CR-124107 January 1973
A Study of Methods for Lowering Aerial
Environmental Survey Cost.
NAS8-29074. SCI Systems, Inc.

N73-18369

CR-124108 February 1973
Shuttle Free-Flying Teleoperator System
Experiment Definition. Vol. 1.
NAS8-29153. Bell Aerospace Co.

X73-10162

CR-124109 February 1973
Shuttle Free-Flying Teleoperator System
Experiment Definition. Vol. 2.
NAS8-29153. Bell Aerospace Co.

X73-10163

- CR-124110 July 24, 1972 Time Exposure Studies on Stress Corrosion Cracking of Aluminum 2014-T6, Aluminum 7075-T651, and Titanium 6Al-4V. NGR-19-011-009. N73-18525 Grambling College.
- CR-124111 January 20, 1972

 The Study and Development of an Active Scattering Particle Size Spectrometer for Space Environments.

 NAS8-28297 Particle Measuring Systems.

 N73-19425
- CR-124112 July 1968 Sound Wave Shear Wave Interaction with Oblique Shock Fronts. NGR-15-005-056. Purdue University.
- CR-124113 June 30, 1972
 Combined Loading Criteria Influence on
 Structural Performance. NAS8-26916.
 General Dynamics. N73-20874

CR-124114 February 15, 1973 Characteristics of a Gelled Liquid Hydrogen Polyphenylene Oxide PPO Foam Open Cell Insulation System. NAS8-27203. General Dynamics.

N73-18568

- CR-124115 October 1972
 Protective Overlay for Low Power TTL
 Integrated Circuits. NAS8-20896. Texas
 Instruments, Inc. X73-10166
- CR-124116 December 1, 1971
 Development of a Plan for Automating
 Integrated Circuit Processing.
 NAS8-26909. Motorola, Inc. N73-18465
- CR-124117 December 20, 1972 Switch, Toggle, Hermetically Sealed. Final Technical Progress Report. NAS8-27441. McGraw-Edison Co.

X73-10165

- CR-124118 June 1968
 Stored Program Concepts for Analog
 Computers. Final Report. NAS8-21228.
 Electronic Associates, Inc. N73-72024
- CR-124119 December 1972
 Electromagnetic Radiation Screening of
 Semiconductor Devices for Long Life
 Applications. NAS8-28937. Hughes
 Aircraft Co. N73-18757
- CR-124120 January 10, 1973
 Optimum Mission Profile Designs: Documentation of Programs POPS.
 NAS8-28146. Martin Marietta Corp.
 X73-10179

- CR-124121 November 14, 1969
 S-2 Terminal Stage Analysis Dry
 Workshop Launch Vehicle. Final Report.
 NAS7-200. North American Rockwell
 Corp. X73-72809
- CR-124122 September 1966
 Welding Commercial Base-Plate Investigation. Final Report. NAS8-20303.
 Battelle Memorial Inst.
- CR-124123 July 14, 1972
 Design, Manufacture and Install Sample
 Holder in X-Ray Reflectometer and
 Perform Data Analysis of Results.
 NAS8-27605. Visidyne, Inc.
- CR-124124 December 1972
 Automated Design and Optimization of
 Flexible Booster Autopilots via Linear
 Programming. Vol. 1. NAS8-28482.
 Martin Marietta Corp. N73-19621
- CR-124125 December 1972
 Automated Design and Optimization of
 Flexible Booster Autopilots via Linear
 Programming. Vol. 2. NAS8-28482.
 Martin Marietta Corp. N73-19622
- CR-124126 June 30, 1970
 Analysis of Strapdown Sensor Testing,
 Phase II. NAS12-678. The Analytic
 Sciences Corp. N73-19641
- CR-124127 December 1972
 Prototype Data Terminal Multiplexer
 Demultiplexer. NAS8-27538. Martin
 Marietta Corp. N73-19203
- CR-124128 February 15, 1972 Advanced Technical Studies. NAS7-200. North American Rockwell Corp.

- CR-124129 August 9, 1972 Apollo/Saturn 5 Postflight Trajectory AS-511. NAS8-5608. The Boeing Co. N73-72531
- CR-124130 1972

 Analytical Treatment of Gas Flows
 Through Multilayer Insulation, Project 1.
 University of Alabama. N73-19281
- CR-124131 January 1973
 Mass Transport Contamination Study.
 NAS8-26554. Lockheed Missiles and
 Space Co. N73-20875
- CR-124132
 Inert Gas Weldment Effects Study,
 Phase 1; July 1965 November 1965.
 NAS8-20168. The Boeing Co.
- CR-124133 January 10, 1973

 Metrication Study for Large Space
 Telescope. NAS8-29318. Battelle
 Memorial Inst. N73-19426
- CR-124134 December 22, 1972
 Electromagnetic Free Suspension System
 for Space Manufacturing. NAS8-27228.
 General Electric Co. N73-20522
- CR-124135 January 19, 1973 Design, Fabrication, Testing and Delivery of a Prototype Self Locking Actuator. NAS8-28247. Aerojet Liquid Rocket Co. N73-19459
- CR-124136 December 1972
 Definition of Experiments and Instruments for a Communications/Navigation
 Research Laboratory. Vol. 1.
 NAS8-27540. TRW Systems Group.
 N73-20273

CR-124137 CR-124144 May 1972 May 1972 Definition of Experiments and Instru-Space Tug Economic Analysis Study. ments for a Communications/Navigation Vol. 2; Part 2. NAS8-27709. Lockheed Research Laboratory. Vol. 2. Missiles and Space Co. N73-20901 NAS8-27540. TRW Systems Group. N73-20274 CR-124145 May 15, 1970 Ground Wind and Wind Tunnel Velocity CR-124138 July 1972 Measurements. Vol. 1. NAS8-21293. Definition of Experiments and Instru-Raytheon Co. X73-73553 ments for a Communications/Navigation Vol. 3. CR-124146 Laboratory. May 1972 NAS8-27540. TRW Systems Group. Space Tug Economic Analysis Study. N73-20275 Vol. 2: Appendix. NAS8-27709. Lockheed Missiles and Space Co. N73-20902 CR-124139 October 1972 Definition of Experiments and Instru-CR-124147 May 1972 ments for a Communications/Navigation Space Tug Economic Analysis Study. Research Vol. 4. Vol. 3. NAS8-27709. Lockheed Missiles Laboratory. and Space Co. NAS8-27540. TRW Systems Group. N73-20903 N73-19268 CR-124148 May 1972 CR-124140 March 1972 Space Tug Economic Analysis Study (U). Lubrication Handbook for Use in the Vol. 3; Copy S-3. Secret. NAS8-27709. Space Industry. NAS8-27662. Midwest Lockheed Missiles and Space Co. Research Inst. X73-73512 X73-75494 CR-124149 November 27, 1972 CR-124141 September 15, 1972 to Determine the Vacuum S-IC Stage Vertical Internal Access Ultraviolet Degradation Rate of Thermal Equipment Technical Manual. NAS8-5608. The Boeing Co. N73-72063 Coatings. NAS8-28765. IIT Control Research Inst. N73-20608 CR-124142 June 1972 CR-124150 October 31, 1972 Space Tug Economic Analysis Study. Cybernetic Integration of Experiments Vol. 1. NAS8-27709. Lockheed Missiles into the CVT System. NGR-43-001-117. and Space Co. N73-20899 University of Tennessee. N73-21136 CR-124143 May 1972 CR-124151 November 1972 Space Tug Economic Analysis Study.

Multiprocessor

NAS8-28605. Intermetrics. Inc.

Architectural

Vol. 2; Part 1. NAS8-27709. Lockheed

N73-20900

Missiles and Space Co.

- CR-124152 June 30, 1971 Single Stage Earth Orbital Reusable Vehicle Space Shuttle Feasibility Study. Vol. 4: Appendix. NAS8-26341. Chrysler Corp.
- CR-124153 June 30, 1971 Single Stage Earth Orbital Reusable Vehicle Space Shuttle Feasibility Study. Vol. 3: Appendix. NAS8-26341. Chrysler Corp.
- CR-124154 January 18, 1973 Extended Definition Feasibility Study for a Solar Electric Propulsion Stage. Vol. 2; Part 1. NAS8-27360. North American Rockwell Corp. X73-10230
- CR-124155 January 18, 1973 Extended Definition Feasibility Study for a Solar Electric Propulsion Stage. Vol. 2; Part 2. NAS8-27360. North American Rockwell Corp. X73-10231
- CR-124156 November 21, 1967 Low Acceleration Space Transportation System Study. Vol. 1. NAS8-21030. General Electric Co. X73-72714
- CR-124157 January 27, 1970

 Nuclear Flight System Definition Study.

 Interim Briefing No. 2. NAS8-24714.

 McDonnell Douglas Astronautics Co.

X73-73519

CR-124158 January 15, 1968
Proposed Payload for ATM B for
Observing High Energy Celestial Sources.
NAS8-20166. Teledyne Brown Engineering.

- CR-124159 December 1972
 Mathematical Model of a Flexible Space
 Shuttle Vehicle. NAS8-25708. Honeywell, Inc. N73-20876
- CR-124160 February 28, 1973
 Investigation of Crystal Growth from Solutions. NAS8-28098. University of Alabama. X73-10228
- CR-124161 September 1972
 Dynamic Errors in a Tuned FlexureMounted Strapdown Gyro. NAS12-670.
 Analytic Science Corp. N73-20682
- CR-124162 January 26, 1973
 Further Reduction and Analysis of
 Skylab, SL-1 Ground Winds Loads Test
 Data. NAS8-28118. Baganoff Associates,
 Inc. X73-10244
- CR-124163 December 1972
 Study of the Dynamics of Orbital
 Assemblies Including Interactions with
 Geometrical Appendages, Unified Flexible Spacecraft Simulation Program
 (UFSSP) Users Manual. NAS8-26131 and
 NAS8-28169. TRW Systems Group.

X73-10298

- CR-124164 April 14, 1972 S-IC Stage Transporting and Handling. NAS8-5608. The Boeing Co. N73-72022
- CR-124165 November 1972
 Investigation of Extendable Nozzle
 Concepts. NAS8-21476. Goodyear
 Aerospace Corp. N73-20300

CR-124173 CR-124166 October 1972 June 30, 1971 Survey of Digital Filtering. NAS8-20163. Single-Stage Earth-Orbital Reusable Auburn University. N73-20256 Vehicle Space Shuttle Feasibility Study. Vol. 2. NAS8-26341. Chrysler Corp. CR-124167 November 1972 X73-10295 Detection of Lack of Fusion Using CR-124174 Additives (Phase 1). June 30, 1971 NAS8-28708. McDonnell Douglas Astro-Single-Stage Earth-Orbital Reusable nautics Co. N73-20536 Vehicle Space Shuttle Feasibility Study. Vol. 1. NAS8-26341. Chrysler Corp. CR-124168 December 1972 X73-10294 Study of the Dynamics of Orbital Assemblies Including Interactions with CR-124175 February 28, 1973 Geometrical Appendages. NAS8-26131. Cost Analysis of Oxygen Recovery TRW Systems Group. NAS8-28377. N73-20878 System. McDonnell Douglas Astronautics Co. N73-21137 CR-124169 December 1972 Study of the Dynamics of Orbital CR-124176 December 31, 1972 Assemblies Including Interactions with Evaluation of a 40 to 1 Scale Model of a Geometrical Appendages. NAS8-26131 Pressure Engine. NAS8-28899. and NAS8-28169. TRW Systems Group. Lockheed Missiles and Space Co. N73-21690 N73-20220 CR-124177 November 1972 CR-124170 December 1972 Fabrication, Study of the Dynamics of Orbital Design, Assembly Delivery of a Laboratory Prototype of a Assemblies Including Interactions with Residual Gas Analyzer. Final Report. Geometrical Appendages. NAS8-26131 and NAS8-28169. TRW Systems Group. NAS8-27877. National Research Corp. N73-21386 N73-20877 CR-124178 February 28, 1973 CR-124171 March 1, 1973 Evaluation of a High Response Electro-Design of a Modular Digital Computer hydraulic Digital Control Valve. System. NAS8-27926. Hughes Aircraft NAS8-28379. Bertea Corp. N73-20523 Co. X73-10198 CR-124179 January 1973 CR-124172 January 1973 Investigation of KC-135 Flight Samples Preparation of Composite Materials in Solidified in Near Zero Gravity. Space. NAS8-27806. General Dynamics.

N73-20609

N73-20610

NAS8-28728. Grumman Aerospace Corp.

- CR-124180 February 23, 1973
 Feasibility Study of a Solar Electric
 Propulsion Stage for Geosynchronous
 Equatorial Mission. Vol. 2; Part 2.
 NAS8-27360. North American Rockwell
 Corp. X73-10287
- CR-124181 February 23, 1973
 Feasibility Study of a Solar Electric
 Propulsion Stage for Geosynchronous
 Equatorial Mission. Vol. 2; Part 1.
 NAS8-27360. North American Rockwell
 Corp. X73-10286
- CR-124182 February 23, 1973
 Feasibility Study of a Solar Electric
 Propulsion Stage for Geosynchronous
 Equatorial Mission. Vol. 1. NAS8-27360.
 North American Rockwell Corp.

X73-10285

CR-124183 February 1973 Control of a Flexible Space Shuttle Vehicle, NAS8-25708. Honeywell, Inc.

- CR-124184 January 1973
 Types of Natural Convection in Space
 Manufacturing Processes. Summary
 Report. NAS8-25577. Lockheed Missiles
 and Space Co. X73-10208
- CR-124185 February 1973
 Nuclear Stage System Definition Study,
 Phase 4. Vol. 1. NAS8-27951. McDonnell
 Douglas Astronautics Co. X73-10279
- CR-124186 February 1973
 Nuclear Stage System Definition Study,
 Phase 4. Vol. 3. NAS8-27951. McDonnell
 Douglas Astronautics Co. X73-10281

- CR-124187 February 1973
 Nuclear Stage System Definition Study,
 Phase 4. Vol. 2. NAS8-27951. McDonnell
 Douglas Astronautics Co. X73-10280
- CR-124188 February 1973
 Nuclear Stage System Definition Study,
 Phase 4. Vol. 4. NAS8-27951. McDonnell
 Douglas Astronautics Co. X73-10282
- CR-124189 February 15, 1973
 Study of Design and Control of Remote
 Manipulators. Part 2: Vibration Considerations in Manipulator Design.
 NAS8-28055. Massachusetts Inst. of
 Technology. N73-20138
- CR-124190 February 15, 1973
 Study of Design and Control of Remote
 Manipulators. Part 4: Experiments in
 Video Camera Positioning with Regard
 to Remote Manipulation. Final Report.
 NAS8-28055. Massachusetts Inst. of
 Technology. N73-20139
- CR-124191 February 15, 1973
 Study of Design and Control of Remote
 Manipulators. Part 1: Summary and
 Conclusions. NAS8-28055. Massachusetts
 Inst. of Technology. N73-22046
- CR-124192 June 1972 LO₂ and LH₂ Turbopump Assemblies Program. NAS8-27794. Rocketdyne Div. of North American Rockwell Corp.
- CR-124193 August 1972
 Turbopumps for Cryogenic Upper Stage
 Engines. NAS8-27794. Rocketdyne Div.
 of North American Rockwell Corp.

- CR-124194 August 1972 LH₂ and LO₂ Turbopump Assemblies Program Test Plan and Facilities Review. NAS8-27794. Rocketdyne Div. of North American Rockwell Corp. N73-26476
- CR-124195 October 1972
 Turbopumps for Cryogenic Upper Stage
 Engines. NAS8-27794. Rocketdyne Div.
 of North American Rockwell Corp.
- CR-124200 January 31, 1973 Application of RL10 Engine for Space Tug Propulsion. Vol. 4. NAS8-29314. Pratt and Whitney Aircraft. X73-10289
- CR-124201 January 31, 1973 Application of RL10 Engine for Space Tug Propulsion. Vol. 3. NAS8-29314. Pratt and Whitney Aircraft. X73-10288
- CR-124202 November 1972 Space Ultrareliable Modular Computer (SUMC) Instruction Simulator. NAS8-26698. Computer Sciences Corp. N73-21194
- CR-124203 March 14, 1973
 Investigation of Empirical Damping Laws
 for the Space Shuttle. NAS8-28513.
 Applied Dynamics Research Corp.
 N73-21828
- CR-124205 November 1972 C-MOS Array Design Techniques. NAS12-2233. Advanced Technology Lab. N73-21195
- CR-124206 February 6, 1972
 Thermal Design of Composite Material
 High Temperature Attachments.
 NAS8-27041. North American Rockwell
 Corp. N73-21469

- CR-124207 March 1973
 Study of Dual Channel Infrared Spectroradiometer System. NAS8-21144.
 Rocketdyne Div. of North American
 Rockwell Corp. N73-21387
- CR-124208 March 12, 1973

 Noncontacting Devices to Indicate
 Deflection and Vibration of Turbopump
 Internal Rotating Parts. NAS8-26903.

 Battelle Memorial Inst. N73-21408
- CR-124209 March 1973
 Prediction of Shuttle Vehicle Damping
 from Component Test Results.
 NAS8-27569. Southwest Research Inst.
- CR-124210 January 1972 LOGSIM. NAS8-25621. M and S Computing, Inc.
- CR-124211 February 1973
 Establishment of Quality, Reliability and
 Design Standards for Low, Medium and
 High Power Microwave Hybrid Microcircuits. NAS8-25616. Texas Instruments, Inc. N73-22419
- CR-124212 March 21, 1973
 Study of Single Crystals of Metal Solid
 Solutions. NAS8-29077. Eagle-Picher
 Industries. N73-22476
- CR-124213 November 1972
 Design Verification Tests of New Silver
 Zinc Battery, Eagle Picher Part No.
 4368, Saturn S-IB. NAS8-27182.
 Chrysler Corp.
- CR-124214 March 1971
 Thermal Control and Heat Storage by
 Melting and Freezing. NAS8-25183.
 Lockheed Missiles and Space Co.

CR-124215 July 7, 1972 Extended Life Testing Evaluation of Complementary MOS Integrated Circuits. NAS8-25897. DCA Reliability Lab, Inc.

N73-22422

CR-124216 January 1973 Fluid and Particle Dynamic Effects in Low-g Composite Casting. NAS8-27015. Lockheed Missiles and Space Co.

X73-10283

- CR-124217 July 1971 Calibration of Propulsion Simulation Nozzles for Space Shuttle Booster and Orbiter Models for the Abort Separation Staging Experimental Program. NAS8-20082. Lockheed Missiles and Space Co. N73-22814
- CR-124218 January 1973 Ground Wind Load Forcing Functions Analysis Program. NAS8-28266. Unidev, Inc.
- CR-124219 1973 Design and Construction of a Remote Sensing Final Report. Apparatus. NGL-19-001-068. Louisiana State University. N73-22393
- CR-124220 January 31, 1973 Application of RL10 Engine for Space Tug Propulsion. Vol. 2. NAS8-29814. Pratt and Whitney Aircraft. X73-10291
- CR-124221 June 1968 Development of S-13 G. Thermal Control Coating Based on Silicate-Treated ZNO. NAS8-26751. Illinois Inst. of Technology.

CR-124222 July 1972 Development of Advanced Material Composites for Use as Internal Insulation for LH₂ Tanks (Gas Layer Concept). NAS8-25974. Martin-Marietta Corp.

- CR-124223 April 1973 Research Study on Stabilization and Control. NAS8-28584. Systems Research Lab. N73-22815
- CR-124224 March 28, 1973 Large Space Telescope Pointing and Control Study. Final Summary Volume. NAS8-29152. Bendix Corp.
- CR-124225 March 15, 1973 LED Pumped NdYAG Laser Develop-Program. Final Report. ment NAS8-27563. IBM Corp. N73-22445
- CR-124226 December 8, 1971 AS-511 Saturn 5 Launch Vehicle Operational Flight Trajectory. NAS8-5608. The Boeing Co. X73-75454
- CR-124227 March 26, 1973 Chemical **Analysis** of Outgassing Contaminants. NAS8-28058. Athens N73-22061 College.
- CR-124228 March 28, 1973 Large Space Telescope Pointing and Control Study. Summary Report. NAS8-29152. Bendix Corp.
- March 28, 1973 CR-124229 Large Space Telescope Pointing and Control Study. Technical Volume, Part 1. NAS8-29152. Bendix Corp.

- CR-124230 April 1973
 Large Space Telescope Pointing and
 Control Study. Technical Volume;
 Part II. NAS8-29152. Bendix Corp.
- CR-124231 1973 Investigation into Reversion of Polyurethane Encapsulant. NAS8-5608. The Boeing Co.
- CR-124232 April 1973
 Method for Structural Design at Elevated
 Temperatures. NAS8-28170. Lockheed
 Missiles and Space Co. N73-22851
- CR-124233 January 19, 1973 Low Speed Inducers For Cryogenic Upper Stages. NAS8-29189. Rocketdyne Corp. N73-22722
- CR-124234 April 1973
 Competitive Evaluation of Failure
 Detection Algorithms for Strapdown
 Redundant Inertial Instruments.
 NAS8-27335. TRW Systems. N73-22608
- CR-124235 December 1972
 Unified Flexible Spacecraft Simulation
 Program Generalized Control System
 Addition. NAS8-28169. TRW Systems.
 X73-10300
- CR-124236 March 15, 1972 Study of Solid Rocket Motor for Space Shuttle Booster. Vol. 1. NAS8-28430. Thiokol Chemical Corp.
- CR-124237 March 15, 1973 Study of Solid Rocket Motor for Space Shuttle Booster. Vol. 2; Book 4. NAS8-28430. Thiokol Chemical Corp. N73-24800

- CR-124238 March 15, 1972 Study of Solid Rocket Motor for Space Shuttle Booster. Vol. 3. NAS8-28430. Thiokol Chemical Corp.
- CR-124239 March 15, 1972 Study of Solid Rocket Motor for Space Shuttle Booster. Vol. 4. NAS8-28430. Thiokol Chemical Corp. N73-24802
- CR-124240 February 16, 1973
 Literature Survey for Suppression of Scattered Light in Large Space Telescopes. NAS8-27804. University of Arizona. N73-23531
- CR-124241 April 1973
 Study of Hypervelocity Meteoroid
 Impact on Orbital Space Station.
 NAS8-28473. Lockheed Missiles and
 Space Co. N73-23841
- CR-124242 March 10, 1973
 Design, Process, Development, Manufacture, Test and Evaluation of Boron Aluminum for Space Shuttle Components. NAS8-27735. McDonnell Douglas Astronautics Co. N73-23873
- CR-124243 May 7, 1970
 Evaluation of a New Penetrating
 Sporicide Potentially Useful in Spacecraft Sterilization. NAS8-20157.
 McDonnell Douglas Astronautics Co.
 N73-72894
- CR-124244 April 2, 1973
 H-Engine H7080 and H7083 Flight
 Worthiness Verification Program.
 NAS8-25156. Rocketdyne Div. of North
 American Rockwell Corp.

- CR-124245 January 23, 1972
 Brazing of Beryllium for Structural
 Applications, Compression Panel, Compression Tube. NAS8-28029. Solar Div.
 of International Harvester Co.
- CR-124246 March 1973 Digital Capacitance Measuring System.
 NAS8-27657. SCI Electronics, Inc.
 N73-24218
- CR-124247 January 31, 1973 Autonomous Target Relative Navigation. NAS8-28251. University of Tennessee.
- CR-124248 March 1973
 Geyser Characteristics of Feedline
 Configuration Having Both Vertical and
 Non-Vertical Sections. NAS8-29079.
 Martin-Marietta Corp.
- CR-124249 April 10, 1973
 Thermally Resistant Polymers for Fuel
 Tank Sealants. NAS8-21401. Monsanto
 Research Corp. N73-23635
- CR-124250 1973
 Frequency Division Multiplexer Code 04236, Serial No. 001, Phase 2. Final Report. NAS8-25987. Martin-Marietta Corp. N73-23293
- CR-124251 May 1973

 Detection of Lack of Fusion Using
 Opaque Additives, Phase II.

 NAS8-20708. McDonnell Douglas Astronautics Co.

 N73-24515
- CR-124252 April 1973
 Approach to Rapid Mission Design and Planning. NAS8-26578. Lockheed Missiles and Space Co.

- CR-124253 December 14, 1972
 Development of Continuous Forming
 and Curing Techniques for Production of
 Circular Structural Composite Shapes for
 Space Vehicle Application. NAS8-26900.
 Engineering, Inc. N73-2453N
- CR-124254
 Particle-Fluid Interaction Corrections for Flow Measurements with a Laser Doppler Flowmeter. NAS8-21397. Arizona State University. N73-23379
- CR-124255 April 17, 1973 Photoheliograph Thermal Concepts Study. Vol. 2. NAS8-28520. Itek Corp. N73-24492
- CR-124256 April 15, 1973
 Thermolectric Thin Film Thermal
 Coating Systems. NAS8-2851. Ohio
 Semitronics, Inc. N73-24935
- CR-124257 March 30, 1973 Shuttle Wind Tunnel **Tests** Space Utilizing the Ground Winds Data Reduction Device. NAS8-28611. Baganoff Associates Inc.
- CR-124258 April 1973
 Modal Analysis for Liapunov Stability of
 Rotating Elastic Bodies. NAS8-28358.
 University of California. N73-24904
- CR-124259 February 5, 1973
 Computer Program for the Load and Trajectory Analysis of Two DOF Bodies
 Connected by an Elastic Tether. User's Manual. NAS8-29144. Goodyear Aerospace Corp. N73-24903

CR-124260 December 10, 1972 Study for Identification of Beneficial Uses of Space, Phase 1. Vol. 1. NAS8-28179. General Electric Co.

- CR-124261 April 1973 Large Space Telescope Engineering Scale Model Optical Design, Phase 1. Vol. 1. NAS8-29312. Perkin-Elmer Corp.
- CR-124262 May 7, 1973 Liquid Hydrogen Turbopump Rapid Start Program. NAS8-27608. Rocketdyne Div. of North American Rockwell Corp. N73-25522
- CR-124263 February 1973

 Determination of the Distribution of Sound Source Intensities in Subsonic and Supersonic Jets. NAS8-27011. IIT Research Inst.
- CR-124264 November 15, 1965 LVDC Equation Defining Document for the AS-204 Flight Program. NAS8-14000. IBM Corp. X73-76995
- CR-124265 December 15, 1964 LVDC Equation Defining Document for the AS-201 Flight Program. NAS8-14000. IBM Corp. X73-76996
- CR-124266 May 1, 1973
 Engineering Design Manual of Parachute
 Decelerator Characteristics for Space
 Shuttle Solid Rocket Booster Recovery.
 NAS8-29144. Goodyear Aerospace Corp.
 N73-25072

- CR-124267 April 1973
 Investigate Optimum EAY of Adding
 Wideband Capability and Recommend a
 Design for Modification of One
 Government-Furnished AM Baseband
 Demultiplexer. NAS8-29039. MartinMarietta Corp. N73-25182
- CR-124268 April 17, 1973
 Photoheliograph Thermal Concepts
 Study. Vol. 1. NAS8-28520. Itek Corp.
 N73-25483
- CR-124269 April 30, 1973
 Design, Fabrication and Testing of a
 5-Hz Acoustic Exciter System.
 NAS8-29184. Applied Dynamics
 Research Corp. N73-25482
- CR-124270 March 1965

 Mission Oriented Advanced Nuclear

 System Parameters Study. Vol. 1.

 NAS8-5371. TRW Space Technology

 Lab. N73-72962
- CR-124271 April 1973
 Remote Analysis of Planetary Soils:
 X-ray Diffractometer Development.
 NAS8-27336. University of Alabama.
 N73-25879
- CR-124272 April 1973
 Dynamics and Control of Advanced
 Space Vehicles. Vol. 1. NAS8-28358.
 University of California. N73-25908
- CR-124273 April 1973
 Conceptual Design Study for a Teleoperator Visual System, Phase 2.
 NAS8-29024. Martin-Marietta Corp.
 N73-25133

- CR-124274 December 1972
 The Role of Process History, Phase Morphology and Interface Strength upon the Mechanical Properties of Dispersion Strengthened Alloys. NAS8-26007. Rensselaer Polytechnic Inst. N73-25600
- CR-124275 March 1965
 Mission Oriented Advanced Nuclear
 System Parameters Study. Vol. 3.
 NAS8-5371. TRW Space Technology
 Lab.
- CR-124276 June 30, 1972 Habitability Study, Earth Orbital Space Stations. NAS8-28362. Loewy/Snaith, Inc. N73-25132
- CR-124277 May 1973
 Experimental Investigation of Liquid
 Propellant Dynamics in a Double
 Cylindrical Tank. NAS8-28086. Southwest Research Inst. N73-25287
- CR-124278 January 1973 Monolayer Boron-Aluminum Compacted Sheet Material. NAS8-27626. Martin-Marietta Aluminum, Inc. N73-25601
- CR-124279 March 1973
 Evaluation of Forming and Manufacturing Characteristics of Boron/
 Aluminum Materials. NAS8-29081.
 Americom, Inc. N73-25523
- CR-124280 November 30, 1964
 Saturn 5 Launch Vehicle Digital Computer. Vol. 2. NAS8-11561. IBM Corp.
 N73-73084
- CR-124281 November 30, 1964 Saturn 5 Launch Vehicle Digital Computer. Vol. 1. NAS8-11561. IBM Corp. N73-73083

- CR-124282 March 5, 1965 Saturn Launch Vehicle Digital Computer and Launch Vehicle Adapter Test Equipment. Vol. 4. NAS8-11561. IBM Corp.
- CR-124283 April 1973
 Design, Fabrication, Testing and Delivery
 of Improved Beam Steering Devices.
 NAS8-26846. GTE Labs., Inc.

N73-25246

- CR-124284 March 1973
 Digital Capacitance Measuring System.
 NAS8-27657. SCI Electronics, Inc.
- CR-124285 May 1973
 Image Processing Techniques and Applications to the Earth Resources Technology Satellite Program. NAS8-28545.
 University of Alabama. N73-25910
- CR-124286 May 1973
 Active Control of Primary Mirror of an Orbiting Telescope with Thermal Excitation. NAS8-28019. University of Alabama N73-26449
- CR-124287 April 1973 Handbook on Passive Thermal Control Coatings. NAS8-25900. Teledyne Brown Engineering. N73-25969
- CR-128754 March 1973
 Hypersonic Aerodynamic Characteristics
 of the NR-ATP Orbiter, Orbiter with
 External Tank, and Ascent Configuration. NAS9-13247. Chrysler Corp.

(Available only from authors. Dates are clearance dates.)
(Only MSFC authors listed. "Co-author" indicates non-MSFC author.)

ADMIRE, JOHN R. S&E-ASTN-AAD (co-authors)

A Dynamic Transformation Method for Modal Synthesis Solution of Selected System Modes. September 19, 1972. AIAA/ASME/SAE 14th Structure Structural Dynamics/Material Conference of AIAA Dynamics Specialist Conference, Williamsburg, Virginia.

ALLEN, ROBERT V. S&E-ASTR-RMH Reliability Requirements for Thick-Film Hybrid Microcircuits. March 16, 1973. 1973 Electronic Components Conference, Washington, D.C.

ALLEN, R.V. S&E-ASTR-RMH CARUSO, S.V. S&E-ASTR-RMH (co-author)

Reliability Characterization of Capacitor Chip Bonding Techniques. March 16, 1973. International Microelectronics Symposium, San Francisco, California.

ALLEN, R.V. S&E-ASTR-RMH
GRAFF, S.M. S&E-ASTR-RMH
Environmental and Electrical Characterization of Laser Trimmed Thick-Film
Resistors. March 16, 1973. International
Microelectronics Symposium, San Francisco, California.

ANDRESSEN, C.E., JR. A&PS-DIR
Management Information System (MIS).
February 21, 1973. Short Course on
Critical Elements of Management of
Large Government/Industry Projects,
Tullahoma, Tennessee.

ATKINS, HARRY L. S&E-SSL-TE MRAZEK, W.A. PD-DIR Metrication-NASA/MSFC. December 19, 1972. American Association for the Advancement of Science (AAAS), Washington, D.C.

BALLANCE, JAMES O. PD-MP-S
DONOVAN, JARRELL PD-MP-S
Radiation Configuration Factors for
Annular Rings and Hemispherical
Sectors. October 4, 1972. Publication in
Transactions of the ASME.

BALLANCE, J.O. S&E-AERO-YS SMITH, ROBERT E. S&E-AERO-YS (co-author)

On the Effects of Atomic Oxygen During Thermospheric Density Measurements with a Cryogenic Gauge. September 20, 1972. Publication in the Journal of Geophysical Research.

BAUGHER, CHARLES R. S&E-SSL-TE Solar Radio Observations. July 20, 1972. Southeastern Regional Convention of the Astronomical League, Huntsville, Alabama.

BAXTER, DAVID K. S&E-AERO-G
BURNS, ROWLAND E. S&E-AERO-G
Singular Arc Guidance for Low Thrust
Mission Analysis. August 4, 1972. AIAA
11th Aerospace Sciences Meeting, Washington, D.C.

(Available only from authors. Dates are clearance dates.)
(Only MSFC authors listed. "Co-author" indicates non-MSFC author.)

BIANCA, C.J. S&E-ASTN-ASP
The Boron-Epoxy Bolted Joint Test
Program at MSFC. August 17, 1972.
NASA/Contractor Structural Composites
Mini-Symposium, Huntsville, Alabama.

BRANTLEY, WHIT PD-DO-E
HAMILTON, EDWARD C. PD-DO-E
LST Communication and Power Phase A
Results. October 31, 1972. LST Review
to Industry, MSFC, Alabama.

BROUSSARD, P.H. S&E-ASTR-GC
MASTIN, WILLIAM C. S&E-ASTR-GC
A Study of Remote Guidance and
Control for Planetary Surface Vehicles.
August 31, 1972. First National Conference on Remotely Manned Systems,
Pasadena, California.

BROWN, HARROLD E. S&E-ASTR-SGA (co-authors)

Failure Detection and Isolation of Redundant Inertial Systems for Space Shuttle. July 20, 1972. Fifth IFAC Symposium — Automatic Control in Space, Genoa, Italy.

BROWN, RICHARD L. SP-MI-MGR
Project Management Planning. April 2,
1973. Critical Elements in Management
of Large Government/Industry Projects
meeting, Tullahoma, Tennessee.

BUCHER, GEORGE C. AD-S How the Newcomer Adjusts to the Organization. May 9, 1973. Publication in Harvard Business Review.

BURNS, ROWLAND E. S&E-AERO-G See Baxter, David K. BUTLER, JOHN M. PD-DO-SI
LST Current Phase A Concept. October
31, 1972. LST Review to Industry,
MSFC, Alabama.

CAMP, DENNIS W. S&E-AERO-YA
FICHTL, GEORGE H. S&E-AERO-YA
Spectral Structure of Tropospheric
Vertical Temperature Profiles Over Cape
Kennedy, Florida. January 16, 1973.
Publication in the Journal of Geophysical Research.

CAMP, DENNIS W.

KAUFMAN, JOHN W.

TURNER, ROBERT E.

The Maxometer — A Peak Wind Speed Sensor. November 2, 1972. Publication in the Journal of the American Meteorological Society.

CAMPBELL, RICHARD A. S&E-ASTR-GM (co-author)

Optimal Braking Studies. August 28, 1972. Publication in IEEE Trans Vehicular Technology.

CARUSO, S.V. S&E-ASTR-RMH See Allen, R.V.

CHANG, FENG-CHENG S&E-ASTR-R An Explicity Formula for a Function of Matrix. October 20, 1972. Publication in Proceedings of the IEEE.

The Explicity Expression for LaGrange-Sylvester Interpolation Polynomial. October 31, 1972. Publication in American Mathematics Monthly.

(Available only from authors. Dates are clearance dates.)
(Only MSFC authors listed. "Co-author" indicates non-MSFC author.)

Recursive Formulas for the Partial Fraction Expansion of a Rational Function with Multiple Poles. February 8, 1973. Publication in Proceedings of the IEEE.

CHANG, FENG-CHENG S&E-ASTR-R (co-author)

Partial Fraction Expansion and Inverse LaPlace Transform of a Rational Function with Real Coefficients. June 7, 1973. 1973 Conference on Decision and Control, San Diego, California.

Depolarization of an Uncollimated Laser Beam in a Turbulent Medium. June 7, 1973. Publication in Journal of the Franklin Institute.

Design of Stepped Impedance Transformers. May 2, 1973. Publication in Journal of the Franklin Institute.

CHUBB, W.B.

LIU, T.C.

S&E-ASTR
SELTZER, SHERMAN M.

S&E-ASTR-SGA

Optimal Control of the Variable Spin
Speed CMG System to Achieve High
Accuracy Attitude Control for a Space
Vehicle. May 10, 1973. 1973 IEEE
Conference on Decision and Control, San
Diego, California.

CLIFF, WILLIAM C. S&E-AERO-AF (co-authors)

Simultaneous Comparison of Gas Turbulent Fluctuations Measured with a Laser Doppler Velocimeter and a Hot Wire Anemometer. October 10, 1972. Publication in AIAA Journal.

Correlation Between the Outer Flow and the Turbulent Production in a Boundary Layer. November 21, 1972. Publication in Physics of Fluids.

CLIFTON, K. STUART S&E-SSL-PA
Television Studies of Faint Meteors.
January 12, 1973. Publication in Journal
of Geophysical Research.

CLOTFELTER, W.N. S&E-ASTN-MER RISCH, E.R. S&E-ASTN-MER Ultrasonic Measurement of Stress in Metroliner Wheels. April 16, 1973. Nondestructive Evaluation of Materials and Structures used in Transportation, Defense, and the Power Industry, San Antonio, Texas.

COLLEY, CARL E. PD-DO-SA LST Structures Presentation. October 31, 1972. LST Review to Industry, MSFC, Alabama.

COSTES, NICHOLAS C. S&E-SSL-N (co-authors)

Terrain-Vehicle Dynamic Interaction Studies of a Mobility Concept (ELMS) for Planetary Surface Exploration. September 26, 1972. AIAA Dynamics Specialist Conference, Williamsburg, Virginia.

COSTES, NICHOLAS C. S&E-SSL-N
Regional Variations in Physical and
Mechanical Properties of Lunar Surface

(Available only from authors. Dates are clearance dates.)
(Only MSFC authors listed. "Co-author" indicates non-MSFC author.)

Regolith. January 29, 1973. Fourth Lunar Sciences Conference, Houston, Texas.

COUNTER, DUANE E. S&E-ASTR-M FAILE, GWYN C. S&E-ASTR-M (co-author)

Dynamic Passivation of a Spinning and Tumbling Satellite Using Free Flying Teleoperators. July 3, 1972. Publication in proceedings of 1st National Conference on Manipulator Systems, Pasadena, California.

CUMMINGS, ROBERT E. S&E-AERO-F (co-author)

An Unsupervised Classification Technique for Multispectral Remote Sensing Data. August 28, 1972. Eighth International Symposium on Remote Sensing of Environment, Ann Arbor, Michigan.

CURRY, J.E. S&E-ASTN-MN (co-authors)

Copolymers and Elastomers with Alternating Dioxysilphenylene and Silane Units. August 21, 1972. Publication in Journal of Applied Polymer Science.

CURRY, J.E. S&E-ASTN-MN
McKINLEY, M.D. S&E-ASTN-MN
Transient Permeation of Organic Vapors
Through Elastomeric Membranes. March
28, 1973. Publication in Journal of
Applied Polymer Science.

DALINS, ILMARS S&E-SSL-N (co-authors)

Observations of Early Arriving Seismic Signals from Apollo 16 Launch. July 20,

1972. Atmospheric Acoustics and Noise Propagation Symposium, Gaithersburg, Maryland.

Analysis of Incident and Reflected Components of Audible and Infrasonic Atmospheric Waves Generated by Saturn V Launch. July 20, 1972. Atmospheric Acoustics and Noise Propagation Symposium, Gaithersburg, Maryland.

A Study of the Effectiveness of the Standard Surface Cleaning Techniques as Applied to Ni(111), Ni(100) and Ni Sheet Using Auger Electron Spectroscope (AES). March 8, 1973. Publication in Journal of Vacuum Science and Technology.

DALINS, ILMARS S&E-SSL-N HORGAN, A.M. S&E-SSL-N

Absorption of Hydrogen, Carbon Monoxide and Oxygen on Vacuum Degassed Stainless Steel 304 at 20°C. July 20, 1972. Publication in Journal of Vacuum Science and Technology.

Chemical Shifts in the Auger Spectrum and Characteristic Loss Spectrum: Oxygen Absorption on Ni(111). July 20, 1972. Publication in Surface Science.

DARBRO, W. S&E-SSL-PM
On the Mathematics Profession. June 6,
1973. Publication in Mathematical
Monthly.

(Available only from authors. Dates are clearance dates.)
(Only MSFC authors listed. "Co-author" indicates non-MSFC author.)

DARWIN, CHARLES R. PD-DO MURPHY, JAMES T. PD-DIR Refurbishment-Module Replacement as a Means to Keep Payload Costs Down. January 30, 1973. Publication in Aeronautics and Astronautics.

DONOVAN, JARRELL PD-MP-S See Ballance, James O.

DOZIER, JAMES B. S&E-SSL-PX
Solar Astronomy on Skylab. July 26,
1972. Southeastern Regional Convention
of the Astronomical League, Huntsville,
Alabama.

EBY, P.B. S&E-SSL-N MORGAN, S.H., JR. S&E-SSL-N Corrections to the Bethe-Bloch Formula for Average Ionization Energy Loss of Relativistic Heavy Nuclei — Close Collisions. October 5, 1972. Publication in Nuclear Instruments and Methods.

EBY, PETER B. S&E-SSL-N MORGAN, S.H., JR. S&E-SSL-N PARNELL, T.A. S&E-SSL-N Calculation of Energy Loss by Highly Charged Particles and the Interpretation of Cosmic Ray Data. April 23, 1973. 13th International Cosmic Ray Conference, Denver, Colorado.

EDWARDS, THOMAS R. S&E-SSL-PA
A Mini-Midi Computer Link for a CCIS
Quadrupole RGA. November 21, 1972.
6th International Mass Spectroscopy
Conference, Edinburgh, Scotland.

Image Reproduction with Interactive Graphics. June 20, 1973. Publication in R/D Magazine.

EDWARDS, THOMAS R. S&E-SSL-PA
KNIGHT, R.D. S&E-SSL-PA
A Fast Digital Noise Filter Capable of
Locating Spectral Peaks and Shoulders.
November 21, 1972. Pittsburgh Conference on Analytical Chemistry and
Applied Spectroscopy, Cleveland, Ohio.

EDWARDS, T.R.

McCOY, J.C.

An Absolute Pressure Detecting Circuit for Automatic Protection of a Mass Spectrometer. August 21, 1972. Publication in Analytical Chemistry.

ELLSWORTH, J.D. S&E-ASTR-SGA THOMPSON, Z. S&E-ASTR-SGA (co-authors)

Identification of Comet Nucleus from Comet Coma. October 17, 1972. IEEE Region 3 Convention, Louisville, Kentucky.

Autonomous Target Relative Navigation. June 22, 1973. Publication in Navigation.

EMANUEL, GARVIN PD-MP-A
Telescope Optics. November 1, 1972.
LST Industry Briefing, MSFC, Alabama.

ENGLER, E.E. S&E-ASTN-ES
The Application of Composite Materials.
April 10, 1973. Design and Fabrication

(Available only from authors. Dates are clearance dates.)
(Only MSFC authors listed. "Co-author" indicates non-MSFC author.)

of Aerospace Structures Using Composite Materials Conference, Tullahoma, Tennessee.

ESPY, PATRICK N. S&E-SSL-PO Stress Investigation of Material Properties by Holographic Spacial Filtering Techniques. April 10, 1973. 50th Meeting of the Alabama Academy of Science, Huntsville, Alabama.

FAILE, GWYN C. S&E-ASTR-M See Counter, Duane E.

FALLS, LEE W. S&E-AERO-YT
The Beta Distribution: A Statistical
Model for World Cloud Cover. January
19, 1973. Publication in Journal of
Applied Meteorology.

FARMER, JOHN E. S&E-ASTR-SD
Private Rapid Transit (PRT) – Considerations for Control and Command
System Development. September 26,
1972. Local Group of IEEE, Huntsville,
Alabama.

FICHTL, GEORGE H. S&E-AERO-YA
Probability Distribution of Vertical
Longitudinal Shear Fluctuations. July
18, 1972. Publication in Journal of
Applied Meteorology.

See Camp, Dennis D.

FICHTL, GEORGE H. S&E-AERO-YA
KUMAR, PREM S&E-AERO-YA
The Response of a Propeller Anemometer to Turbulent Flow with the Mean

Wind Vector Perpendicular to the Axis of Rotation. March 2, 1973. Publication in International Journal of Boundary-Layer Meteorology.

FIELDS, STANLEY A. S&E-SSL-TR REYNOLDS, JOHN M. S&E-SSL-TR A Study of the Reflection of X-Rays by Optical Surfaces. March 15, 1973. Presentation and publication at the Annual Meeting and Journal of the Alabama Academy of Science, Huntsville, Alabama.

The Use of a Vacuum X-Ray Reflectometer to Determine Optical Properties of Materials. June 7, 1973. 20th National Vacuum Symposium, American Vacuum Society, New York, New York.

FISHER, R.R. S&E-ASTN-PTB (co-authors)

Aerothermodynamics of the Space Shuttle Reaction Control System. January 8, 1973. AIAA 11th Aerospace Sciences Meeting, Washington, D.C.

FLOYD, HENRY B. SL-DP
The Skylab Student Project. March 9,
1973. Tenth Space Congress, Cocoa
Beach, Florida.

FRITZ, CARL G. PD-DO-MT LST Thermal Control. October 31, 1972. LST Review to Industry, MSFC, Alabama.

FULMER, CLARENCE R. A&PS-CP-S
SHIPMAN, DAVID L. A&PS-CP-S
Autoscan: Technique for Scanning
Masses of Data to Determine Potential

(Available only from authors. Dates are clearance dates.)
(Only MSFC authors listed. "Co-author" indicates non-MSFC author.)

Areas for Detailed Analysis. October 19, 1972. AIIE Conference, Chicago, Illinois.

GARY, GILMER ALLEN S&E-SSL-TT Zodiacal Light and the Gegenschein. July 5, 1972. Southeast Regional Astronomical League Convention, Huntsville, Alabama.

GATES, DANIEL W. S&E-SSL-TT (co-author)

Atomic Density as a Parameter for Characterizing Materials. July 20, 1972. Fall Meeting of the American Ceramic Society, Ceramic-Metal Systems, Annapolis, Maryland.

Improved Zn₂TiO₄ Thermal Control Pigment. June 22, 1973. 26th Pacific Coast Meeting of the American Ceramic Society, San Francisco, California.

GODFREY, R.E. SP-MGR
Space Shuttle Booster Recovery
Planning. April 12, 1973. Aerodynamic
Deceleration System Conference, Palm
Springs, California.

GOULD, J.M. S&E-ASTR-RD
JUERGENSEN, K. S&E-ASTR-RD
The NASA Computer Aided Design and
Test System. April 13, 1973. XXV
AGARD Avionics Panel Technical Meeting on Computer Aided Design, Lyngby,
Denmark.

GRAFF, CHARLES B. S&E-ASTR-EP Space Power Systems. October 31, 1972. Louisville Section of IEEE, Louisville, Kentucky. GRAFF, S.M. S&E-ASTR-RM See Allen, R.V.

GREENWOOD, TERRY E. S&E-AERO-AT SEYMOUR, D.C. S&E-AERO-AT (co-authors)

A Study of the Plume Impingement Environment Experienced by the Booster During the Space Shuttle Nominal Staging Maneuver. August 21, 1972. AIAA/SAE 8th Joint Propulsion Specialist Conference, New Orleans, Louisiana.

GUEST, STANLEY H. S&E-AERO-AU (co-authors)

Sound Source Measurement in Air Jets using the Crossed Beam Correlation Technique. February 16, 1973. AGARD Fluid Dynamics Meeting, Belgium.

GUEST, STANLEY H. S&E-AERO-AU SLONE, ROBERT M., JR. S&E-AERO-AU Propagation of Intense Sounds Resulting from Static Testing of Large Rocket Engines and Claims of Damage Resulting Therefrom. July 20, 1972. Acoustical Society of America — National Bureau of Standards Joint Symposium, Gaithersburg, Maryland.

HAMILTON, EDWARD C. PD-DO-E See Brantley, Whit.

HARBISON, J.E. S&E-ASTN-ADL (co-author)

POGO Technology Review. July 18, 1972. Joint Army-Navy-NASA-Air Force Interagency Propulsion Committee, Langley Research Center, Hampton, Virginia.

(Available only from authors. Dates are clearance dates.)
(Only MSFC authors listed. "Co-author" indicates non-MSFC author.)

HIRSCH, O.M.

Evolution of Government Contracting and Contract Types. March 27, 1973.

Short Course on Critical Elements in Management of Large Government/ Industry Projects, Tullahoma, Tennessee.

HOCHMAIR, ERWIN S. S&E-ASTR-R Integrated P-Channel MOS Gyrator. August 28, 1972. IEEE Journal of Solid-State Circuits.

Power Gyrators. August 28, 1972. IEEE Journal of Solid-State Circuits.

A Complementary MOS Gyrator. August 31, 1972. IEEE Journal of Solid-State Circuits.

HODGES, BOBBY S&E-COMP-SD Crew/Computer Communication Techniques in Control and Checkout of Shuttle Payloads. September 5, 1972. Shuttle Payload Control and Checkout Conference, Huntington Beach, California.

Image Processing for Space Applications. February 5, 1973. IEEE Computer Society, Houston, Texas.

HODGES, BOBBY S&E-COMP-SD (co-author)

Image Data Processing for ATM Experiment S-056. October 20, 1972. AIAA Computer Conference, Huntsville, Alabama.

Techniques for Automatic Interpretation of Multispectral Imagery. October 27,

1972. Electronics Industries Association Third Annual Symposium, Washington, D.C.

Discrete Simulation of a Computer System Executive. February 20, 1973. Southeastern Regional Meeting of the Society for Computer Simulation, Orlando, Florida.

A Simulator for the Space Ultrareliable Modular Computer with Host Independence. April 10, 1973. Symposium on the Simulation of Computer Systems, Gaithersburg, Maryland.

Simulation as a Computer Design Aid. July 25, 1973. AIAA/NASA/ASTM/IES Seventh Space Simulation Conference, Los Angeles, California.

HODGES, BOBBY C. S&E-COMP-SD THOMAS, D.T. S&E-COMP-SD (co-authors)

Image Analysis Techniques Associated with Automatic Data Base Generation. January 9, 1973. AIAA Computer Network Systems Conference, Huntsville, Alabama.

Image Analysis Techniques Associated with Automatic Data Base Generation. March 19, 1973. AIAA Computer Networks Systems Conference, Huntsville, Alabama. Publication in Conference Proceedings.

HOLLAND, ROBERT L. S&E-SSL-PM Radial Step Integration of Ordinary Differential Equations. January 8, 1973.

(Available only from authors. Dates are clearance dates.)
(Only MSFC authors listed. "Co-author" indicates non-MSFC author.)

Publication in SIAM Journal on Numerical Analysis.

HOLLAND, WAYNE B. S&E-ASTN-ADL (co-author)

Skylab Experience with Apollo Docking/Latching Loads. May 22, 1973. AIAA/ASME/SAE Space Mission Planning and Execution Meeting, Denver, Colorado.

HOOVER, RICHARD B. S&E-ASTR-RPO Gravitational Collapse, Pulsars, Neutron Stars, Black Holes, and Cosmic X-Ray Astronomy. July 28, 1973. Southeastern Regional Convention of the Astronomical League, Huntsville, Alabama.

Telescopes and Techniques for Imaging Cosmic X-Ray Sources. July 28, 1972. Southeastern Regional Convention of the Astronomical League, Huntsville, Alabama.

Was the Universe Created? October 31, 1972. Publication in the Proceedings of the American Philosophical Society.

HOOVER, RICHARD B. S&E-ASTR-RPO (co-authors)

Imaging Characteristics of the Hyperbolic-Aspheric Channel of a Three-Mirror X-Ray Telescope. September 20, 1972. 1972 Fall meeting of SESAPS, Birmingham, Alabama.

HORGAN, A.M. S&E-SSL-N See Dalins, Ilmars.

JAIN, A.C. S&E-AERO-A (co-author)

Hypersonic Merged Stagnation Shock Layers Part I: Adiabatic Wall Case; Part II: Cold Wall Case. February 7, 1973. Publication in AIAA Journal.

JEX, DAVID WILLIAM S&E-SSL-PA Light Gas-Plasma Accelerator. August 28, 1972. 23rd Aeroballistics Association Congress, Vermon, France.

JOHNSTON, MARY HELEN

S&E-ASTN-MEV Influence of Gravity on Growth Orientations of Tin Single-Crystals. August 28, 1972. Publication in Journal of Crystal Growth.

JUERGENSEN, K. S&E-ASTR-RD See Gould, J.M.

KAUFMAN, JOHN W. S&E-AERO-YA See Camp, Dennis W.

KAUFMAN, JOHN W. S&E-AERO-YA
SUSKO, MICHAEL S&E-AERO-YA
The Dynamics of Exhaust Cloud Rise
and Growth Phenomena for Apollo
Saturn Engines. July 12, 1972. Publication in the Journal of Spacecraft and
Rockets.

KEY, C.F.

S&E-ASTN-M

SCHWINGHAMER, R.J.

High Pressure Oxygen Test Evaluation.

March 9, 1973. AICHE — Oxygen

Utilization Under Pressure Symposium,

New Orleans, Louisiana.

(Available only from authors. Dates are clearance dates.)
(Only MSFC authors listed. "Co-author" indicates non-MSFC author.)

KIEFLING, LARRY S&E-AERO-DDS (co-authors)

Methods and Application of System Identification in Shock and Vibration. September 20, 1972. ASME Winter Annual Meeting, New York, New York.

KLINGMAN, EDWIN E., III S&E-SSL-PA Implementation of a "Frog's Eye" Type Discriminator, Responsive Only to Pattern Changes, as a Pre-Processor for Visual Data. March 19, 1973. 19th Annual Meeting Institute of Environmental Sciences, Anaheim, California.

KNIGHT, R.D. S&E-SSL-PA See Edwards, Thomas R.

KRAUSE, FRITZ R. S&E-AERO-T Potential Remote Precipitation Surveys of Showers. January 29, 1973. National ASCE Water Resources Engineering Meeting, Washington, D.C.

> Infrared Change Detection Concepts for Remote Surveys of Local Moisture Exchange. February 7, 1973. 2nd Annual Remote Sensing of Earth Resources Conference, Tullahoma, Tennessee.

> Potential Moisture Balance Surveys of Storms. July 3, 1973. Publication in Journal of Atmospheric Sciences.

KROES, ROGER L. S&E-SSL-TR
Photoluminescence and Optical Transmission of Diffusion-Pump Oil. August
21, 1972. Publication in the Journal of the Optical Society of America.

KROES, R.L. S&E-SSL-TR LINTON, ROGER C. S&E-SSL-TR (co-author)

Optical Properties of INBI. December 19, 1972. Publication in Bulletin of the American Physical Society.

KUMAR, PREM S&E-AERO-YA
First-Order Reactant in Homogeneous
Turbulence Before the Final Period of
Decay. September 11, 1972. Publication
in the Physics of Fluids Journal.

On First-Order Reactants in Homogeneous Turbulence. September 11, 1972. Publication in Journal of Applied Mathematics and Physics.

Statistical Properties of Lateral Shear Along the Vertical. September 14, 1972. Publication in Journal of Applied Meteorology.

Statistical Properties of Vertical Shear of Lateral Velocity. March 7, 1973. Publication in Journal of Applied Meteorology.

See Fichtl, George H.

KURTZ, ROBERT L. S&E-SSL-PO
A Holographic Motion Picture Camera
Which Allows Front Surface Detail to be
Recorded in Real Time Using a
Continuous Wave Laser. January 11,
1973. Publication in Applied Optics.

Author's Reply to Comments on: Experimental Investigation of a Holographic System that Records Front

(Available only from authors. Dates are clearance dates.)
(Only MSFC authors listed. "Co-author" indicates non-MSFC author.)

Surface Detail from a Scene Moving at High Velocities. February 21, 1973. Publication in Applied Optics.

An Introduction of Several Measuring Techniques New to the Field of Nondestructive Testing. March 28, 1973. Publication in International Journal of Nondestructive Testing.

LINTON, ROGER C. S&E-SSL-TR
The Optical Properties of Zirconium
Diboride Thin Films. April 17, 1973.
Publication in Journal of Physics of Thin
Solid Films.

See Kroes, R.L.

LIU, T.C. S&E-ASTR See Chubb, W.B.

LIU, T.C. S&E-ASTR-SGA
THOMPSON, ZACK S&E-ASTR-SGA
New Scheme to Suppress Nonlinear
Limit Cycle for Space Vehicle Control.
January 16, 1973. Fifth Annual Southeastern Symposium on System Theory,
Raleigh, North Carolina.

Blending Effects for Limit Cycle Control. April 5, 1973. Twelfth Annual ISA Huntsville Conference, Huntsville, Alabama.

LOOSE, JACK D. S&E-ASTN-PTC (co-authors)

Development of a High Capacity

Variable Conductance Heat Pipe. February 7, 1973. AIAA 8th

Thermophysics Conference, Palm Springs, California.

LOVINGOOD, J.A.

RYAN, ROBERT S.

Computation of Launch Vehicle System
Requirements Using a Hybrid Computer.
February 2, 1973. 1973 Summer
Computer Simulation Conference,
Montreal, Canada.

LUCAS, WILLIAM DEP-T LST Introduction to Industry Briefing. October 31, 1972. LST Briefing to Industry, MSFC, Alabama.

MacPHERSON, J.F. S&E-ASTN-ADD (co-author)

Skylab Payload Assembly Vibroacoustic Test Program. November 9, 1972. Publication in Shock and Vibration Bulletin.

MARSHALL, WILLIAM R. PD-DO-DIR
Sortie Lab Experiment Operations.
September 14, 1972. First Conference
on Shuttle Payload Control and Checkout, Huntington Beach, California.

MASTIN, WILLIAM C. S&E-ASTR-GC See Broussard, P.H.

McCOY, J.C. S&E-COMP-SE , See Edwards, Thomas R.

McKINLEY, M.D. S&E-ASTN-MN See Curry, J.E.

(Available only from authors. Dates are clearance dates.)
(Only MSFC authors listed. "Co-author" indicates non-MSFC author.)

McPEAK, B.J. S&E-ASTR-EBC SOUTHER, C.H. S&E-ASTR-EBC Unplated Copper Hook-Up Wire. October 10, 1972. Publication in Insulation/Circuits.

MICHLOVIC, JOSEPH E. S&E-SSL-TE
Optical Tidbits. July 5, 1972. Southeastern Regional Astronomical League
Convention, Huntsville, Alabama.

MOORE, W. WALDING, JR. S&E-SSL-PO NISEN, DANIEL B. S&E-SSL-PO TASHBAR, PHILIP W. S&E-SSL-PO A Modified Quadrupole Mass Spectrometer with Custom RF Link Rods Driver for Remote Operation. October 5, 1972. Publication in Review of Scientific Instruments.

A Remote-Operation Quadrupole Mass Spectrometer Using a Custom RF Link Approach. March 6, 1973. Publication in Applied Spectroscopy.

MORGAN, Ş.H., JR. S&E-SSL-NA See Eby, P.B.

MRAZEK, W.A. PD-DIR See Atkins, Harry L.

MURPHY, JAMES T. PD-DIR See Darwin, Charles R.

NAUMANN, ROBERT J. S&E-SSL-P
Dynamics of Spacecraft Contamination.
March 10, 1972; IES-NASA AIAA/
ASTM 6th Space Simulation Conference,
New York, New York. July 11, 1972;
Submitted for publication in Journal of
Environmental Sciences.

Design Principles for Contamination Abatement in Scientific Satellites. August 2, 1972. 23rd International Astronautical Congress, Vienna, Austria.

NICHOLS, J.J. S&E-ASTN-ADS (co-authors)

Use of Generalized Mass Contributions in Correlation of Test and Analytical Vibration Modes. July 31, 1972. 43rd Shock and Vibration Symposium, Pacific Grove, California.

Skylab Modal Survey Testing. July 31, 1972. 43rd Shock and Vibration Symposium, Pacific Grove, California.

NISEN, DANIEL B. S&E-SSL-PO See Moore, W. Walding, Jr.

NYBO, LELYN W. MT-AE-E
Omega Windfinding System Designed to
Meet Accuracy Requirements of GARP
Atlantic Tropical Experiments. April 27,
1973; 8th Technical Conference on
Hurricanes and Tropical Meteorology,
Key Biscayne, Miami, Florida. July 3,
1973; Publication in the Bulletin of the
AMS.

O'DELL, C.R. PD-LST
The Large Space Telescope Program.
October 16, 1972. Publication in Sky and Telescope.

Large Space Telescope (LST). April 27, 1973. COSPAR, Konstanz, West Germany.

Nuclei of Planetary Nebulae. May 2, 1973. Extraordinary General Assembly,

(Available only from authors. Dates are clearance dates.)
(Only MSFC authors listed. "Co-author" indicates non-MSFC author.)

International Astronomical Union, Warsaw, Poland.

Control and Checkout Conference, Huntington Beach, California.

ODOM, JIM

Solid Rocket Motors for the Space
Shuttle Booster. July 14, 1972. SAE
National Aerospace Engineering and
Manufacturing Meeting, San Diego,
California.

OLIVIER, JEAN PD-LST Introduction and Summary for LST. November 1, 1972. LST Industry Briefing, Huntsville, Alabama, MSFC.

ORAN, WILLIAM A. S&E-SSL-NP
On Systems that Simulate the
Ionospheric-Satellite Interaction.
September 5, 1972. Publication in
Journal of Applied Physics.

ORAN, W.A. S&E-SSL-NP STONE, N.H. S&E-SSL-NP (co-author)

Laboratory Simulation of the Structure of Disturbed Zones Around Bodies in Space. January 29, 1973. Publication in Journal of Atmospheric and Terrestrial Physics.

ORAN, W.A.
S&E-SSL-NP
STONE, N.H.
S&E-SSL-NP
A Laboratory Simulation of the
Spacecraft-Ionospheric Plasma Interaction. March 28, 1973. American
Geophysical Union Meeting, Washington,
D.C.

ORILLION, ALFRED G. PD-SA-V Space Tug Checkout Considerations. September 14, 1972. Shuttle Payload PALUDAN, CHARLES T. N. S&E-EA-DIR The Uses of ERTS Data in Land-Use Study. April 5, 1973. Annual Meeting of the Association of Geographers, Atlanta, Georgia.

PARKHIE, MUKUND R. S&E-ASTN-SM
Hypothalamic Growth Hormone
Releasing Factor; Release and Synthesis
after Exposures to a High Ambient
Temperature. January 8, 1973. Publication in Proceedings of the Society for
Experimental Biology and Medicine.

PARKS, P.G. S&E-PE-MW (co-author)
Welding of Aluminum 2219 Alloy with M934 Filler Wire. July 3, 1973. Publication in Welding Journal.

PARNELL, T.A. S&E-SSL-NA (co-authors)

Measurements of Cosmic Ray Trajectories with a Proportional Counter Hodoscope. April 24, 1973. 13th International Cosmic Ray Conference, Denver, Colorado.

PARNELL, T.A. S&E-SSL-NA See Eby, Peter B.

PETERS, PALMER N. S&E-SSL-NP Mobility of Sulfur on a Ni(100) Surface. October 13, 1972. Southeastern Section of the American Physical Society, Birmingham, Alabama.

(Available only from authors. Dates are clearance dates.)
(Only MSFC authors listed. "Co-author" indicates non-MSFC author.)

PETERS, P.N.

S&E-SSL-NP

(co-author)

Application of Internal Reflection Spectroscopy to the Study of Spacecraft-Type Contaminants. June 20, 1973. Publication in Research and Development Magazine.

POE, JAMES W.

S&E-AERO-AU

(co-authors)

Ground Wind Loads on Skylab Launch Vehicles. September 12, 1972. AIAA/ASME/SAE 14th Structures, Structural Dynamics and Materials Conference, Williamsburg, Virginia, and AIAA Dynamics Specialist Conference, Williamsburg, Virginia.

REECE, O.Y.

S&E-ASTN-MM

(co-authors)

Shock Wave Synthesis and Characterization of NB₃SN. March 8, 1973. Publication in the Journal of Less Common Metals.

REICHMANN, EDWIN J. S&E-SSL-TE Solar Flare Brightness Distribution. July 5, 1972. Southeastern Regional Astronomical League Convention, Huntsville, Alabama.

REYNOLDS, JOHN M. S&E-SSL-TR See Fields, Stanley A.

RISCH, E.R. S&E-ASTN-MER See Clotfelter, W.N.

RUSSELL, DEAN M. S&E-SSL-PO WILLIAMS, JOHN R. S&E-SSL-PO Particle Analysis by Active Scattering

Particle Spectrometry. November 21,

1972. Instrument Society of America National Aerospace Symposium, Las Vegas, Nevada.

RYAN, ROBERT S. S&E-AERO-D See Lovingood, J.A.

SCHIEHLEN, WERNER O. S&E-ASTR-A Fine Pointing System for a LST Spacecraft. February 5, 1973. EUROMECH 38 (Gyrodynamics), Louvain-la-Neuve, Belgium.

A Fine Pointing System for Large Orbiting Telescopes. February 20, 1973. AIAA Guidance and Control Conference, Key Biscayne, Florida.

SCHOCKEN, KLAUS

The Attenuation of X Rays Emitted by
Supernovae. December 19, 1972.
Publication in Astronomy and Astrophysics.

Structure of the Crab Nebula. July 5, 1972. Southeastern Regional Astronomical League Convention, Huntsville, Alabama.

The Attenuation of X Rays from the Crab Nebula. January 8, 1973. Publication in Science.

SCHULTZ, DAVID N. PD-DO-ES
Attitude Control System/Reliability.
October 31, 1972. LST Review to
Industry, MSFC, Alabama.

SCHWINGHAMER, R.J. S&E-ASTN-M See Key, C.F.

(Available only from authors. Dates are clearance dates.)
(Only MSFC authors listed. "Co-author" indicates non-MSFC author.)

SELTZER, SHERMAN M. S&E-ASTR-A (co-authors)

Attitude Control of a Spinning Skylab. February 4, 1972; AIAA Guidance and Control Conference, Stanford, California. August 21, 1972; Publication in AIAA Journal of Spacecraft and Rockets.

Attitude Control of a Spinning Flexible Spacecraft. April 3, 1973. Publication in Automatica.

SELTZER, SHERMAN M. S&E-ASTR-A See Chubb, W.B.

SEYMOUR, D.C. S&E-AERO-AT See Greenwood, Terry E.

SHIPMAN, D.L. A&PS-CP-S
A Simulation Model for Allocating
Resources in a Project Type Environment. October 2, 1972. AIIE Conference, Huntsville, Alabama.

SHIPMAN, D.L. A&PS-CP-S See Fulmer, Clarence R.

SHRIVER, EDWARD L. S&E-SSL-PA (co-author)

Magnetogasdynamic Compression of a Coaxial Plasma Accelerator Flow for Micrometeoroid Simulation. July 7, 1972. Publication in Journal of Applied Physics.

SIEBEL, MATHIAS P. S&E-PE-DIR

Manufacturing in Space. July 3, 1972.

1972 SAE National Aerospace Engineering and Manufacturing Meeting, San Diego, California.

SIMS, JOSEPH L. S&E-AERO-AF (co-authors)

Simulation of Space Shuttle Main Propulsion System Exhaust Plumes at Ascent Trajectory Test Points. September 26, 1972. JANNAF 7th Plume Technology Meeting, Redstone Arsenal, Alabama.

An Investigation of Exhaust Plume Simulation and Its Effect on Plume Induced Boundary Layer Separation. September 26, 1972. JANNAF 7th Plume Technology Meeting, Redstone Arsenal, Alabama.

SINGH, S.P.

TRAUBOTH, H.

S&E-COMP-SA

MARSYAS – A Software System for
Digital Simulation of Large-Scale Dynamical Systems. April 10, 1973. Publication
in IEEE Circuit Theory Newsletter.

SLONE, ROBERT M., JR. S&E-AERO-AU See Guest, Stanley H.

SMITH, ORVEL E. S&E-AERO-YT
Counting Things (Analysis of Runs:
Statistical Concepts and Applications).
February 13, 1973. Alabama Chapter of the American Statistical Association,
Birmingham, Alabama.

SMITH, ROBERT E. S&E-AERO-YS (co-authors)

Long Wavelength Acoustic Modes in the Topside Ionosphere. October 27, 1972. Publication in Journal of Geophysical Research.

(Available only from authors. Dates are clearance dates.)
(Only MSFC authors listed. "Co-author" indicates non-MSFC author.)

Characteristics of Ionospheric Waves Generated by Rocket Launches. November 10, 1972. Publication in Journal of Geophysical Research.

Observational Evidence of Acoustic Waves on the Ionospheric Sounding Records. December 19, 1972. Publication in Journal of the Acoustical Society of America.

Propagation of Hydromagnetic Waves in Upper F2 Region. December 19, 1972. Publication in Planetary and Space Science.

SMITH, ROBERT E. S&E-AERO-YS See Ballance, James O.

SMITH, ROBERT E. S&E-AERO-YS
SWENSON, GARY R. S&E-AERO-YS
Ground Based OI 6300 A Doppler
Temperature Measurements During
August 4, 1972 Storm Period. September
20, 1972. American Geophysical Union,
San Francisco, California.

SNODDY, WILLIAM C. S&E-SSL-T RCAA Talk on "Real Time Solar Magnetograph." May 9, 1973. RCAA, Huntsville, Alabama.

SNYDER, R.S. S&E-ASTN-MTE
Electrophoresis Demonstration on
Apollo 16. August 11, 1972. Gordon
Conference on Separation and Purification, New London, New Hampshire.

Apollo 16 Electrophoresis. February 21, 1973. Physics Society Annual Meeting, Fredonia, New York.

Electrophoresis at Zero Gravity on Apollo 16. May 8, 1973. Publication in Science.

SOUTHER, C.H. S&E-ASTR-EBC See McPeak, B.J.

Retrieval of a Dual Description for Kinematics from Local Temporal Information. November 9, 1972. Colloquium to Physics Department, Oklahoma University, Norman, Oklahoma.

Impact of Physics on Lead Research for Land Inventories, Air Quality and Hydrological Investigations. November 9, 1972. Colloquium to Physics Department, Ft. Hays Kansas State College, Hays, Kansas.

STEPHENS, J. BRISCOE
S&E-AERO-F
ST. JOHN, R.M.
S&E-AERO-F
Recognition of Dispersion and Convection Patterns of Transport Phenomena in
Stationary and Nonstationary Fluids.
November 9, 1972. Oklahoma Academy
of Science, Weatherford, Oklahoma.

STEWART, RODNEY D. A&PS-PR-G Lecture: New Approaches in Government Cost Estimating. February 13, 1973. Short Course on Critical Elements in Management of Large Government/ Industry Projects, Tullahoma, Tennessee.

ST. JOHN, R.M. S&E-AERO-F See Stephens, J. Briscoe

STONE, N.H. S&E-SSL-NP See Oran, W.A.

(Available only from authors. Dates are clearance dates.)
(Only MSFC authors listed. "Co-author" indicates non-MSFC author.)

STUCKEY, JAMES M. S&E-ASTN-MNM (co-author)

Development and Evaluation of Graphite and Boron Polyimide Composites. September 19, 1972. 4th National SAMPE Technical Conference, Palo Alto, California.

STUHLINGER, ERNST AD-S
Space Exploration During the Next
Twenty Years. July 17, 1972. Paper
presented at the Max Planck Institute for
Extraterrestrial Physics, Munich; the
University of Tübingen, Tübingen, West
Germany; the Institute of Technology,
Stuttgart, Garmish, West Germany, and a

SUSKO, MICHAEL S&E-AERO-YA See Kaufman, John W.

high school in Stuttgart.

SWEARINGEN, C.N. S&E-ASTR-C (co-authors)

Highly Reliable Processor System for Space Application. March 6, 1973. Biennial Computer Group National Conference on Computer Network Systems, Huntsville, Alabama.

SWENSON, GARY R. S&E-AERO-YS See Smith, Robert E.

TASHBAR, PHILIP W. S&E-SSL-PO See Moore, W. Walding, Jr.

TAVASSOLI, A.A. S&E-ASTN-MM
Mechanical Properties of Columbium
Alloy SU31. July 18, 1972. Publication
in Metallurgical Transactions.

Elevated Temperature Tensile Properties of Silicide Slurry Coated Columbium Alloys. July 26, 1972. Publication in Journal of Materials.

THOMAS, D.T. S&E-COMP-SD See Hodges, Bobby.

THOMASON, H.E. SP-EM-MGR
Space Shuttle System Solid Rocket
Booster. May 22, 1973. AIAA/ASME/
SAE Space Mission Planning and
Execution Meeting, Denver, Colorado.

THOMPSON, ZACK S&E-ASTR-SGA See Chubb, W.B.; Ellsworth, J.D.; and Liu, T.C.

TRAUBOTH, H. S&E-COMP-SA MARSYAS – User's Manual. January 30, 1973. Copy of manual presented to COSMIC Library, University of Georgia, Athens, Georgia.

Real-Time Computer Systems. February 5, 1973. University of Notre Dame, Notre Dame, Indiana.

Guidelines for the Documentation of Scientific Software Systems. April 10, 1973. IEEE Symposium on Computer Software Reliability, New York, New York.

See Singh, S.P.

TRENKLE, J.J.

WILKES, D.R.

Optical Contamination
Outgassed Products

S&E-SSL-TR

S&E-SSL-TR

Figure 1

S&E-SSL-TR

S&E-SSL-TR

Figure 2

Figure 3

Figure 3

Figure 4

Figure 3

Figure 4

Figure

(Available only from authors. Dates are clearance dates.)
(Only MSFC authors listed. "Co-author" indicates non-MSFC author.)

Control Surfaces. April 2, 1973. 1973 Conference on Environmental Systems, San Diego, California.

TURNER, ROBERT E. S&E-AERO-Y. See Camp, Dennis W.

URBAN, EUGENE W. S&E-SSL-N
Magnetic Flux Annihilation in Type II
Superconductors. October 13, 1972.
Southeastern Section of the American
Physical Society, Birmingham, Alabama.

VAUGHAN, OTHA H. S&E-AERO-YE
VAUGHAN, WILLIAM W. S&E-AERO-Y
Zero-Gravity Research Potential in Cloud
Physics and Weather Modification. March
15, 1973. Publication in Bulletin of the
American Meteorological Society.

VAUGHAN, WILLIAM W. S&E-AERO-Y See Vaughan, Otha H.

VILLELLA, F. S&E-QUAL-QT (co-author)

Thermal Excursions Cause Transistor Failures. November 30, 1972. Publication in Circuits Manufacturing.

VON PRAGENAU, GEORGE L.

S&E-ASTR-A Status and Present Development of Space Vehicle Steering. August 16, 1972. Publication in Osterreichische Ingenieur

Zeitschrift.

WALLACE, G.R. S&E-ASTR-IA

Statistical Properties of Filtered Pseudorandom Digital Sequences Formed from

the Sum of Maximum Length Sequences. April 16, 1973. Transactions on IEEE, Communication Technology.

WAMSTEKER, WILLEM S&E-SSL-TE
The Wavelength Dependence of the
Albedo of Uranus and Neptune from
0.3μ to 1.1μ. April 12, 1973. Publication
in Astrophysical Journal.

WDOWIAK, THOMAS J. S&E-SSL-TE (co-author)

Photometry of Supernova 1972 in NGC 5253. August 21, 1972. Publication in Astrophysical Journal Letters.

On the Recent Supernova in NGC 5253 and the Supernova Rate. December 19, 1972. Publication in Nature.

WEAVER, LEON B. PD-DO-MC Maintenance of the Large Space Telescope. September 14, 1972. Shuttle Payload Control and Checkout Conference, Long Beach, California.

WELLS, ERNEST H. S&E-SSL-PA
Water on Mars, and Martian Blue Haze
and Flash Phenomena. July 24, 1972.
Southeast Astronomical League, Huntsville, Alabama.

WHITE, J.B., Jr. S&E-ASTR-CA
The Effect of Modularity on a
Reconfigurable Architecture for Either
Ultra-Reliability or Multiprocessing.
November 10, 1972. Publication in IEEE
Transactions on Computers.

(co-authors)

(Available only from authors. Dates are clearance dates.) (Only MSFC authors listed. "Co-author" indicates non-MSFC author.)

WILKES, D.R.

S&E-SSL-TR

ZOLLER, LOWELL K.

SP-ET-MGR

See Trenkle, J.J.

Space Shuttle External Tank. September

S&E-SSL-PO

26, 1972. AIAA Space Shuttle Short Course, Boulder, Colorado.

WILLIAMS, JOHN R. See Russell, Dean M.

97